



Transcend's SLC Mode technology is a cost-effective solution that offers performance close to that of SLC NAND flash. SLC Mode SDXC/SDHC220 UHS-I U1 Cards combine the advantages of high performance and exceptional endurance at an affordable price, making them ideal for demanding industrial applications such as POS terminals as well as portable devices equipped with an SD memory card slot.

Hardware Features

- Compliant with RoHS 2.0 standards
- Compliant with SD specification 3.01
- Compliant with UHS-I
- Electrostatic protection (ESD IEC 61000-4-2)
- Supports Transcend Scope Pro software

Firmware Features

- Supports S.M.A.R.T. function to conduct health monitoring, analysis, and reporting for storage devices
- · Early Move
- · Built-in ECC (Error Correction Code) functionality
- · Wear-Leveling

Ordering Information

16GB TS16GSDC220 32GB TS32GSDC220

^{*}Scope Pro is only available when used with the RDF5 card reader.






www.transcend-info.com

Specifications

Appearance Form Factor Flash Type Capacity Operating Volta Drop Test Operating Tem Operating Environment Dimensions Form Factor Flash Type Capacity Operating Volta Drop Test Operating Tem		24 mm x 32 mm x 2.1 mm (0.94" x 1.26" x 0.08") SD flash card
Storage Flash Type Capacity Operating Volta Drop Test Operating Tem Storage Tempor		
Capacity Operating Volta Drop Test Operating Tem Storage Temps		MI C NAND fleeb (CL C mede)
Capacity Operating Volta Drop Test Operating Tem Operating Storage Temps		MLC NAND flash (SLC mode)
Drop Test Operating Tem Storage Temps		16 GB / 32 GB
Operating Tem Storage Temps	age	2.7V ~ 3.6V
Operating Storage Temps		1.5m free fall
Storage Tempe	perature	Standard Temp. -25°C (-13°F) ~ 85°C (185°F)
	erature	-40°C (-40°F) ~ 85°C (185°F)
Humidity		0% ~ 95%
Shock		Acceleration: 490 m/s² (standard holding time: 11 ms, semi-sine wave, velocity change: 3.44 m/s)
Vibration (Ope	rating)	20 G (peak-to-peak), 20 Hz ~ 2,000 Hz (frequency)
Power Consun	nption (Max.)	2.88 watt(s)
Read Speed (N	Max.)	up to 95 MB/s
Performance Write Speed (N	Max.)	up to 80 MB/s
Terabytes Writi	ten (TBW)	up to 600 TBW
Certificate		CE / FCC / UKCA
Warranty Warranty		CE / FCC / UNCA

Mechanical Dimensions



Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment. Due to the complexity and variety of industrial applications, Transcend cannot guarantee 100% compatibility with all platforms and under all scenarios. For special applications and environments, it is strongly suggested that you contact Transcend beforehand for clarification.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660