

AI Embedded Box PCs

COMPACT AI Rugged Series

Computer Vision Edge Unit with NVIDIA Jetson Xavier NX

optional
LTE / GNSS / Wi-Fi




Image similar

Power Supply
9 ... 45VDC

CAN

2x Gbit LAN

USB 3.1

HDMI

RPC/COMPACT A3N

This fanless COMPACT A3N generation is based on the NVIDIA Jetson Xavier NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- IP67 protection
- Product lifecycle management
- Long term availability with fixed BOM

 **NVIDIA. Linux for Tegra (L4T)**

Product Highlights

- Ultra rugged
- Sealed housing, protection class IP67
- Maintenance free
- Power Ignition controller
- No moving parts / passively cooled
- Pressure equalization membrane
- Resistance to chemicals
- Long term availability (fixed BOM)

Product Features

- 384-core NVIDIA Volta™ GPU with 48 Tensor Cores
- 6-Core ARM v8.2 64-bit NVIDIA Carmel CPU
- 8GB or 16 GB 128-bit LPDDR4x RAM
- M.2 NVMe slot for storage expansion up to 2TB
- USB 3.1 and HDMI 2.0 ports with dust covers
- Ethernet, active / passive CAN
- Optional LTE & WiFi extensions
- Aluminum housing

Markets / Applications

- Autonomous Mobile Robots (AMRs)
- Agriculture
- Construction
- Transportation
- Off-Highway Vehicles
- Heavy Industry
- Outdoor applications



Order Code **RPC/RSA3NI19-A102S^{1,5}** **RPC/RSA3NI19-B106S^{1,5}**

Rugged AI Computer

Processor module / Performance			
NVIDIA Jetson Xavier NX 384-core NVIDIA Volta™ GPU with 48 Tensor Cores		•	•
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU			
NVIDIA Jetson Xavier NX (16GB RAM) 384-core NVIDIA Volta™ GPU with 48 Tensor Cores		on request	on request
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU			
AI Performance (INT8)		21 TOPs	21 TOPs
Memory / Storage			
Data Cache Size		2MB	2MB
128-bit LPDDR4x RAM soldered on board		8GB	8GB
eMMC 5.1 Flash Storage on board		16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) ⁵		1	1
microSD Card socket ²		1	1
Features			
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)		•	•
Inertial measurement unit (IMU) ¹ STMicroelectronics ISM330DHCXTR		on request	on request
Communication Interfaces			
Video output ² behind the service cover		DisplayPort 1.4	DisplayPort 1.4
Internal USB version 2.0 OTG ² behind the service cover (micro USB Type AB)		1	1
USB version 2.0 ² behind the service cover (Type A)		2	2
Video output		HDMI 2.0	HDMI 2.0
USB version 3.1 (5 Gbit/s) (Type A)		1	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT) (M12 female, x-coded)		2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (M12 female, a-coded)		1	1
Mini PCIe socket ² , used for extensions depending on configuration		2	2
Serial RS232 ¹ (M12 female, a-coded)		on request	on request
USB version 2.0 ¹ (M12 female, a-coded)		on request	on request
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface ¹		on request	on request
Wireless Connectivity			
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS Telit LE910C4-WWX ⁶ (Dual nano SIM support)		none	3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.0 Emwicon WMX6218 ⁶		none	2x RP-SMA
High Accuracy GNSS Positioning Module w/ RTK & optional heading support ¹ u-blox ZED F9R / F9P		on request	on request
Technical Data			
Dimensions [mm] (housing, incl. mounting)		w245 x h66 x d165	w245 x h66 x d165
Net weight [gram]		~2300	~2350
Non isolated Input voltage, with Ignition controller, reverse polarity protected (M12 male, a-coded)		9 ... 45VDC	9 ... 45VDC
Power consumption typ. in Watt @ 24V without Add-Ins, idle		~8.5	~8.5
Environmental Conditions			
Operating temperature ³		-25°C ... +70°C	-25°C ... +70°C
Storage temperature		-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529		IP67	IP67
Conformal coating ⁴		on request	on request
Shock (designed to meet)		EN60068-2-27	EN60068-2-27
Vibration (designed to meet)		EN60068-2-64	EN60068-2-64
EMC-Conformity		EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)		EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)		n/a	RED
estimated MTBF @ 25°C ambient ⁵ according to Telcordia SR-332, Environment GB, excluding battery and SSD		~ 550 000h	~ 385 000h

¹Please contact factory for minimum order quantities

²Internal connector

³Depending on installation situation and interface connection. Please see user documentation.

⁴On all possible components (excl. Xavier NX module, connectors and wireless devices)

⁵It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes:

RPC/RSA3NI19-[A/B]102S-01 = 120GB | RPC/RSA3NI19-[A/B]10xS-02 = 240GB | RPC/RSA3NI19-[A/B]10xS-05 = 480GB | RPC/RSA3NI19-[A/B]10xS-10 = 960GB

⁶These LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL (previous products: RPC/RSA3NI19-B102S)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG
All rights reserved

Syslogic Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:
info@syslogic.com
support@syslogic.com
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)
+49 7741 9671-420 Germany and Austria



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660