



IMB-191 / IMB-193

Mini-ITX Motherboard

Spotlight Features

- Supports Intel® 7th/ 6th Gen (KabyLake-S/Skylake-S) Core™ Processors (Socket 1151)
- Supports Dual Channel DDR4 SO-DIMM 2133, up to 32GB
- 2 x HDMI, 1 x LVDS (IMB-191)
- 2 x HDMI, 1 x DisplayPort, 1 x eDP (IMB-193)
- 4 x USB 3.0, 4 x USB 2.0, 2 x SATA3, 4 x COM
- 1 x Mini-PCIe, 1 x PCIe x4 Slot, 1 x mSATA
- 2 x Intel® LAN (IMB-191)
- 1 x Intel LAN, 1 x Realtek LAN (IMB-193)
- 1 x TPM Header
- 12V / 19~24V DC-in (IMB-191)
- 19V DC-in (IMB-193)

Specifications

Processor System	IMB-191	IMB-193
Dimensions	Mini-ITX (6.7-in x 6.7-in)	
CPU	Supports Intel® 7 th / 6 th Gen (KabyLake-S/Skylake-S) Core™ Processors (Socket 1151)	
Chipset	Intel® H110	

Expansion Slot		
PCIe	1 x PCIe x4	
Mini-PCIe	1 x half size (Supports PCIe x1 & USB device)	
M.2	N/A	
mSATA	1 x full size (shared SATA and USB device)	

Memory		
Technology	Dual Channel DDR4 2133MHz	
Max	32GB	
Socket	2 x SO-DIMM	

Graphics		
Controller	Intel® Gen9 Graphics DX 11/12, OGL4.3/4.4	
VGA	Supports max resolution up to 1920 x 1200	N/A
LVDS	Supports Dual channel 24-bit co-lay with eDP, max resolution up to 1920 x 1200@60Hz	N/A
eDP	N/A	Supports Max. resolution 4096 x 2160@60Hz
HDMI	Supports max resolution up to 4096 x 2160 @30Hz	
DVI	N/A	
DisplayPort	N/A	Supports max resolution up to 4096 x 2160@60Hz
Multi Display	Dual Display	

Ethernet		
Interface	10/100/1000 Mbps	
Controller	1 x Intel® I210 1 x Intel® I219V	1 x Intel® I219v 1 x Realtek RTL8111G

Rear I/O	IMB-191	IMB-193
VGA	N/A	
DVI	N/A	
HDMI	2	
DisplayPort	N/A	1
Ethernet	2	
USB	4 x USB 3.0	
Audio Jack	2 (Mic-in, Line-out)	
Serial	N/A	
PS/2	N/A	

Internal Connector		
USB	4 x USB 2.0	
LVDS	1	N/A
eDP	N/A	1
VGA	1	N/A
Serial	2 x COM (RS-232, 2 x RS-232/422/485)	3 x COM (RS-232), 1 x COM (RS-232/422/485)
SATA	2 x SATA3	
Parallel	N/A	
GPIO	4 x GPI + 4 x GPO	
SATA PWR Output Con	1	
Speaker Header	1	
TPM	1 x Header	

Watchdog Timer	
Output	From Super I/O to drag RESETCON#
Interval	256 segments, 0,1,2...255sec/min

Power Requirements		
Input PWR	12V / 19~24V DC-in (DC Jack / 4-pin ATX PWR Con)	19V DC-in (DC Jack / 4-pin ATX PWR Con)
Power On	AT/ATX Supported AT : Directly PWR on as power input ready ATX : Press button to PWR on after power input ready	

Environment	
Operating Temperature	0°C – 60°C
Storage Temperature	-40°C – 85°C

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660