

# Digital Signage Displays PF43B-2





### **Key Features**



#### Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



#### Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



#### SoC Content Management

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



#### **Usb Security**

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



#### Subtle Design

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluities, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



#### Signal Failover

Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.



### Panel

		B 10117	
Brand	43"	Backlight Type	Slim DLED
Brightness (typical)	500 cd/m <sup>2</sup>	Native Resolution	3840 x 2160 (16:9) - UHD
Contrast Ratio (typical)	1200:1(typ.)	Dynamic Contrast Ratio	50000:1
Panel Life Time ( Min. )	50000 Hrs	Response Time (typical)	8 ms
Active Area (H x V)	941.184(H) ×529.416(V)	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	1.07 G (8 bit + FRC)	Screen Treatment	3H
Haze Level	1%	Refresh Rate	60Hz
Orientation	Landscape	Operation Hours	16/7
Area of Usage	Indoor		
Built-in System			
Mainboard Model	17MB135VS		
Monitor Connectivity			
RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	2xHDMI2.0, 2xUSB2.0, USB2.0(Internal)	Video Output	N/A
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12
Mechanical	"963 x 83 x 555 mm with OPS/SDM		
Product Dimensions (WxDxH)	963 x 63 x 555 mm without	Package Dimensions (WxDxH)	1050 x 178 x 718 mm
	OPS/SDM"		
Product Weight	OPS/SDM" 10.5 kg	Package Weight	13.4 kg
Product Weight Vesa Mounting		Package Weight Bezel Width	13.4 kg 6/6/6/9 mm
Vesa Mounting	10.5 kg 200 mm(W) x 200 mm(H) M6		
	10.5 kg 200 mm(W) x 200 mm(H) M6		
Vesa Mounting	10.5 kg 200 mm(W) x 200 mm(H) M6		
Vesa Mounting Environmental Condition	10.5 kg 200 mm(W) x 200 mm(H) M6 S	Bezel Width	6/6/6/9 mm
Vesa Mounting Environmental Condition Operating Temperature	10.5 kg 200 mm(W) x 200 mm(H) M6 S	Bezel Width	6/6/6/9 mm
Vesa Mounting Environmental Condition Operating Temperature Power	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C	Bezel Width	6/6/6/9 mm
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Bezel Width	6/6/6/9 mm 10-90%
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Bezel Width Operating Humidity	6/6/6/9 mm
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption Typical	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Bezel Width Operating Humidity	6/6/6/9 mm 10-90%
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption Typical	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Bezel Width Operating Humidity	6/6/6/9 mm 10-90%
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption Typical Deep Standby	10.5 kg 200 mm(W) x 200 mm(H) M6 S 0-40°C 110 VAC - 240 VAC - 50/60 Hz	Bezel Width Operating Humidity	6/6/6/9 mm 10-90%
Vesa Mounting Environmental Condition Operating Temperature Power Power Supply Power Consumption Typical Deep Standby Features	<ul> <li>10.5 kg</li> <li>200 mm(W) x 200 mm(H) M6</li> <li>S</li> <li>0-40°C</li> <li>110 VAC - 240 VAC - 50/60 Hz</li> <li>127 W</li> <li>≤0.5 W</li> <li>Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, Remote control</li> </ul>	Bezel Width Operating Humidity Maximum	6/6/6/9 mm 10-90% 160 W Joystick, Rocker Switch, Detachable Power Cable, Dettachable Logo, Internal Usb Cover, 30-degrees



### Accessory

Standard	QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable
Certification	

Safety	Yes	EMC	Yes
CE	Yes		



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660