


Digital Signage Displays  
PR50D-4H

**VESTEL**



**Key Features**



**Daisy Chain**

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



**USB Security**

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



**USB Auto-Play**

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



**Subtle Design**

This series' displays exhibit ultra narrow bezel design eliminating the visual superfluties, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



**Scheduler**

The built in scheduler is one of the many important included features. The scheduler allows you to plan daily routines of when the display is powered on or off, along with selection of different sources or USB playlists.



**SoC Content Management**

With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.

### Panel

|                         |  |                          |                           |
|-------------------------|--|--------------------------|---------------------------|
| Screen Size             | 50"  | Panel Technology         | VA                        |
| Backlight Type          | Slim DLED  | Brightness (typical)     | 700 cd/m <sup>2</sup>     |
| Native Resolution       | 3840 x 2160 (16:9) - UHD                           | Contrast Ratio (typical) | 5000:1 (typ.)             |
| Dynamic Contrast Ratio  | 70000:1  | Panel Life Time ( Min. ) | 50000 Hrs                 |
| Response Time (typical) | 9.5 ms   | Active Area (H x V)      | 1095.8 (H) x 616.4 (V) mm |
| Viewing Angle           | 178° Vert., 178° Hor.<br>(89U/89D/89L/89R) @ CR>10 | Color Value              | 1.07B                     |
| Color Gamut             | 72% NTSC   | Haze Level               | 3%                        |
| Refresh Rate            | 60 Hz  | Orientation              | Landscape / Portrait      |
| Operation Hours         | 24/7   | Area of Usage            | Indoor                    |

### Built-in System

|                    |  |                  |   |
|--------------------|--|------------------|---|
| Mainboard Model    | 17MB400VS  | Operating System | Android 9   |
| Memory             | 2 GB DDR4  | Storage          | 16 GB eMMC  |
| Additional Storage | Micro SD (up to 1TB)                                   | CPU              | Quad-Core ARM Cortex-A55                              |
| GPU                | ARM Mali-G31 MP2                                       | Wired            | 10/100/1000 Mbps Ethernet, IEEE 802.1X Authentication |
| WiFi               | WiFi 5 (802.11 a/b/g/n/ac), IEEE 802.1X Authentication | Bluetooth        | BT 5.1  |
| HTML5 Browser      | Vewd   | Wireless Display | Miracast  |

### Monitor Connectivity

|                 |   |                  |   |
|-----------------|---|------------------|---|
| Video Input     | 4xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB | Video Output     | 1xHDMI2.0   |
| Audio Input     | Headphone, Optic SPDIF  | External Control | RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12) |
| External Sensor | RJ12  |                  |   |

### Mechanical

|                            |                         |                            |                       |
|----------------------------|-------------------------|----------------------------|-----------------------|
| Product Dimensions (WxDxH) | 1121 x 63 x 646 mm      | Package Dimensions (WxDxH) | 1215 x 165 x 775 mm   |
| Product Weight             | 12.8 kg                 | Package Weight             | 16.8 kg               |
| Vesa Mounting              | 200 (W) x 200 (H) mm M6 | Bezel Width                | B: 13 mm, T/L/R: 9 mm |

### Environmental Conditions

|                       |        |                    |        |
|-----------------------|--------|--------------------|--------|
| Operating Temperature | 0-40°C | Operating Humidity | 10-90% |
|-----------------------|--------|--------------------|--------|

### Power

|              |                              |
|--------------|------------------------------|
| Power Supply | 110 VAC - 240 VAC - 50/60 Hz |
|--------------|------------------------------|

### Power Consumption

|              |        |         |       |
|--------------|--------|---------|-------|
| Typical      | 121 W  | Maximum | 160 W |
| Deep Standby | ≤0.5 W |         |       |



## Features

|                      |  |                            |  |
|----------------------|--|----------------------------|--|
| <b>Main Features</b> | HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, Crestron Connected, SNMP | <b>Mechanical Features</b> | Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover |
| <b>Speaker</b>       | 2x10 W   |                            |  |

## Accessory

|                 |   |
|-----------------|---|
| <b>Standard</b> | QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable |
|-----------------|---|

## Certification

|               |     |            |     |
|---------------|-----|------------|-----|
| <b>Safety</b> | Yes | <b>EMC</b> | Yes |
| <b>CE</b>     | Yes |            |     |

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660