

TAM-115P/R/G(H)	15" IP66 / IP69	K Stainless Steel Di	splay		Industrial Panel PC	HMI Controller Industrial Display Monitor	
	Features / · Steel Display True Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure			Dimensions / P			
	(Grade 316 for Op IP66/IP69K Rated Support Resistive Touch on/off Butto Support Ergonom		s ⊎ Touch, and Glass enic Cleaning				
	Specificati	ions / P		• • • 324 22929	397		<u>ه</u> ۲
	VGA	1 x M12 12-pin for VGA with					
· · · ·	HDMI	1 x W.F. HDMI with waterproo		r.			• •
· · · · · · · · · · · · · · · · · · ·	USB 1 x M12 USB 2.0 with waterproof cover and chain			면 브		──────────────────────────────────────	9 U
	Speaker 1 x 2W IP65 speaker (option)						
	OSD Control OSD on the rear side						
	Membrane Power Connector	1 x M12 3 nin for DC nowers	vith waterproof cover and chain			UNIT: mm	
		1 x Witz o-pintion bio power v				Tolerance	±0.5
	Display	Standard	High Brightness Optional		<u></u>		
	Display Type	15" TFT-LCD	15" TFT-LCD				
	Max. Resolution	1024 x 768	1024 x 768				
	Max. Color	16.2M / 262K	16.7M				
	Luminance (cd/m ²)	300	1000				
	View Angle	176(H) /176(V)	160(H) /150(V)				
	Contrast Backlight Lifetime	2000:1 70,000 hrs	800:1 50,000 hrs	Environmental			
	Backlight Lifetime	70,000 115	50,000 ms	Operating Temp		on)	
	Touch Screen			Storage Tempera			
	Touch Screen	Resistive Touch (for R model		Humidity	10 to 95% @ 40°C, non-	- condensing	
	Туре	Projected Capacitive Touch (1 Glass (for G model)) for P model)	Certificate	CE/FCC Class A		
	Interface	USB		Ordering Inform	nation		
	Light Transmission(%)	Popiativo Touch : 90%		Vitam-115P	15" XGA IP66/IP69K stainless steel disp projected capacitive touch, 9~36V DC p	olay, VGA/HDMI input, OSD on the rear side, ower input with Adapter	
	g()						
				VITAM-115R	15" XGA IP66/IP69K stainless steel disp	olay, VGA/HDMI input, OSD on the rear side,	
	Power	DC 9~36V		ViTAM-115R	15" XGA IP66/IP69K stainless steel disp 5 wire resistive touch window, 9~36V D	olay, VGA/HDMI input, OSD on the rear side, C power input with Adapter	
		DC 9~36V VITAM-115R: Max 9W VITAM-115PH: Max 17W		VITAM-115R	5 wire resistive touch window, 9~36V D	C power input with Adapter	
	Power Power Input	VITAM-115R: Max 9W VITAM-115PH: Max 17W		VITAM-115K	5 wire resistive touch window, 9~36V Di 15" XGA IP66/IP69K stainless steel disp protection glass, 9~36V DC power input 15" XGA IP66/IP69K stainless steel disp	C power input with Adapter	
	Power Power Input Power Consumption Mechanical Construction	VITAM-115R: Max 9W VITAM-115PH: Max 17W 304 Stainless steel chassis(d chassis(optional)		VITAM-115R VITAM-115G VITAM-115PH	5 wire resistive touch window, 9–36V D 15° XGA IP66/IP69K stainless steel disp protection glass, 9–36V DC power input 15° XGA IP66/IP69K stainless steel disp projected capacitive touch, 9–36V DC p 15° XGA IP66/IP69K stainless steel disp	C power input with Adapter play, VGA/HDMI input, OSD on the rear side, with Adapter play, VGA/HDMI input, OSD on the rear side, lower input with Adapter, 1,000 nits LCD play, VGA/HDMI input, OSD on the rear side,	
	Power Power Input Power Consumption Mechanical	VITAM-115R: Max 9W VITAM-115PH: Max 17W 304 Stainless steel chassis(d		VITAM-115R VITAM-115G VITAM-115PH	5 wire resistive touch window, 9–36V D 15° XGA IP66/IP69K stainless steel disp protection glass, 9–36V DC power input 15° XGA IP66/IP69K stainless steel disp projected capacitive touch, 9–36V DC p 15° XGA IP66/IP69K stainless steel disp	C power input with Adapter play, VGA/HDMI input, OSD on the rear side, with Adapter play, VGA/HDMI input, OSD on the rear side, ower input with Adapter, 1,000 nits LCD	
	Power Power Input Power Consumption Mechanical Construction Mounting	VITAM-115R: Max 9W ViTAM-115PH: Max 17W 304 Stainless steel chassis(d chassis(optional) VESA Mount 75 x 75, Yoke m		VITAM-115R VITAM-115G VITAM-115PH VITAM-115RH	5 wire resistive touch window, 9–36V Di 15° XGA IP66/IP69K stainless steel disp protection glass, 9–36V DC power input 15° XGA IP66/IP69K stainless steel disp projected capacitive touch, 9–36V DC p 15° XGA IP66/IP69K stainless steel disp 5 wire resistive touch window, 9–36V D	C power input with Adapter play, VGA/HDMI input, OSD on the rear side, twith Adapter play, VGA/HDMI input, OSD on the rear side, lower input with Adapter, 1,000 nits LCD play, VGA/HDMI input, OSD on the rear side, c power input with Adapter, 1,000 nits LCD play, VGA/HDMI input, OSD on the rear side, play, VGA/HDMI input, OSD on the rearear side, play, VGA/HDMI input, OSD	

Industrial Panel PC

Industrial Panel PC



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660