

Rugged Embedded



# Nuvo-9000 Series

Intel® 12th-Gen Core™ Rugged Embedded Computer with 6x 2.5GbE/ GbE, USB 3.2 Type-C, Patented Cassette & MeziO™ Interface



## Key Features

- Supports Intel® 12th-Gen Alder Lake Core™ 16C/ 24T 35W/ 65W CPU
- Patented Cassette for PCI/PCIe add-on card accommodation
- Rugged, -25°C to 70°C fanless operation
- Up to 5x 2.5GbE and 1x GigE ports with optional PoE+, supporting 9.5 KB jumbo frame
- 1x USB 3.2 Gen2x2 type-C and 8x USB 3.2/ 2.0 type-A ports
- Supports M.2 Gen4x4 NVMe and 2x SATA ports
- MeziO™ interface for easy function expansion
- VGA/ DVI/ DP triple independent display, supporting 4K2K resolution

Contact Neosys

Get Quote

\*R.O.C Patent No. M456527

Preliminary

## Introduction

Nuvo-9000 series is Neosys' new rugged embedded computer based on Intel® 12th-Gen Alder Lake platform. Benefiting from cutting-edge Intel® 7 photolithography, the latest Core™ desktop processor comes with up to 16 cores and 24 threads and presents an incredible boost of computational performance. Combining the increase of DDR5 memory bandwidth and PCIe Gen4 NVMe high-speed disk read/write, users can expect an overall system performance improvement of up to 1.8x when compared to previous 10th or 11th-Gen platforms.

Nuvo-9000 series inherits Neosys' patented expansion Cassette design to provide great versatility by allowing additional installation of PCIe or PCI add-on cards. There are three expansion Cassette options available for Nuvo-9000 series, the Nuvo-9000E features a single x16 Gen3 PCIe slot; Nuvo-9000DE has dual x16 PCIe slots, and Nuvo-9000P has a single PCI slot. For users who need more flexible storage, Nuvo-9000LP has a 2.5" HDD tray instead of an expansion Cassette to support a hot-swappable 2.5" HDD/SSD.

I/O functions are also comprehensively enhanced. In addition to six 2.5G and Gigabit Ethernet ports with PoE+ PSE option, Nuvo-9000 series features a USB 3.2 Gen2x2 type-C port offering 20 Gbps bandwidth for data exchange with external devices, plus another six USB 3.2 type-A ports for USB3 camera connectivity. It also has an upgraded M.2 Gen4x4 slot to support the latest NVMe SSD to boost disk read/write speed up to 7000 MB/s. For unfulfilled I/O requirements, users can utilize the expansion Cassette to add on function-specific PCIe/ PCI card, the proprietary MeziO interface, and internal mini-PCIe/M.2 interfaces.

With its field-proven thermal design, significant CPU and I/O upgrades, and multiple expansion methods, the Neosys Nuvo-9000 series fits your need for ruggedness, performance, and versatility for a variety of applications.


## Specifications

System Core		Expansion Bus	
Processor	Supporting Intel® 12th-Gen Alder Lake Core™ CPU (LGA1700 socket, 35W/ 65W TDP)	PCI/PCI Express	1x PCIe x16 slot@Gen3, 8-lanes PCIe signals in Cassette (Nuvo-9002E/ 9006E)
	- Intel® Core™ i9-12900E/ i9-12900TE		2x PCIe x16 slots@Gen3, 8-lanes PCIe signals in Cassette (Nuvo-9002DE/ 9006DE)
	- Intel® Core™ i7-12700E/ i7-12700TE	Mini PCI Express	1x PCI slot in Cassette (Nuvo-9002P/ 9006P)
	- Intel® Core™ i5-12500E/ i5-12500TE		1x full-size mini PCI Express socket
	- Intel® Core™ i3-12100E/ i3-12100TE	M.2	1x M.2 2242/3052 B key socket with SIM slot for M.2 5G/ 4G module
	- Intel® Pentium® G7400E/ G7400TE		1x MeziO™ expansion port for Neosys MeziO™ modules
- Intel® Celeron™ G6900E/ G6900TE			
Chipset	Intel® Q670E platform controller hub	<b>Power Supply</b>	
Graphics	Integrated Intel® UHD Graphics 770 (32EU)	DC Input	
Memory	Up to 64 GB DDR5 4800 SDRAM (two SODIMM slots)	1x 3-pin pluggable terminal block for 8 to 48V DC input	
AMT	Supports Intel vPro/ AMT 16.0	Remote Ctrl. & LED Output	
TPM	Supports dTPM 2.0	1x 3-pin pluggable terminal block for remote control and PWR LED output (Ctrl_In/ GND/ LED_Out)	
<b>I/O Interface</b>		<b>Mechanical</b>	
Ethernet port	1x 2.5G Ethernet by I225 and 1x Gigabit Ethernet by I219 (Nuvo-9002E/ P/ DE) with screw-lock	Dimension	240 mm (W) x 225 mm (D) x 90 mm (H) (Nuvo-9000E/ P series)
	5x 2.5G Ethernet by I225 and 1x Gigabit Ethernet by I219 (Nuvo-9006E/ P/ DE) with screw-lock		240 mm (W) x 225 mm (D) x 110.5 mm (H) (Nuvo-9000DE series)
PoE+	Optional IEEE 802.3at PoE+ PSE for Port 3 ~ Port 6 (2.5GbE) 100 W total power budget	Weight	4.4 kg (Nuvo-9000E/ P series) TBD (Nuvo-9000DE and Nuvo-9000LP series)
USB 3.2	1x USB 3.2 Gen2x2 (20 Gbps) port in type-C connector with screw-lock	Mounting	Wall-mount (standard) or DIN-rail mount (optional)
	4x USB 3.2 Gen2x1 (10 Gbps) ports in type-A connectors 2x USB 3.2 Gen1x1 (5 Gbps) ports in type-A connectors		<b>Environmental</b>
USB 2.0	2x USB 2.0 ports	Operating Temperature	with 35W CPU -25°C ~ 70°C *
Video Port (Integrated Graphics)	1x VGA, supporting 1920 x 1200 resolution		with 65W CPU -25°C ~ 70°C */** (configured as 35W TDP) -25°C ~ 50°C */** (configured as 65W TDP)
	Serial Port	1x DVI-D, supporting 1920 x 1200 resolution	Storage Temperature
1x DisplayPort, supporting 4096 x 2304 resolution		Humidity	
Audio	2x software-programmable RS-232/ 422/ 485 ports (COM1/ COM2)	Vibration	Operating, MIL-STD-810G, Method 514.6, Category 4
	2x RS-232 ports (COM3/ COM4)		Shock
Storage Interface	1x 3.5 mm jack for mic-in and speaker-out	EMC	
	SATA HDD		2x internal SATA port for 2.5" HDD/ SSD installation, supporting RAID 0/ 1
M.2 NVMe	1x M.2 2280 M key NVMe socket (PCIe Gen4x4) for NVMe SSD		


Nuvo-9000 Series



## Appearance



## Dimensions



## Ordering Information

Model No.	Product Description
<b>Nuvo-9002E</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 2x 2.5GbE/ GbEGbE, USB 3.2 Type-C, single-slot PCIe Cassette & MeziO™ Interface
<b>Nuvo-9002DE</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 2x 2.5GbE/ GbEGbE, USB 3.2 Type-C, dual-slot PCIe Cassette & MeziO™ Interface
<b>Nuvo-9002P</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 2x 2.5GbE/ GbEGbE, USB 3.2 Type-C, single-slot PCI Cassette & MeziO™ Interface
<b>Nuvo-9006E</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 6x 2.5GbE/ GbEGbE, USB 3.2 Type-C, single-slot PCIe Cassette & MeziO™ Interface
<b>Nuvo-9006DE</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 6x 2.5GbE/ GbEGbE, USB 3.2 Type-C, dual-slot PCIe Cassette & MeziO™ Interface
<b>Nuvo-9006P</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 6x 2.5GbE/ GbEGbE, USB 3.2 Type-C, single-slot PCI Cassette & MeziO™ Interface
<b>Nuvo-9002LP</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 2x 2.5GbE/ GbEGbE, USB 3.2 Type-C, MeziO™ Interface & 2.5" HDD tray
<b>Nuvo-9006LP</b>	Intel® 12th-Gen Core™ Rugged Embedded Computer with 6x 2.5GbE/ GbEGbE, USB 3.2 Type-C, MeziO™ Interface & 2.5" HDD tray
<b>PoE+ Option</b>	Option of 802.3at PoE+ PSE for 2.5GbE port 3 ~ port 6

## Optional Accessories

<b>DINRAIL-O</b>	DIN-rail mount assembly for Nuvo-9000 series
<b>Dmpbr-Nuvo5000_7000</b>	Neosys' patented damping brackets assembly for Nuvo-9000 Series
<b>Fankit-25</b>	Fan assembly for 1-slot Cassette, 25x25x10 mm
<b>PA-160W-OW</b>	160W AC-DC power adapter 20V/8A; 18AWG/120cm; cord end terminals for terminal block, operating temperature: -30°C to 70°C. (recommended for 35W CPU)
<b>PA-280W-ET2</b>	280W AC/DC power adapter 24V/ 11.67A; 16AWG/ 100cm; cord end terminals for terminal block, operating temperature : -30°C to 60°C. (recommended for 65W CPU)

### MeziO™ Modules

<b>MeziO™ -C180</b>	MeziO™ module with 4x RS-232/ 422/ 485 ports and 4x RS-232 ports
<b>MeziO™ -C181</b>	MeziO™ module with 4x RS-232/ 422/ 485 ports and 4x RS-422/ 485 ports
<b>MeziO™ -D220</b>	MeziO™ module with 8-CH isolated digital input and 8-CH isolated digital output
<b>MeziO™ -D230</b>	MeziO™ module with 16-CH isolated digital input and 16-CH isolated digital output
<b>MeziO™ -V20-EP</b>	MeziO™ module with ignition power control function for in-vehicle application
<b>MeziO™ -U4</b>	MeziO™ module with 4x USB 3.1 ports
<b>MeziO™ -G4</b>	MeziO™ module with 4x GigE ports
<b>MeziO™ -G4P</b>	MeziO™ module with 4x IEEE 802.3at PoE+ ports

Only Nuvo-9006E-PoE, Nuvo-9006P-PoE and Nuvo-9006DE-PoE support MeziO-G4P

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660