

EMS-EHL-HDMI

Intel® Elkhart Lake Atom®/Celeron®
Processor Fanless Rugged Embedded System,
w_HDMI IET Module



Product Features

- Intel® Celeron®/Atom™ J6413/x6425E SoC BGA Processor
- Rich I/O, 4-USB3.2, 2-USB2.0, 1-DP, 2-HDMI, 4-COM, 4-LAN, 1-8bit GPIO
- Fanless operation temperature from -40°C ~ 70°C (WT) / 0°C ~ 65°C (ST)
- Wide range DC power input from +9~36V
- Support IET modules
- 1 x 260-pin SODIMM socket Max. up to 32GB DDR4 3200MT/s
- Support 5G (Sub-6G) module, HDMI 2.0b (4K @ 60Hz), LAN 2.5G Base-Tx GbE
- CE, FCC Class B, LVD 62368-1, IP50
- Support HW TPM 2.0

Specification

System Information

Processor	Intel® Celeron® Processor J6413 (1.5M Cache, up to 3.00Ghz), ST, Tj=105°C Intel® Atom® Processor x6425E(1.5M Cache, up to 3.00Ghz), WT, Tj=-40°C ~105°C
System Memory	1 x 260-pin SODIMM socket Max. Up to 32GB DDR4 3200 MT/s
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	CPU & system temperature monitoring and Voltages monitoring
TPM	TPM 2.0
SBC	EBM-EHLS

Expansion

M.2	1 x M.2 Key-B 2242/3042/3052 support SATA3/ PCIe III/ USB3.2 Gen.1 and SIM slot1 (internal), default support 3.3V, jumper setting to adjust 3.3V/ 3.8V 1 x M.2 Key-E 2230 for Wi-Fi & BT Module (USB2.0/ PCIe III)
------------	---

Storage

M.2	1 x M.2 Key-B 2242/2280, support SATA 1 x M.2 Key-B 2242, support SATA (share with expansion slot)
------------	---

Front I/O

Power Button	1 x Push Button for Power on/off
Reset Button	1 x Push Button for Reset
LED Indicator	1 x Power LED (Blue) 1 x Storage LED (Yellow)- M.2 B-key SATA 1 x LTE LED (Green)- M.2 B-key PCIe 1 x Wifi LED (Green)- M.2 E key
COM Port	2 x COM RS232/422/485 (select via BIOS, auto flow control via HW)
Digital I/O	1 x 8-bit GPIO (DB9)
Audio	1 x Mic-In, 1 x Line-Out
Wire-Control Power On/Off	1 x 2-Pin Terminal Block for wire-control power on/off
Antenna	2 x Antenna with dust cover

Rear I/O

USB	2 x USB 2.0 2 x USB 3.1 Gen.2 (10Gbp/s) 2 x USB 3.1 Gen.1 (5Gbp/s), via USB Hub
COM Port	2x RS232/422/485 (select via BIOS, auto flow control via HW)
LAN Port	4 x RJ45
Audio	1 x Mic-In, 1 x Line-Out
DP	1 x DP 1.4
HDMI	2 x HDMI 2.0b
Antenna	2 x Antenna with dust cover
AC/DC Input	3-Pin Terminal Block (V+, V-, GND)

Right I/O

Antenna	2 x Antenna with dust cover
----------------	-----------------------------

Left I/O

Antenna	2 x Antenna with dust cover
----------------	-----------------------------

Display

Graphic Chipset	Intel® UHD Graphics for 10th Gen Intel® Processors
------------------------	--

Resolution	DP++ 1.4: 4096x2304 @ 60Hz HDMI 2.0b : Max. resolution 4096x2304 @ 60Hz
-------------------	--

Audio

Audio Codec	Realtek ALC888S (co-lay with ALC897) HD codec
--------------------	---

Ethernet

LAN Chipset	2 x Intel I226-IT 2 x Intel® I211-AT
--------------------	---

Specification	2 x 10/100/1000/2.5G Base-Tx GbE compatible 2 x 10/100/1000Base-Tx GbE compatible
----------------------	--

Power Requirement

ACPI	Single power ATX Support S0,S3, S4, S5 ACPI 5.0 Compliant
-------------	--

Power Mode	AT/ATX (ATX is default setting)
-------------------	---------------------------------

Software Support

OS	Win 10 64bit / Win 11 64 bit/ Linux
-----------	-------------------------------------

Certification

Certification Information	CE, FCC Class B, LVD 62368-1
----------------------------------	------------------------------

Mechanical & Environmental

Operating Temp.	-40°C ~ 70°C (w/SSD) ambient w/ 0.5 air flow, WT sku, x6425E -40°C ~ 60°C (w/SSD) ambient w/ 0.2 air flow, WT sku, x6425E 0°C ~ 65°C (w/SSD) ambient w/ 0.5 air flow, ST sku, J6413 0°C ~ 55°C (w/SSD) ambient w/ 0.2 air flow, ST sku, J6413
------------------------	--

Storage Temp.	-30°C ~ 70°C (-22°F ~ 158°F)
----------------------	------------------------------

Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
---------------------------	--

Dimension (W x L x H)	240mm x 150mm x 64 mm (w/ IET module)
------------------------------	---------------------------------------

Weight	1.9 kg (System) 2.7 kg (w_Package)
---------------	---------------------------------------

Vibration Test	With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
-----------------------	---

Shock Test	With SSD : 55Grms, IEC 60068-2-27, Half Sine, 11ms
-------------------	--

IP Rating	IP 50
------------------	-------

Mounting Kit	Wall mount kit (standard) DIN RAIL (optional)
---------------------	--

Ordering Information

Ordering Information

Intel® Elkhart Lake Atom®/Celeron® Processor Fanless Rugged Embedded System, w_HDMI
IET Module

EMS-EHL-X64-A1-6R (x6425E)
EMS-EHL-J64-A1-6R (J6413)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660