

58:9 Ultra Stretch for Dynamic Digital Content

Ultra Stretch Signage 86BH5C



Ultra Stretch 86BH5C is a new signage format with a 58:9 widescreen that can display dynamic content depending on the user's installation environment. (E.g. airports, subways, banks, art galleries, or retail stores) This product is also a work of structural art in itself that can be seen as digital decor.

Key Features

New Design Configuration



Ultra HD Resolution (3840 x 600)

Ultra HD large screens deliver an immersive viewing experience.



Conventional

86BH5C

58:9 Extended Wide Format

Dynamic content is delivered on one screen since the new widescreen format is a 58:9 bar-type display.



Conventional

86BH5C

Multiple Screens



4 Divided PBP in Landscape or Portrait

The Picture-by-Picture (PBP) feature allows you to divide a screen into four parts in landscape or portrait installations.



58:9 Ultra Stretch for Dynamic Digital Contents

Ultra Stretch Signage 86BH5C



Screen Size
86"

86BH5C

- Brightness : 500cd/m²
- Bezel : 4.4mm (Left/Right), 5.9mm (Top/Bottom)
- Depth : 81.7mm
- Interface : HDMI, DP, RJ45, IR, USB2.0, USB3.0, Daisy-Chain (DP Out, RS232C In/Out, RJ45)

Other Features

Content Management



58:9 Content Editing

With the LG SuperSign media editor, you can easily edit images or video clips of original content without any additional editing programs.




↓ Video file or Still Image



Multiple Content Creation

Users can edit content that consists of one video and several still images (up to 20) with SuperSign Editor.



Convenient Connectivity Support



Tiling Scene with Daisy Chain

This product supports lateral tiling for 1x4 or 4x1 installations (landscape or portrait), and up to a 4x4 installation with a daisy chain configuration.



LAN Daisy Chain


The LAN daisy chain allows you to control and monitor devices, distribute content, and even update firmware.



Easy Installation

Side Bracket / Classified Port

This product supports side brackets for buried installations. The classified in/out port prevents errors when connecting a daisy chain.



① Mounting hole for side bracket



② Classified in/out port
- Input : White
- Output : Green


Specifications

BH5C		86BH5C-B
PANEL	Screen Size	86" class (85.6") diagonal
	Panel Technology	IPS
	Aspect Ratio	58.9
	Native Resolution	3,840 x 600 (UHD)
	Brightness	Typ: 500cd/m ² , Min : 400cd/m ²
	Contrast Ratio	1,100:1 (Typ)
	Dynamic Contrast Ratio:	(Typ) 500,000:1
	Viewing Angle(H x V)	178 x 178
	Response Time	8ms (G to G BW) typ.
	Surface Treatment	AGP (10% Haze)
Life time	50,000 Hrs	
Orientation	Landscape / Portrait	
CONNECTIVITY	Input	HDMI(3), DP, OPS, DVI-D, USB2.0, USB3.0, SD Card
	Output	Analog Audio
	External Control	RS232C, RJ45, IR+B Receiver, Pixel Sensor, Analog Audio
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	4.4mm (L/R), 5.9mm (T/B)
	Monitor Dimension (W x H x D)	85" x 13.7" x 3.2"
	Weight (Head)	45.2lbs
	Carton Dimensions (W x H x D)	90.2" x 9" x 18.9"
	Packed Weight	78lbs
VESA™ Standard Mount Interface	600mm x 200mm	
SPECIAL FEATURES	Temperature Sensor, Auto Brightness Sensor, Tile Mode, Natural Mode@Tile Mode, ISM Method, Energy Saving, Smart Energy Saving, File Play with USB/SD/Internal Memory, PIP/PBP, 8GB (System 4GB + Available 4GB), Wi-Fi Dongle Ready, 4K Up Scaling	
ENVIRONMENT CONDITIONS	Operation Temperature Range	32 °F to 104 °F
	Operation Humidity Range	10 % to 80 %
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Typ. / Max.	180W/220W
Consumption Smart Energy Saving	30% of typical	
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KC
	ErP / Energy Star	NA / NA
MEDIA PLAYER COMPATIBILITY	OPS type compatible	Yes
EXTERNAL Media player Attachable		No
SOFTWARE COMPATIBILITY	SuperSign W/Lite	Yes
SuperSign C		Yes
ACCESSORY	Basic	Remote Controller (2ea Batteries included), Power Cord, DP (3M), RS-232C Cable (3M) Owner's Manual (Website upload)
	Optional	AN-WF500 (WiFi USB Dongle), MP700, KT-OPSA (OPS KIT), KT-SPO (RGB Sensor) ** Stand is not available
OTHER	UPC	7 19192 19990 3
WARRANTY	3-Year Limited Warranty (Parts and Labor) Extended Warranties Available	

Dimension (unit : mm)


86"

85" x 13.7" x 3.2" / 45.2lbs



Connectivity

- ① AUDIO IN/OUT
- ② DP OUT
- ③ DP IN
- ④ DVI-D IN
- ⑤ HDMI IN
- ⑥ USB
- ⑦ SD Card
- ⑧ LAN IN
- ⑨ LAN OUT
- ⑩ PIXEL SENSOR
- ⑪ IR & LIGHT SENSOR
- ⑫ RS-232C IN
- ⑬ RS-232C OUT




HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE



Download LG Commercial Display Mobile App



More info www.lgecommercial.com

You  youtube.com/c/LGCommercialDisplay

LG may make changes to specifications and product descriptions without notice.
Copyright © 2015 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.
LG_SPEC_86BH5C_061675_PR

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660