

# LPC-P156WAG-2Tx

15.6" (1920\*1080) Bezel-Free P-cap Panel PC, Intel® Tigerlake-UP3 Core™ i3/i5/i7 Processors, IP65 Aluminum Front Bezel, AG, Removable 2.5" HDD/SSD Tray, DC 12~24V Wide Range Power Input, -40~70°C



## Features

- ▶ Intel® Tigerlake-U Core™ i3/i5/i7 Processors
- ▶ 15.6" P-cap Flat Bezel
- ▶ 1920\*1080 Resolution LCD
- ▶ Bezel-Free Design
- ▶ Fanless Design
- ▶ DC 12~24V Wide Range Power Input
- ▶ IP65 / 66 Front Panel
- ▶ 3-Pin Power Input Terminal Block
- ▶ Optional 1000 nits LED Backlight
- ▶ Accordance with MIL-STD-810H

### System

Processor	Intel® TigerLake-U Core™ i3/i5/i7 Processors
System Memory	2 x DDR4 SO-DIMM, up to 64GB
External I/O Port	4 x USB 3.2 Gen2 Ports 2 x RJ45 GbE LAN (Intel® I225-LM supports 2.5GbE LAN) 1 x Display Port 1 x HDMI 4 x RS-232/422/485 1 x Audio out 1 x Power press button 1 x 3-Pin Terminal Block for Power Input
Storage	1 x 2.5" Storage Bay 1 x M.2 M-key(NVME) 2280 Socket
Operating System	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2) Windows 11 IoT Enterprise (64-bit, 21H2, Pre-scan) Linux Ubuntu 22.04 (64-bit, by request) / Linux Yocto Project 3.1 (64-bit, by request)
Expansion	1 x M.2 B-key 2242/3042 (SATA 3.0, PCIe x1, USB 2.0) 1 x M.2 E-key 2230 ( PCIe x1, USB 2.0)

### LCD

Display Type	15.6" TFT LCD
Max. Resolution	1920*1080
Max. Color	16.2M
Luminance	450 nits
View Angle	85/85/85/85
Backlight Lifetime	30,000 hours

### Power Requirement

Power Input	DC 12~24V Wide Range Power Input
-------------	----------------------------------

### Touch Screen

Type	15.6" P-cap USB
------	-----------------

### Environment


Operating Temp	-40~70 °C · IEC-60068-2-1/2/14
Storage Temp	-40~70 °C
Humidity	10~90% @40 °C, non-condensing
EMC	Accordance to MILSTD-461G,CE101/102
Vibration	MIL-STD-810H, 514.8, Procedure I (Accordance)
Shock	MIL-STD-810H, 516.8, Procedure I (Accordance)

### Mechanical

Construction	Aluminum Front Bezel and Metal Case
IP Rating	Front Panel IP65 / IP66 Compliant
Mounting	M4 VESA Mount 75 x 75 / 100 x 100 Panel Mounting
Dimension	387.4 x 242.4 x 84 mm

\* All specifications are subject to change without prior notice.

## Dimension & I/O Connector



### Ordering Information

LPC-P156WAG-2T3	15.6" (1920*1080) Bezel-Free P-cap Panel PC, Intel® Tigerlake-UP3 Core™ i3-1115G4E, IP65 Aluminum Front Bezel, AG, Removable 2.5" HDD/SSD Tray, DC 12~24V Wide Range Power Input, -40~70°C
LPC-P156WAG-2T5	15.6" (1920*1080) Bezel-Free P-cap Panel PC, Intel® Tigerlake-UP3 Core™ i5-1145G7E, IP65 Aluminum Front Bezel, AG, Removable 2.5" HDD/SSD Tray, DC 12~24V Wide Range Power Input, -40~70°C
LPC-P156WAG-2T7	15.6" (1920*1080) Bezel-Free P-cap Panel PC, Intel® Tigerlake-UP3 Core™ i7-1185G7E, IP65 Aluminum Front Bezel, AG, Removable 2.5" HDD/SSD Tray, DC 12~24V Wide Range Power Input, -40~70°C

### Ordering Code

LPC-P156WAG-2Tx Series	-H / -OB / -B / -AR / -V
H	= High Brightness 1000 nits LED backlight
OB	= Optical Bonding
B	= Glass without touch
AR	= Anti-Reflection
V	= Vandal Proof Glass (By Project)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660