



Rugged Embedded

# Nuvo-11531/ Nuvo-11588

Intel® Core™ Ultra 200 Compact Fanless Computer with 4x PoE+ 2.5GbE, 4x USB 3.2, 1x Easy-Swappable 2.5" SSD Tray, and 1x External SlimSAS Connector



## Key Features

- 212 x 165 x 63 mm low-profile design
- Intel® Core™ Ultra 200 series 35W/ 65W LGA1851 CPU
- Rugged, -25°C to 60°C fanless operation
- Up to 48GB DDR5 6400 memory
- 4x 2.5GbE with optional PoE+ and 4x USB3.2 Gen1 with screw-lock
- 1x M.2 2280 Gen4x4 NVMe and 1x swappable 2.5" SSD tray for storage
- 1x PCIe Gen4x8 via SlimSAS 8i (SFF-8654) connector (Nuvo-11588 only)
- 8V to 48V wide-range DC input with optional ignition power control



CONTACT US

GET QUOTE

## Introduction

The Nuvo-11531 is one of the most compact fanless embedded AI computers powered by the Intel® Core™ Ultra 200 series. Its low-profile 212 x 165 x 63 mm footprint makes it ideal for constrained spaces, including robotic arms, AMRs, machine vision systems, and roadside cabinets.

Despite its compact size, the Nuvo-11531 does not compromise on performance. Leveraging TSMC's advanced 3nm process, Intel® Core™ Ultra 200 processors can offer nearly 120% the performance while consuming only 80% of the power\*. Furthermore, with the new NPU and integrated GPU, Intel® Core™ Ultra 200 processors deliver up to 36 TOPS, enhancing AI inspection capabilities for existing rule-based computer vision algorithms.

Designed for diverse edge applications—such as machine vision, AMRs, and smart automation—the Nuvo-11531 offers versatile sensor connections. It features four PoE+ 2.5GbE ports and four USB 3.2 Gen1 ports for industrial/ security cameras or LiDAR, along with multiple isolated DIO and dual COM ports for communication with external devices. Internally, it includes one M.2 E-key slot for Wi-Fi modules and two mPCIe slots for flexible I/O expansion, supporting 5G/4G modules, COM ports, CAN bus, or additional GbE ports. For data storage, it provides an internal Gen4x4 M.2 NVMe slot for the OS and an easy-swappable 2.5" SSD tray for data logging. The wide DC input and optional ignition power control are ideal for battery-powered applications, such as robotics and in-vehicle usage. Additionally, the Nuvo-11588 variant features a SlimSAS connector with PCIe Gen4x8 bandwidth for external NVMe, U.2 storage, industrial PCIe cameras, or GPUs.

As compact embedded computers, the Nuvo-11531 and Nuvo-11588 deliver exceptional computing performance and extensive I/O connectivity. They are well-suited for various industrial and edge applications, including smart factories, autonomous logistics, smart cities, and robotics—particularly where installation space is limited.

\*Benchmarked using PassMark PerformanceTest.


## Specifications

	Nuvo-11531	Nuvo-11588		Nuvo-11531	Nuvo-11588
<b>System Core</b>			<b>Storage Interface</b>		
Processor	Supports Intel® Core™ Ultra 200 CPU (LGA1851 socket, 65W/ 35W TDP)		SATA HDD	1x easy-swappable 2.5" HDD/ SSD tray for 7mm HDD/ SSD	
Chipset	Intel® H810 platform controller hub	Intel® Q870 platform controller hub	M.2 M	1x M.2 2280 M key socket (PCIe Gen4x4) for NVMe SSD	
Graphics	Integrated Intel X® Graphics (Up to 64EU)		<b>Power Supply</b>		
Memory	Up to 48GB DDR5 6400 memory via one SODIMM slot		DC Input	1x 3-pin pluggable terminal block for 8V to 48V DC input with optional ignition power control <sup>[1]</sup>	
TPM	fTPM 2.0 (standard) / dTPM 2.0 (optional)		<b>Mechanical</b>		
<b>Panel I/O Interface</b>			Dimension	212 mm (W) x 165 mm (D) x 63 mm (H)	
Ethernet	4x 2.5GBASE-T Ethernet ports with screw-lock by Intel® I226 GbE controllers. Port 4 supports Wake-on-LAN (WOL)		Weight	TBD	
PoE+	Optional IEEE 802.3at PoE+ PSE for 4x 2.5GbE ports (100W total power budget)		Mounting	Wall-mount (standard) or DIN-rail mount (optional)	
External PCIe Connector	-	1x PCIe Gen4x8 via SlimSAS 8i (SFF-8654) connector	<b>Environmental</b>		
USB	4x USB 3.2 Gen1 (5 Gbps) ports with screw-lock 2x USB 2.0 ports		Operating Temperature	With 35W CPU -25°C to 60°C <sup>[2]</sup> With 65W CPU (installation of the optional fan kit is recommended) -25°C to 60°C <sup>[2],[3]</sup>	
Video Port (Integrated Graphics)	1x HDMI, supporting 4096 x 2160 resolution 1x DisplayPort, supporting 4096 x 2304 resolution		Storage Temperature	-40°C to 85°C	
Serial Port	1x software-programmable RS-232/422/485 ports (COM1) 3x 3-wire RS-232 ports (COM2/ 3/ 4) or 1x RS-422/ 485 port (COM2)		Humidity	10% to 90%, non-condensing	
Isolated DIO	4-CH isolated DI and 4-CH isolated DO	8-CH isolated DI and 8-CH isolated DO	Vibration	MIL-STD-810H, Method 514.8, Category 4	
<b>Internal Expansion Bus</b>			Shock	MIL-STD-810H, Method 516.8, Procedure I	
Mini PCI Express	2x full-size mini PCI Express sockets with internal SIM sockets		EMC	CE/FCC Class A, according to EN 55032 & EN 55035	
M.2 E	1x M.2 2230 E key socket for WiFi module		<p><small>[1] The maximum input current for each pin is 20A</small></p> <p><small>[2] For sub-zero operating temperature, a wide temperature HDD or Solid State Disk (SSD) is required.</small></p> <p><small>[3] For 65W CPUs, the optional fan kit is recommended for operating at ambient temperatures higher than 50°C.</small></p>		



Nuvo-11531/ Nuvo-11588

**Appearance**



**Dimensions**



**Ordering Information**

Model No.	Product Description
<b>Nuvo-11588-PoE</b>	Intel® Core™ Ultra 200 compact fanless computer featuring 4x PoE+ 2.5GbE, 4x USB 3.2, 1x easy-swappable 2.5" SSD tray and 1x external SlimSAS connector
<b>Nuvo-11531-PoE</b>	Intel® Core™ Ultra 200 compact fanless computer featuring 4x PoE+ 2.5GbE, 4x USB 3.2, 1x easy-swappable 2.5" SSD tray
<b>Nuvo-11531</b>	Intel® Core™ Ultra 200 compact fanless computer featuring 4x 2.5GbE, 4x USB 3.2, 1x easy-swappable 2.5" SSD tray
	Optional ignition power control

**Optional Accessories**

<b>DINRAIL-11531</b>	DIN-rail mounting assembly for Nuvo-11588/ Nuvo-11531/ Nuvo-11501 series
<b>AccsyBx-FAN-Nuvo11531</b>	Fan kit with 92mm x 92mm fan for Nuvo-11588/ Nuvo-11531/ Nuvo-11501 series

All specifications and photos are subject to change without prior notice

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660