

**iBOX-N97 R2**  
Fanless Embedded BOX PC



**KEY FEATURES**

- Intel® Alder Lake-N SoC Processor N97
- 1 x 260-pin SO-DIMM DDR4 3200 MHz, up to 32GB
- 6 x USB 3.2 Gen2, 1 x M.2 Key E, 1 x M.2 Key M, 1 x COM, 1 x SATA3
- 2 x Realtek 2.5 Gigabit LAN
- Supports Triple display, 2 x HDMI 2.0b, 2 x DP 1.4a (From Type-C)
- TPM 2.0 onboard IC
- 19V/65W Power Adapter
- 135 x 110 x 44.5mm (5.31" x 4.33" x 1.75"), Fanless Embedded BOX PC

**SPECIFICATIONS**

**Processor System**

CPU	Intel® Alder Lake-N SoC Processors iBOX-N97 R2 (N97, QC, Max Speed Up to 3.6GHz, 12W)
Chipset	SoC
BIOS	AMI SPI 256 Mbit

**Memory**

Technology	Single Channel DDR4 3200 MHz
Capacity	32GB
Socket	1 x 260-pin SO-DIMM

**Graphics**

Controller	Intel® UHD Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Triple-Display (Included 2 outputs from Type-C)

**Expansion Slot**

M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless
-----	---

**Audio**

Interface	Realtek ALC256, High Definition Audio
-----------	---------------------------------------

**Ethernet**

Controller/ Speed	LAN1: Realtek RTL8125BG with 10/100/1000/2500 Mbps LAN2: Realtek RTL8125BG with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

**Storage**

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe Gen3 x1 and SATA3 for SSD *M.2 Key M 2280 (Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

**Front I/O**

USB	2 x USB 3.2 Gen2 (Type-A) 2 x USB 3.2 Gen2 (Type-C, Supports DP 1.4a display output)
COM	1 x COM (RS-232)
Audio	1 (headphone & microphone jack)

**Rear I/O**

HDMI	2 x HDMI 2.0b
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

**Watchdog Timer**

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ..., 255sec

**Power Requirements**

Input PWR	1 x 19V/65W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

**Environment**

Operating Temp	-20°C ~ 40°C with air flow 0.5-0.8 m/s (with extended temp. peripherals)
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

**Mechanical**

Construction	Aluminum housing
Mounting	VESA mount/Wall mount/Din-rail
Dimensions (L x W x H)	135 x 110 x 44.5mm (5.31" x 4.33" x 1.75")
Weight	Net Weight: 0.7kg

**Others**

OS Support	Windows 10/11
TPM	TPM 2.0 onboard IC
Certifications	CE, FCC
Packing List	1 x 19V/65W Power Adapter 1 x Wall mount kit

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660