

MPC152-845

15" XGA TFT Fanless Medical Grade Touch Panel Computer with Intel® Celeron® Processor N3060

Features

- 15" XGA TFT LCD display with LED backlight
- Fanless design with Intel® Celeron® processor N3060
- 2 GbE LANs, 4 USB and 2 COM
- Plastic and IP65-rated front bezel
- Supports RFID (optional)
- External AT/ATX mode selection switch
- Easy access storage design
- Supports panel mount, wall mount, VESA arm and desktop stand
- Adjustable RS-232/422/485 setting via BIOS
- 4th EN 60601-1 (ESD contact 8KV, air 15KV), CE and FCC



A Side view



Introduction

The MPC152-845 is a 15" fanless medical touch panel computer. In response to market demand, this medical panel computer is a cost effective solution. It adopts a modern, super sleek and fanless design and is equipped with a 15" TFT LCD as well as Intel® Celeron® processor N3060 dual core up to 2.48 GHz. For wireless network connection, the MPC152-845 offers 2 PCI Express Mini Card slots. By just plugging in the mini card WLAN card, customers can have instant access to wireless LAN/GPRS/GSM/4G environments. Besides, it provides two types of power input: DC power with terminal block connector and AC power adapter with screw type connector.

Super Slim & Ultra Lightweight Design

With a thickness of 54.6 mm and weight of $3.2~{\rm kg}$ the MPC152-845 is designed for use in space-constrained environments.


Certifications

This 15-inch medical panel platform complies with 4th version of EN 60601-1 and CE, FCC Class B certifications to ensure medical operation safety.

Aluminum Back Chassis with Excellent Thermal Solution

With Axiomtek's patent for plastic plus aluminum mechanism design, the MPC152-845 can dissipate the heat easily and keep the system operation stable.





1. Power switch (ATX) 2. Power input connector (Phoenix) 3. Power input connector (Screw) 4. 2 x USB 2.0 5. Audio (Line-out) 6. 1 x RS-232/422/485 7. 1 x RS-232 8. 2 x USB 3.0 9. 2 x LAN 10. 8 x DIO (programmable, DB9) 11. AT/ATX selectable switch 12. Touch LED indicator 13. Touch on/off button 14. HDD & Power LED indicator

Specifications

Front Bezel	IP65, NEMA 4 rugged protection, plastic front bezel	
LCD Panel	Display Type	15" XGA TFT LCD with LED backlight
	Brightness (cd/m ²)	420 nits (XGA)
	Resolution	1024 x 768 (XGA)
	Viewing Angel (H/V)	160°/160°
Main System	CPU	Intel® Celeron® processor N3060 2 cores (up to 2.48 GHz)
	System Memory	1 x 204-pin DDR3L-1600 SO-DIMM, up to 8GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 2.5" SATA HDD (9.5 mm height) 1 x mSATA
	Watchdog Timer	255 levels, 0 to 255 sec.
	Onboard Graphics	Integrated in Intel® GFX



Specifications

I/O Connector	1 x RS-232	
	1 x RS-232/422/485	
	2 x 10/100/1000 Mbps Ethernet	
	2 x USB 2.0	
	2 x USB 3.0	
	1 x Audio (Line-out)	
	1 x Switch for power on/off	
	1 x AT/ATX selectable switch	
	1 x 8-bit DIO (programmable, DB9)	
Expansion Interface	1 x Full-size PCI Express Mini Card slot with mSATA	
	1 x Full-size PCI Express Mini Card slot with SIM	
Touchscreen	Resistive type	
Power Supply	AC version: 100 to 240 V AC-DC, 65W power adapter or	
	DC version: 9 to 36 VDC with over current protection fuse	
Power Consumption	32 W	
Dimension	387.9 mm (15.27") (W) x 54.6 mm (2.14") (D) x 307.7 mm	
	(12.11") (H)	
Packing Dimensions	510 mm (20.08") (W) x 105 mm (4.13") (D) x 385 mm (15.16") (H)	
Weight (net/gross)	3.2 kg (7.05 lb)/5.1 kg (11.24 lb)	
Operating Temperature	0°C to +40°C (+32°F to +122°F)	
Relative Humidity	20% to 90% @ +40°C; non-condensing	
Operation Vibration	2G, 5 - 500Hz, random for SSD	
Certifications	4th EN 60601-1 (ESD contact 8KV, air 15KV), CE and FCC	

Packing List

- 1 x MPC152-845 1 x Driver CD 1 x Adapter (MPC152-845-J) 1 x Power cord (MPC152-845-J) 1 x Phoenix connector (MPC152-845 DC)

Ordering Information

Standard	itandard	
MPC152-845-J	15" XGA fanless medical touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen, AC-DC 65W power adapter (screw type connector) and EMI class B	
MPC152-845-DC	15" XGA fanless medical touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen and DC power input (terminal block connector)	

Optional Accessories

Wi-Fi + Bluetooth kit		
	881251520A0E	Panel mount kit
	881251521A0E	Wall mount kit
	E226171119	Stand kit
	881251203A0E	RFID kit
	*Specifications and certific	ations may vary based on different requirements.

Optional EOS Installation


WES 7	
WE8S (64-bit)	


Optional OS Installation

Windows® 7	
Windows® 8.1 (64-bit)	
Windows® 10	



Dimensions





336



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660