



## ARC-21W34

21.5" with Full-HD PCAP Multi-touch Intel® Core™ i5-7300U Rugged Touch Panel PC with IET Expansion

- > 21.5" Full HD LCD with PCAP Multi-Touch
- > Onboard Intel® Core™ i5-7300U SoC BGA Processor
- > 1 x 260-pin DDR4 SODIMM Socket, Supports Up to 16GB DDR4 2133Mhz SDRAM
- > Rich I/Os, 2 LAN, 2 COM, 4 USB, SIM Card Slot, Swappable Drive Bay, Speaker out for Flexible Expansion Modules
- > 1 x Mini PCIe Slot
- > Rugged Design for Vibration & Shock Protection, Cableless Design
- > Fanless Operation from -10 ~ 50°C
- > Wide Range DC Power Input from +12~26Vdc
- > Service Window, Easy to Install Memory Module
- > Front panel: IP65, Rear: IP41(except I/O)
- > TPM2.0 (optional)

+ Spec	
<b>-System Information-</b>	
<b>Processor</b>	Onboard Intel® Core™ i5-7300U 2.6GHz SoC BGA Processor
<b>System Memory</b>	One 260-pin DDR4 SODIMM Socket, Supports Up to 16GB DDR4 2133Mhz SDRAM (Non-ECC)
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec./1sec.step
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>CPU Cooler (Type)</b>	Fanless Heatsink
<b>Expansion</b>	
<b>Expansion</b>	1 x mSATA supports on the 1st Mini PCIe slot, Auto switch for mSATA or Mini PCIe 1 x 80-pin IET interface
<b>Storage</b>	
<b>Storage</b>	1 x 2.5" Drive Bay(7mm HDD Restricted)
<b>HDD/ SSD</b>	1 x SATA3
<b>Panel</b>	
<b>LCD Size</b>	21.5" 16:9
<b>Display Type</b>	Full HD
<b>Resolution</b>	1920x1080
<b>Pixel pitch</b>	0.24795mm(H) x 0.24795mm(V)
<b>Luminance</b>	250 cd/m2
<b>Contrast ratio</b>	3000
<b>Viewing angle</b>	89 (U), 89 (D), 89 (L), 89 (R)
<b>Response time</b>	20 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	PCAP Multi-Touch support up to 10 points
<b>Touch Light Transmission</b>	89 %
<b>Touch Controller</b>	EETI
<b>I/O</b>	
<b>USB Port</b>	4 x USB3.0 (2 x Double deck)
<b>COM Port</b>	1 x RS-232/422/485, selectable by BIOS, RS-485 supports Auto Flow, Pin-9 selected by Ring/+5V/+12V) 1 x RS-232
<b>DIO</b>	16-bit GPIO (option by IET DB)
<b>Expansion</b>	1 x mSATA supports on the 1st Mini PCIe slot, Auto switch for mSATA or Mini PCIe 1 x Optional by IET module
<b>Other</b>	3 x Knockouts for Antenna Mounting
<b>System Control</b>	
<b>LED Indicator</b>	HDD LED, Power LED
<b>DC In/Out Characteristics</b>	
<b>Power Type</b>	AT/ATX
<b>Audio</b>	
<b>Audio Codec</b>	Realtek ALC888S
<b>Speaker Output</b>	2 x 2W
<b>Certifications</b>	
<b>Certification Information</b>	CE / FCC Class B
<b>Ethernet</b>	
<b>LAN Chipset</b>	1 x Intel® I211AT 1 x Intel® I219LM
<b>Power Requirement</b>	
<b>DC Input</b>	DC in +12V ~ +26V, wide voltage single power input
<b>DC Input Connector</b>	Lockable DC Jack (Default) optional for phoenix connector



<b>ACPI</b>	Single power ATX Support S0, S3, S4, S5 and ACPI 3.0 Compliant
<b>Power Mode</b>	AT/ATX
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	-10°C ~ 50°C
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	538.05 x 341.05 x 60.05mm
<b>Weight</b>	7.3Kgs
<b>Vibration Test</b>	With SSD/mSATA : 1.5Gms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
<b>Shock Test</b>	Operating with SSD/CFast/mSATA : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G
<b>IP Rating</b>	Front Panel IP65 back cover IP41
<b>Mounting Kit</b>	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
<b>Power Requirement</b>	DC in +12V ~ +26V, wide voltage single power input
<b>Power Mode</b>	AT/ATX
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Die Casting with Cover lens
<b>Construction - Rear</b>	Black Die Casting
<b>Relative Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Drop</b>	ISTA 2A, IEC-60068-2-32 Test:Ed
<b>Software Support</b>	
<b>OS Information</b>	Linux, Windows 10
<b>Ordering Information</b>	
<b>Ordering Information</b>	<p>ARC-21W34-730-B2R 21.5" 1920x1080 Industrial Touch Panel PC, ErP Design, PCAP Multi Touch 7th Gen Intel Core i5 7300U 2.6GHz CPU/2GLAN/2COM/4USB/SPK/12~26V input/12V Adapter</p> <p>ACC-ARC-USB-1R 4 x USB 3.0 Kit for ARC Series</p> <p>ACC-ARC-AUDIO-1R HDMI + 5.1 CH Audio Kit for ARC Series</p> <p>ACC-ARC-MPCIE-1R HDMI + MPCIE w/SIM Kit for ARC Series</p> <p>ACC-ARC-COM-1R 2 x Isolated RS-232 Kit for ARC Series</p> <p>ACC-ARC-COM-2R 3 x RS-232 Kit for ARC Series</p> <p>ACC-ARC-COM-3R 2 x RS-232 + USB Kit for ARC Series</p> <p>ACC-ARC-COM-4R 2 x RS-232 + LAN Kit for ARC Series</p> <p>ACC-ARC-GPIO-1R 12-bit GPIO + 2-pin CAN Bus Kit for ARC Series</p> <p>ACC-ARC-OBDII-1R OBDII - CAN Bus Kit for ARC Series (OBDII/EOBD for Small Vehicle)</p> <p>ACC-ARC-OBDII-2R OBDII - CAN Bus Kit for ARC Series (J1939/J1708 for Large Vehicle)</p> <p>ACC-ARC-OBDII-3R OBDII - CAN Bus Kit for ARC Series (ISO15765-4 for Special Large Vehicle)</p> <p>E1702031833R USA Power Cord</p> <p>E1702031000R EU Power Cord</p> <p>E1702031834R Japan Power Cord</p> <p>E1702031830R UK Power Cord</p> <p>E1702031831R Australia Power Cord</p>

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660