




28.1" Primary Control Monitor
Raptor[®] SQ2825



Design

Slim Bezels



The unobtrusive bezels are approximately 40% slimmer than the previous model, measuring just 36.1 mm on all sides so ATCOs can focus more on the screen.

Protection Glass




Protection glass is optional with two variations — standard and fully flat. Standard glass covers the visible part of the LCD panel and extends to the inner bezel. Fully flat glass reaches to the edges of the monitor for a smooth, streamlined look. The monitor's housing is built with edge protection for fully flat glass so it is not exposed and vulnerable to damage.

Rounded Corners



The monitor's design features rounded corners and edges for a pleasing and modern aesthetic.


Balanced Design



The monitor's depth has been reduced, bringing the weight distribution closer to the center of mass for less stress on mounting fixtures over time. It is also 50% lighter and more compact than the previous model, weighing just 14.6 kg.


Direct Backlight System

Brightness Uniformity




The monitor's unique LED direct backlight system has 16% more LED cells than its predecessor for increased efficiency and performance. It offers superior brightness uniformity for smoother images compared to edge-type backlight solutions.

Mission-Critical Redundancy




The direct backlight system is divided into four interchangeable quadrants, each of which performs consistently over a lifetime of 100,000 hours. Each quadrant is controlled by two independent sub-unit driver boards that protect the on-screen information from being visually impacted in the unlikely event that an LED stops performing.

Wide Brightness Range



The monitor can be adjusted within a wide brightness range of 2 to 500 cd/m² to suit your environment's requirements as well as the needs of the ATCO.

Brightness Stabilization



EIZO's fully automated stability function uses an internal backlight sensor to stabilize the brightness level throughout the life of the monitor, compensating for fluctuations caused by variations in ambient temperature and the passage of time.


Durability and Reliability

Industrial-Grade Housing



The monitor's housing uses full sheet steel industrial-grade housing for durability in demanding mission-critical environments.

Fanless Operation




The monitor provides noiseless, fanless operation while still maintaining low heat output without impacting performance.

Built-In Power Supply



The power supply of the monitor is built in, freeing the installation space of an additional power brick and cabling. A secondary power supply is available as an option.

24/7 Operation




The Raptor SQ2825 is developed specifically for meeting the stringent requirements of mission-critical ATC environments with 24/7 operation.

10+ Years of Primary Control Monitor Manufacturing

EIZO has been an industry leader in the innovation and development of quality 2K primary control monitors for ATC since 2005. Backed by over 45 years of technical expertise in visual display solutions, the Raptor SQ2825 is a 5th generation 2K x 2K monitor that culminates the features and functionality of EIZO's line of primary control monitors while adding further value with new technology and improved operational reliability.

Extensive Customization

EIZO offers extensive customization in order to meet the specific needs of individual control centers.



Contact us to configure your monitor.
atc@eizo.com

Complete Connection

Dual link DVI video signal inputs are included as standard as well as the option of additional DisplayPort or analog 5-BNC inputs. The monitor also comes equipped with a wide range of communication interfaces for connection to a network, remote monitor management, or maintenance purposes — RS232, RS422, USB, and TCP/IP.

Non-Intrusive Hardware Calibration

The monitor comes equipped with EIZO's hardware calibration functionality using the optional EIZO EACAL-R01 luminance reader. Easily accessed through the OSD menu, calibration of the backlight brightness, gamma, and white point can be carried out in just minutes. No additional software is needed, ensuring calibration operation is non-intrusive to your system.

Optional Accessories

EACAL-R01

External advanced serial luminance meter for high-precision monitor calibration.



EACON-S01

External OSD keyboard for control of a single monitor.



Specifications

Cabinet Color	Black	
Panel	Type	VA
	Backlight	Direct LED backlight system
	Size	28.05" / 71.2 cm
	Native Resolution	2048 x 2048 (1:1 aspect ratio)
	Viewable Image Size (H x V)	503.8 x 503.8 mm
	Pixel Pitch	0.246 x 0.246 mm
	Grayscale Tones	256 tones
	Display Colors	16.7 million
	Viewing Angles (H / V, typical)	170°, 170°
	Brightness (typical)	500 cd/m ² (maximum) 2 cd/m ² (minimum)
Contrast Ratio (typical)	1800:1	
Response Time (typical)	25 ms	
Video Signals	Input Terminals	DVI-I 29 pin (dual-link) x 2 5-BNC (single or dual, optional) or DisplayPort (dual, optional)
	Digital Scanning Frequency (H / V)	2 – 130 MHz (pixel) / 60 Hz
	Analog Scanning Frequency (H / V)	30 – 130 kHz / 50 – 70 Hz
	Sync Formats	Separate Sync 1-5 Vpp (75 Ω) / Sync on Green
USB	Function	2 upstream
	Standard	Rev. 2.0
Power	Power Requirements	AC 90 – 264 V, 47 – 63 Hz
	Maximum Power Consumption	120 W (Brightness: 500 cd/m ²)
	Typical Power Consumption	60 W (Brightness: 150 cd/m ²) 50 W (Brightness: 70 cd/m ²)
	Standby Mode	0.5 W or less
	Power Management	VESA DPMS
	Features and Functions	Brightness Stabilization OSD Languages Hardware Calibration External Keyboard Preset Modes Communication Protocol Communication Interface
Physical Specifications	Dimensions (With Stand, W x H x D)	576 x 603 – 688.4 x 280.6 mm
	Dimensions (VESA Mount, W x H x D)	576 x 576 x 119 mm
	Dimensions (Chassis Mount, W x H x D)	603 x 639 x 119 mm
	Net Weight (With Stand, W x H x D)	18.6 kg / 41 lbs
	Net Weight (VESA Mount, W x H x D)	14.6 kg / 32.2 lbs
	Net Weight (Chassis Mount, W x H x D)	15.1 kg / 33.3 lbs
	Height Adjustment Range	85 mm
	Tilt	25° Up, 0° Down
	Swivel	172° Right, 172° Left
	Hole Spacing (VESA Standard)	100 x 100 mm, 200 x 100 mm
Environmental Requirements	Operating Temperature	0 – 40°C / 32 – 104°F
	Operating Humidity (R.H., non condensing)	max. 95% (no condensation)
	Storage Temperature	-25 – 60°C / -13 – 140°F
Certifications & Standards	CE, UL, c-UL, FCC, RoHS, WEEE, CCC	
Warranty	Two Years	

EIZO Technologies GmbH

Bürgermeister-Seidl-Str. 8, 82515 Wolfratshausen, Germany
 Phone : +49-8171-3492-11 Fax : +49-8171-3492-16
atc@eizo.com
www.eizoglobal.com

All product names and logos are trademarks or registered trademarks of their respective companies.
 Raptor and EIZO are registered trademarks of EIZO Corporation.
 Screen images provided by THALES.
 Specifications are subject to change without notice.

Copyright © 2018 EIZO Corporation. All rights reserved.
 Printed in Japan, 2, 2018, 0.5K (160806)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660