



## ESM-BYT2

### Intel® Celeron®/Atom™ SoC Processor Type6 COMe Compact Module

- > Onboard Intel® Celeron®/Atom™ SoC BGA Processor
- > One 204-pin DDR3L SODIMM Up to 8GB DDR3L 1066/1333 SDRAM
- > Support Dual-channel 18/24-bit LVDS, Display Port, HDMI, DVI, VGA, eDP (Option)
- > Intel® I211AT Gigabit Ethernet
- > 2 SATA II, 7 USB 2.0, 1 USB 3.0, 8-bit GPIO
- > HD Audio Interface
- > +9 ~ +19V Wide Range Power Input
- > Type 6 Rev. 2.1 Pin-out
- > Extended Temperature: -40 ~ +85°C

**Spec**

-System Information-	
<b>Processor</b>	Intel® Celeron®/J1900 4-Core 2.0GHz processor Intel® Atom™ E3845 4-Core 1.91GHz processor Intel® Atom™ E3825 2-Core 1.33GHz processor
<b>System Memory</b>	1 x 204-Pin DDR3L 1066MHz SO-DIMM up to 8 GB or 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB Processor E3845 & J1900 only support 1333MHz
<b>BIOS Information</b>	AMI uEFI BIOS, 64Mbit SPI Flash ROM
Expansion	
<b>Expansion</b>	3 x PCIe1
I/O	
<b>USB Port</b>	7 x USB 2.0 1 x USB 3.0
<b>COM Port</b>	2 x UART
<b>SATA</b>	2 x SATA II
<b>DIO</b>	1 x 8bit GPIO
<b>MIO</b>	1 x SMBus 1 x LPC 1 x I2C
Display	
<b>Graphic Chipset</b>	Intel® Valleyview SoC integrated Graphics
<b>Spec. &amp; Resolution</b>	VGA: Max. resolution 2560x1080@ 60Hz LVDS: Max. resolution 1920x1080@ 60Hz DP: Max. resolution 2560x1080@ 60Hz HDMI: Max. resolution 1920 x 1080@60 24bpp
<b>Multiple Display</b>	VGA+LVDS
<b>LVDS</b>	CH7511B (eDP to LVDS)
<b>DDI</b>	HDMI DVI DisplayPort
Audio	
<b>Audio Codec</b>	Intel® Valleyview SoC integrated
<b>Audio Interface</b>	Intel® High Definition Audio
Certifications	
<b>Certification Information</b>	CE, FCC Class B
Ethernet	
<b>LAN Chipset</b>	1 x Intel® I211AT
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
Mechanical & Environmental	
<b>Operating Temperature</b>	0°C ~ 60°C (32°F ~ 140°F) (Standard) -40°C ~ 85°C (-40°F ~ 185°F) (Extended)
<b>Storage Temperature</b>	-40°C ~ 85°C (-40°F ~ 185°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Power Requirement</b>	+9V ~ +19V
<b>ACPI</b>	Single Power ATX Support S0, S3, S4, S5 ACPI 3.0 Compliant
<b>Power Mode</b>	AT/ATX
<b>Dimension (L x W)</b>	3.7" x 3.7" (95mm x 95mm)
Software Support	
<b>OS Information</b>	Win 8 / Win 7 / Linux / Android
Ordering Information	



<b>Ordering Information</b>	<p>ESM-BYT2-E3845-A2R Intel® Atom™ SoC Processor E3845D1 Type6 COMe Compact Module</p> <p>ESM-BYT2-E3825-A2R Intel® Atom™ SoC Processor E3825D1 Type6 COMe Compact Module</p> <p>EEV-EX14-B1R mATX Ev. Board for COMe Type 6 A2</p> <p>ESM-BYT2-HSK-A1R Heatsink for ESM-BYT2 W/O FAN H=36mm</p> <p>ESM-BYT2-HSP-A1R Heatspreader for ESM-BYT2</p>
-----------------------------	--

[www.avalu.com.tw](http://www.avalu.com.tw)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660