



UTX-111

UTX Motherboard

Spotlight Features

- Intel® Atom™ Baytrail-M/D Processor
 - UTX-111D (J1900)
 - UTX-111N (N2930)
- Integrated Intel® Gen7 Intel Graphics DX 11*, OGL3.2
- Supports Single Channel DDR3L 1066/1333MHz, 1 x SO-DIMM, up to 4/8GB system memory
- 2 x HDMI, 1 x Dual Channel 24-bit LVDS
- 1 x USB 3.0, 2 x USB 2.0, 1 x SATA2
- 1 x mini-PCIe(1 x Half size), 1 x mSATA (Full size, co-lay with mini-PCIe function)
- Gigabit LAN : 2 x Intel 210 x 1
- 12 V DC-in
- Soc Buttom up design

Specifications

Processor System

Dimensions	111.76 x 116.84 mm(10 layer)
CPU	Intel® New Atom™ Baytrail-M/D J1900 / N2930 / N2807 Supports Hyper-Threading Technology
Core Number	(By CPU, Max 4)
Max Speed	(By CPU)
L2 Cache	(By CPU)
Chipset	(By CPU)
BIOS	UEFI

Expansion Slot

PCI	0
Mini-PCIe	1 x full size co-lay with mSATA
mSATA	1 (Full Size)
SIM slot	1
CFast Card Socket	0

Memory

Technology	Single Channel DDR3L 1066/1333 MHz SDRAM
Max.	4/8GB
Socket	1 x SO-DIMM

Graphics

Controller	Intel® Gen7 Intel Graphics DX 11*, OGL3.2
VRAM	Shared Memory
VGA	Supports max. resolution 1920X1200
LVDS	Dual channel 24-bit, max resolution 1920 x 1200@60Hz
HDMI	Supports HDMI 1.4a, max resolution 1920x1200
DVI	No
Display Port	No
Multi Display	Yes (Dual Display)

Ethernet

Interface	10/100/1000 Mbps
Controller	2 x Intel 210
Connector	2 x RJ-45

SATA

Max Data Transfer Rate	SATA2 (3.0Gb/s)
------------------------	-----------------

Rear I/O

VGA	0
HDMI	2 (1 x HDMI, 1 x Micro HDMI)
DVI-I/D	0
Display Port	0
Ethernet	2
USB	1 x USB 3.0 Compliant, 1 x USB2.0 Compliant 1 x Micro USB 2.0 SMT type connector
Audio	1 (Line out/Mic out)
Serial	0
e-SATA	0
PS/2	0

Internal Connector

USB	0
LVDS/Inverter	1/1
VGA	1 (Pin heater 2.0 mm Pitch)
Serial	(RS-232/422/485 x 1, RS232 x 1) Pin heater 2.0 mm pitch COM1 Pin9 (+5V & +12V)
SATA	1 x SATA2 (3.0Gb/s)
m-SATA	1
Mini-PCIe	2 (full/Half size)
Parallel	0
IrDA	0
GPIO	4 x GPI + 4 x GPO Pin heater 2.0 mm pitch
SATA PWR Output Con	1
Speaker Header	1

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 segments, 0,1,2...255sec/min

Power Requirements

Input PWR	12V DC Jack
Power On	AT/ATX Supported AT: Directly PWR on as Power input ready ATX: Press Button to PWR on after Power input ready

Environment

Operating Temperature	0°C – 60°C
-----------------------	------------

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660