

Panel

Diagonal Size	65
Type	120Hz E-LED BLU
Resolution	3840*2160 (4K UHD)
Pixel Pitch(mm)	0.124 x 0.372 (mm)
Active Display Area(mm)	1428.48(H) x 803.52(V)
Brightness(Typ.)	Landscape : 600nit(peak 1,500nit), Portrait : 500nit(peak 1,000nit) nit
Contrast Ratio	6000:01:00
Viewing Angle(H/V)	178/178
Response Time(G-to-G)	6ms (Typ)
Display Colors	1.07B(True Display 10bit)
Color Gamut	Color Volume 100% (DCI-P3)
Haze	0%

Display

Dynamic C/R	Mega	H-Scanning Frequency
V-Scanning Frequency	48 ~ 75HZ	Maximum Pixel Frequency

Display

Speaker Type	Built in Speaker(10W + 10W)
--------------	-----------------------------

Connectivity

Input	RGB	Display Port 1.2 (1)
	Video	HDMI 2.0 (2)
	HDCP	HDCP2.2
	Audio	N/A
	Usb	USB 2.0 x 2
Output	RGB	N/A
	Video	N/A
	Audio	HDMI #1 ARC support
	Power Out	N/A
External Control		RS232C(in/out), RJ45
External Sensor		N/A
Tuner		N/A

Power

Type	Internal
Power Supply	AC 100 - 240 V~ (+/- 10 %),
Power Consumption	

Max[W/h]	
Typical[W/h]	
BTU(Max)	N/A
Sleep mode	less than 0.5W
Off mode	less than 0.5W

Mechanical Specification

Dimension (mm)	Set	1444.1 X 820.9 X 44.0
	Package	1585 x 958 x 178
Weight (kg)	Set	
	Package	
VESA Mount (mm)		400x400
Mounting Hole		N/A
Protection Glass		N/A
Stand Type		Foot Stand (Optional)
Media Player Option Type		N/A
Bezel Width (mm)		bezel-less

Operation

Recommended Usage Hours	
Operating Temperature	0.0 °C ~ 40.0 °C
	Humidity

Feature

Key Features		QLED Signage Display Slim & Light with Built-in MagicInfo S5, 5000hrs
Special Features		H/W : Temperature Sensor, Clock Battery(168hrs Clock), Speaker(10W 2ch), Wi-Fi/BT, Source Switching & Recovery, Button Lock, Hot key option
Internal Player	Processor	Coretex A72 1.7GHz Quad-Core
	On-Chip Cache Memory	L1 Instruction Cache : 48KB 32KB L2 Cache : 2MB
	Clock Speed	1.7GHz Quad-Core CPU
	Main Memory Interface	3GB 3ch 64bit LPDDR4 1.6GHz
	Graphics	2D & 3D Graphic Accelerator 32bpp Graphic resolution : Output resolution : 3840x2160 (4K) (graphic processing result.)
	Storage (FDM)	8GB (3.88GB Occupied by OS) Available

	Multimedia	Video Decoder - MPEG 1/2, H.264/AVC - UHD H.264/AVS/AVS+, MVC - VP8, VP9, DSP(Decoder) - MPEG, AC3, and etc
	IO Ports	USB 2.0
	Operating System	Tizen 3.0 (VDLinux)

Certification

Safety	60950-1
EMC	Class A

Accessory

	Included	Quick Setup Guide, Warrant Cord, Remote Controller, B
Optional	Stand	STN-L6500E
	Mount	WMN6575SD WMN-M11E
	Specialty	CLM450D

Media Player

Media Player	N/A
---------------------	-----

30 ~ 81kHz
594MHz

--

50/60 Hz

253
144

23.9
32.7

16-Jul
%

& Light Signage
SSSP 5.0
.Pivot Display, Keeping), Built in T S/W : Auto ry,LFD Home UI, 1, Plug&Play
Core CPU
L1 Data Cache :
Hz
or Data Format : 1920x1080 160 (Scale up from
)/S, 4.12GB

74, H.263, 7C, VC-1, HEVC, JPEG Audio , AC4, DD, MP3

ty Card,Power atteries
(Slim W/M)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660