

The Brightest Choice For Seamless Innovation NARROWEST BEZEL DISPLAY WV70/70B



WV70/70B 55"



SLIMMER BEZEL

The slim bezels create powerful and impactful video walls that can be easily installed, maintained and managed.

55WV70/70B



Bezel to Bezel
5.3mm

Competitor(55")



Bezel to Bezel
5.5mm

LED LOW POWER CONSUMPTION

By using LED panels without mercury or other harmful substances, WV70 is eco-friendlier than any of its competitors. Most of all, WV70 consumes less energy.



210W(Typ), 120W(SES)


Competitor



225W(Typ)

SHINE-OUT

Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.




55WV70 Competitor

IPS SUPERB PICTURE QUALITY

NO BLACKENING DEFECT

Hardly affected by light or heat, hence no blackening.




IPS

Normal

TRUE WIDE

No color changes or distortion from any viewing angle



IPS

Normal

STABLE PANEL

When touch the screen, it can also display consistently with leaving no mark.



IPS

Normal

NARROWEST BEZEL DISPLAY

WV70/70B 55F"




- Brightness : 800nit (55WV70), 500nit (55WV70B)
- Shine-Out (55WV70)
- Direct LED
- 2 pairs of Handle
- Super Narrow Bezel (Bezel to Bezel 5.3mm) technology allows public to see more of everything
- USB playback is simple, easy solution without additional cost



FEATURES

- Direct LED
- Panel Size : 55"
- Bezel to Bezel Size : 5.3mm
- Slim Depth : 99mm
- Power Consumption : 210W (Typ), 120W (SES) (55WV70)
- Tile Mode : 15 x 15
- USB Playback → Low cost media player
- Hi Tni : 110°C (Competitors : 75°C)
- Shine-Out (55WV70) → High Visibility

DIMENSION (unit : mm)



SPECIFICATIONS

	WV70	WV70B
PANEL	Screen Size	55F"
	Panel Technology	IPS (LED BLU)
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	800nit 500nit
	Contrast Ratio	1,400 : 1
	Dynamic CR	500,000 : 1
	Viewing Angle (H x V)	178 x 178
	Response Time	8ms (G to G, *WOT)
	Input (Rear)	
CONNECTIVITY	Digital	DVI-D(I), HDMI(I), Display Port(I) with HDCP for all input
	Analog	RGB(I), Shared Component(I), AV(I)
	Audio	PC Audio In
	External Control	RS232C(I), RJ45(I), IR Receiver(I)
	USB	USB
	Output (Rear)	
	Digital	DVI-D
PHYSICAL SPECIFICATION	Analog	RGB
	Audio	External Speaker
	External Control	RS232C
	Bezel Width	3.4mm (left/top) / 1.9mm (right/bottom)
	Monitor Dimension (W x H x D)	121.52cm x 68.6cm x 9.9cm
	Weight (head)	33.4kg
	Carton Dimensions (W x H x D)	140.0cm x 80.5cm x 33.0cm (Box outer size)
SPECIAL FEATURES	Packed Weight	42.4kg
	VESA Standard Mount Interface	600mm x 400mm
ENVIRONMENT CONDITIONS	Additional	Temp sensor, 15x15 Tile mode, 2 pairs of Handle, Shine out, USB playback
	Operation Temperature	0°C ~ 40°C
POWER	Operation Humidity	10% ~ 80%
	Power Supply	100-240V~, 50/60Hz
STANDARD(CERTIFICATION)	Power Consumption	
	Typical / Smart Energy Saving	210W (Typ) / 120W (SES) 160W (Typ) / 90W (SES)
	DPMS	1.0W (RGB), 1.0W (HDMI)
	Power Off	0.5W
MEDIA PLAYER COMPATIBILITY	Safety	UL / c-UL / CB / TUV / KC
	EMC	FCC / CE / KCC
SOFTWARE COMPATIBILITY	ErP / Energy Star	Yes / Yes
	Slot PC compatible (optional)	No
ACCESSORY	External Media player Attachable	Yes
	Supersign Compatibility	Elite-w / Elite-w lite (Only control)
INCLUDED	Remote Controller, Power Cable, RGB Cable, DVI Cable, Manual, IR Receiver, RS-232C Cable, Tiling Guide, Screw, Ring Core	

* WOT : Within Operation Temperature

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660