

INJ-C201G-bt-100-T

Industrial Gigabit Enhanced PoE++ Injector
- 1*10/100/1000Base-T(X) with Enhanced PoE-PSE
(100W/Port) + 1*10/100/1000Base-T(X), 48-55VDC,
EOT: -40°C to 75°C



Features


- ▶ Supports 10/100/1000Tx for PoE & Data Out
- ▶ IEEE 802.3af/at/bt Compliant PoE
- ▶ Provide Data and Power over Ethernet to Power Device
- ▶ Provides up to 100 Watts on PoE Port
- ▶ Redundant 48~55VDC power inputs design
- ▶ IP30 Protection
- ▶ Dip-switch setting for PoE mode and dual PD check
- ▶ Operating Temperature Range – -40°C to 75°C
- ▶ DIN-Rail or Wall Mountable
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' INJ-C201G-bt-100-T, solve the problem simply by deploying data and power from non-PoE switch and power input to the PD device. PoE injector is a brilliant low-cost solution for the case that only one side of devices is supporting PoE function. Therefore, INJ-C201G-bt-100-T will be your best choice to deal with the lack of PoE function cases.

Additionally, INJ-C201G-bt-100-T supports power input from 48VDC to 55VDC, ensuring full 90W PoE output, in compliance with IEEE 802.3bt standard, for better usage in the automation industry. Moreover, for some special application which eagers for more PoE power from the PSE device, this model also supports Enhanced PoE mode to offer up to 100W to the powered device. INJ-C201G-bt-100-T with fan-less design, besides extending surely apply to various industrial applications, works perfectly in polarized temperature from -40°C to 75°C, and undoubtedly becomes your best option in the industrial market.

DIMENSIONS



SPECIFICATIONS

Technology		Power Requirement	
Standards	IEEE 802.3 10BaseT Ethernet	Input Voltage	48~55VDC Redundant Input
	IEEE 802.3u 100BaseTX Fast Ethernet	Power Connection	1 removable 4-contact and 2-contact terminal block
	IEEE 802.3ab 1000BaseT(X)	Relay Contact	24VDC, 1A resistive
	IEEE 802.3af/at/bt Power over Ethernet	Reverse Polarity Protection	Present
Switch Properties		Overload Current Protection	Present
Transfer Rate	14,880pps for Ethernet Port	PoE Pin Assignment	V-, V-, V+, V+, for pin 1, 2, 3, 6; V+, V+, V-, V-, for pin 4, 5, 7, 8 *Support Modes: Mode A, Mode B, 4-Pair Mode
	148,800pps for Fast Ethernet Port		
	1,488,000pps for Gigabit Ethernet Port		
Interface		PoE Power Budget	100Watts
Ethernet Port	2*10/100/1000BaseT(X) (1*Data IN, 1*PoE OUT)	System Power Consumption	1.6W
DIP Switch	DIP Switch 1: PoE Mode	Environmental Limits	
	On - Enhanced / Off (default) - Standard	Operating Temperature	-40°C to 75°C
	DIP Switch 2: Dual PD Check	Storage Temperature	-40°C to 85°C
LED Indicators	On - Enable / Off (default) - Disable	Ambient Relative Humidity	5 to 95%, (non-condensing)
	Power, PoE	Regulatory Approvals	
Mechanical Characteristics		EMI	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
Housing	Metal, IP30 protection	EMS	CE EN55035/EN61000-6-2, IEC61000-4-2,3,4,5,6,8
Dimensions	30 x 95 x 75 mm (W x H x D)	Free Fall	IEC60068-2-32
Weight	Unit: 0.80 lb.	Shock	IEC60068-2-27
	Shipping: 1.14 lbs.	Vibration	IEC60068-2-6
Mounting	DIN-Rail Mounting, Wall Mounting	Green	RoHS Compliant
Protection		Certifications	FCC, CE, UL 61010-1, UL 61010-2-201
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable	Compliance	NEMA TS1/TS2
	EIA/TIA-568 100-ohm (100m)	Warranty	5 Years
	100Base-TX: 2-pair UTP/STP Cat. 5 cable		
	EIA/TIA-568 100-ohm (100m)		
	1000Base-TX: 4-pair UTP/STP Cat.5/5E cable; EIA/TIA-568 100-ohm (100m)		
NOTE: The total length from the device A through the injector to the device B must not exceed 100 meters			

ORDERING INFO

INJ-C201G-bt-100-T	Industrial Gigabit Enhanced PoE++ Injector - 1*10/100/1000Base-T(X) with Enhanced PoE-PSE (100W/Port) + 1*10/100/1000Base-T(X), 48-55VDC, EOT: -40°C to 75°C
--------------------	--

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660