

### iEP-5020G Series Industrial IoT Controller

**ASRock**  
— Industrial —

Preliminary



Basic SKU

PoE SKU  
5LAN SKU

DIO SKU

#### KEY FEATURES

- Latest and Powerful Intel® Atom® x7433RE Processor (Amston Lake)
- Fan-less and Rugged Design
- -40°C to 70°C Wide Operating Temp. for Basic SKU
- -40°C to 50°C Wide Operating Temp. for PoE SKU
- 6-36VDC Wide Range Power Inputs for Basic SKU
- 19-36VDC Wide Range Power Inputs for PoE SKU
- Most Flexible IOs and Expansion for Industrial Applications
- Intel® TCC and TSN Support for Real-Time Computing
- DIN Rail or Wall Mount Options
- 4 x Intel 1G LAN (2 Support IEEE 802.3AF PoE Ports)
- 1 x Intel 2.5G LAN
- Support Intel® IN-Band ECC

#### SPECIFICATIONS

##### System Core

Processor	Intel® Atom® x7000RE Processor (Amston Lake Platform) - Intel® Atom® x7433RE, 4C, 1.5GHz, 9W
Video	1 x Type-C, 1 x DP1.4a
Memory	1 x DDR5 4800MHz SO-DIMM, up to 16GB (In-Band ECC)

##### I/O Interface

Ethernet	2 x Intel® I210-IT (1GbE) 1 x Intel® I226-IT (2.5GbE, support TSN) 2 x Intel® I210-AT for PoE SKU/5LAN SKU
Ethernet/PoE (Option)	2 x Intel® i210AT, each port supports IEEE 802.3AF PoE for PoE SKU
Serial Port	2 x RS-232/422/485 (9-pin D-sub connector)
USB	2 x USB 3.2 Gen2 1 x USB2.0 1 x Type-C USB3.2 Gen2
Digital I/O	8DIs/8DOs with sink/source isolation 3KV for DIO SKU
Audio	1 x Mic in 1 x Line out

##### Expansion

SIM	1 x Nano SIM Card slot
RF& Antenna (Option)	M.2 Wi-Fi 6E module supports IEEE 802.11 a/b/g/n/ac/ax + BT 5.2 - 3 x 4G LTE antenna and 2 x Wi-Fi antenna - 4 x 5G antenna and 2 x Wi-Fi antenna
M.2 Socket	1 x M.2 3042/3052 Key B (PCIe Gen3x1 / USB3.2 Gen1x1 mode) - Support 4G LTE/5G module 1 x M.2 2230/2260 Key E (PCIe Gen3x1 / USB2.0 mode) - Support Wifi/BT module

##### Manageability / Security

Manageability	WDT, Intel® In-Band Manageability
Security	TPM2.0

##### Power Supply

DC Input	2 x 3-pin terminal block (Phoenix type) for 6 to 36V DC input (For Basic/5LAN/DIO SKU) 2 x 3-pin terminal block (Phoenix type) for 19 to 36V DC input (For PoE SKU) - OVP, UVP, OCP, plus 80V surge protection
AC to DC Adaptor (Option)	AC input 100-240Vac, 1.5A 50-60Hz, DC output 19V, 3.42A, 65W Adaptor (For Basic/5LAN/DIO SKU) AC input 100-240Vac, 1.8A 50-60Hz, DC output 19V, 6.32A, 120W Adaptor (For PoE SKU)

##### Storage Device

SD Slot	1 x Micro SD card slot(SD Card specification version 3.01)
M.2 Socket	1 x M.2 2280 Key M (PCIe Gen3x2)

##### Mechanical

Dimensions	58mm (W) x 125mm (D) x 157mm (H)
Indicator	1 x NVMe Storage LED 1 x Wi-Fi / BT LED 2 x Diagnostic LED 2 x Power LED
Function	Power on Button with LED
Net Weight	TBD
Mounting (Option)	DIN-Rail or Wall mounting

##### Environmental

Operating Temperature	For Basic/5LAN/DIO SKU: -40°C ~ 70°C (-40°F~158°F) (w/ airflow 0.5~0.8m/s) For PoE SKU : -40°C ~ 50°C (-40°F~122°F) (w/ airflow 0.5~0.8m/s)
Storage Temperature	-40°C ~ 85°C (-40°F~185°F)
Humidity	-95% @ 40°C (non-condensing)
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes with SSD
ESD	Contact +/-8 KV, Air +/-15 KV
Shock	Operating 100G, half sine 11 ms duration with SSD
EMC	CE (EN61000-6-4/-2) and FCC Class A
Safety	LVD

##### Add-on Feature / OS Support

Real-Time Enablement	TSN, TCC support under Ubuntu (only LAN1)
OS Support	Windows®, Linux

Order Information	SKU	Processor	Storage	Wi-Fi*	4G LTE/5G*	LAN	PoE	DI/DO
iEP-5020G-020	Basic SKU	x7433RE	M.2 Key M	Support	Support	3	Not Support	Not Support
iEP-5020G-021	PoE SKU			Support	Support	5	Support	Not Support
iEP-5020G-022	5LAN-WIFI			Support	Not Support	5	Not Support	Not Support
iEP-5020G-023	5LAN-5G			Not Support	Support	5	Not Support	Not Support
iEP-5020G-024	DIO SKU			TBD	TBD	3	Not Support	Support

\*The Wi-Fi, 4G LTE and 5G module kits are purchased separately.

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660