

Preliminary

# CAB-IVI701

QSeven Carrier Motherboard

## Coming Soon

### KEY FEATURES

- Supports QSeven Module
- 1 x PCIe x2 (Gen3), 1 x USB 3.2 Gen1, 2, USB 2.0, 1 x USB 2.0 OTG, 1 x M.2 Key B, 1 x M.2 Key M, 1 x M.2 Key E, 2 x COM, 2 x SATA3
- 1 x Realtek Gigabit LAN
- 1 x HDMI 2.0a or 1 x DP 1.2, 1 x LVDS or 1 x eDP, 2 x MIPI-CSI (By CPU Board)
- 1 x SIM Socket
- 1 x SD Slot
- 20V, 3A with USB Type-C

### SPECIFICATIONS

#### Form Factor

Dimensions (LxWxH)	Micro ATX (9.6-in x 9.6-in)
--------------------	-----------------------------

#### Processor System

CPU	By CPU Board
Chipset	By CPU Board
BIOS	AMI SPI 128 Mbit (For x86 CPU)

#### Memory

Technology	By CPU Board
Capacity	By CPU Board

#### Graphics

Controller	By CPU Board
HDMI	By CPU Board (shared with internal Display Port, by CPU Board)
DisplayPort	By CPU Board (shared with internal HDMI, by CPU Board)
LVDS	By CPU Board, up to Dual channel 24 bit up to 1920x1080 (shared with internal eDP, by CPU Board)
eDP	By CUP Board (shared with internal LVDS, by CPU Board)
MIPI	2 x MIPI-CSI (By CPU Board)

#### Expansion Slot

PCIe	1 x PCIe x2 (Gen3)
M.2	1 x M.2 (Key B, 3042 / 3052) (PCIe x1 Gen3 + 1 x USB 3.2 Gen1 + 1 x USB 2.0) 1 x M.2 (Key M, 2242/2260/2280) (PCIe x1) 1 x M.2 (Key E, 2230) (PCIe x1 + 1 x USB 2.0)
SIM Socket	1 x Socket connected to M.2 Key B

#### Audio

Interface	Nuvoton NAU88U22A, High Definition Audio Mic-In, Line-Out
-----------	---

#### Ethernet

Controller/ Speed	By CPU Board
Connector	1 x RJ-45

#### Rear I/O

HDMI	1 x HDMI 2.0a
DisplayPort	1 x DP 1.2
Ethernet	1 x 1 Gigabit LAN
USB	1 x USB 3.2 (GEN1) 2 x USB 2.0 1 x USB 2.0 OTG
Audio	2 (Mic-in, Line-out)
COM	2 x COM (RS485)

#### Internal Connector

LVDS	1
eDP	1
SATA PWR Output	1
Speaker Header	1
Audio Header	1
MIPI	2 x MIPI-CSI

#### Storage

M.2	1 x M.2 (Key M, 2242/2260/2280) with PCIe x1 Gen3
SATA	2 x SATA3 (6Gb/s)
SD Slot	1

#### Power Requirements

Input PWR	20V, 3A with USB Type-C connector
-----------	-----------------------------------

#### Environment

Operating Temp	0°C - 60°C
Storage Temp	-40°C - 85°C
Operating Humidity	5% - 90%
Storage Humidity	5% - 90%

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660