

iEPF-7001

Fanned BOX PC



IoT Solutions
Alliance

ASRock
— Industrial —



KEY FEATURES

- Intel®10th Gen LGA1200 Processors, up to 65W
- 2 x 260-pin SO-DIMM DDR4-2933MHz up to 64GB (32GB per DIMM)
- 2 x USB 3.2 Gen1 (Type-A), 2 x USB 3.2 Gen1 (Type-C), 4 x USB 2.0
- 1 x M.2 Key E, 1 x M.2 Key M, 1 x SATA3, 1 x COM
- 1 x Realtek 1 Gigabit LAN
- Supports dual display, 1 x HDMI 1.4b, 1 x DP 1.4a, 1 x VGA
- 1 x 19V/90W AC-DC power brick adapter
- 178 x 178 x 34mm, Fanned Barebone

SPECIFICATIONS

Processor System

CPU	Intel®10 th Gen (Comet lake-S) Core™ Processors up to 65W
Chipset	H410
Socket	LGA1200
BIOS	AMI SPI 128 Mbit

Memory

Technology	Dual Channel DDR4 2933 / 2666 / 2400 MHz - Intel Core i9 / i7 CPUs support DDR4 up to 2933 MHz - Intel Core i5/i3 CPUs support DDR4 up to 2666 MHz - Intel Pentium/Celeron CPU support DDR4 up to 2400 MHz
Capacity	64 GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	Integrated Intel®UHD Graphics
HDMI	HDMI 1.4b Max resolution up to 4096x2160@30Hz
DisplayPort	DisplayPort 1.4a Max resolution up to 4096x2160@60Hz
VGA	Max resolution up to 1920x1200@60Hz
MultiDisplay	Dual Display

Expansion Slot

M.2	1 x M.2 Key E (Intel® Wi-Fi 6 3168 + Bluetooth 4.2)
-----	---

Audio

Interface	Realtek ALC233, High Definition Audio
-----------	---------------------------------------

Ethernet

Controller/ Speed	1 x Realtek RTL8111GN with 10/100/1000 Mbps
Connector	1 x RJ-45

Storage

M.2	1 x Key M (2280)with PCIe x4 and SATA3 for SSD
SATA	1 x SATA3 (6Gb/s)

Front I/O

HDMI	N/A
DisplayPort	N/A
USB	2 x USB 3.2 Gen1 (Type-A) 2 x USB 3.2 Gen1 (Type-C)
Audio	2 (Mic-in, Line-out)

Rear I/O

HDMI	1 x HDMI 1.4b
DisplayPort	1 x DP 1.4a
VGA	1
Ethernet	1 x Realtek 1 Gigabit LAN
USB	4 x USB 2.0
Audio	N/A
COM	1 x COM (RS-232)
PS2	N/A

Watchdog Timer

Output Interval	From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec
-----------------	--

Power Requirements

Input PWR	1 x 19V/90W AC-DC power brick adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C ~ 50°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	10% ~ 90%
Storage Humidity	10% ~ 90%

Mechanical

Construction	Front Panel - Plastic / Base - Metal
Mounting	VESA mounting
Dimensions (W x H x D)	178 x 178 x 34mm
Weight	Net Weight:1.0Kg

Others

OS Support	Windows 10
Certifications	CE, FCC Class A
Packing List	- 1 x SATA Data with Power Cable - 1 x Screw Pack - 1 x Stand - 1 x VESA Mount - 2 x Antenna

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660