



## EAX-C226

Intel® LGA1150 Socket Supports 4th Generation Core™ Refresh i7/ i5/ i3, Pentium® and Celeron® Processors ATX Motherboard With Intel® C226 Chipset

- > Intel® LGA1150 Socket Supports 4<sup>th</sup> Generation Core™ Refresh i7/ i5/ i3, Pentium® and Celeron® Processors
- > Intel® C226 Chipset (Co-lay Q87 Chipset)
- > 4 x 240-pin DDR3 1333/1600 MHz DIMM supports up to 32 GB
- > 1 x VGA, 1 x DP, 1 x DVI, 5 x RS-232, 1 x RS-232/422/485, 1 x 8-bit GPIO, 6 x SATA III, 4 x USB 3.0, 9 x USB 2.0
- > Realtek ALC892 Supports 5.1-CH HD Audio Codec
- > 1 x Intel® I217LM PCIe Gigabit Ethernet PHY
- > 1 x Intel® I210AT PCIe Gigabit Ethernet
- > 1 x PCIe x 16, 4 x PCI (Support 5V), 1 x PCIe x 4, 1 x PCIe x 1

### Spec

System	
<b>Processor</b>	Intel® LGA1150 Socket Supports Xeon® Process
<b>System Chipset</b>	Intel® C226 Chipset (Co-lay Q87 Chipset)
<b>System Memory</b>	4 x 240-Pin DDR3 1333/1600 MHz DIMM up to 32 GB
<b>I/O Chip</b>	Nuvoton NCT6776F
<b>BIOS</b>	AMI uEFI BIOS, 64Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec./min. 1sec. or 1min. Step
<b>H/W Status Monitor</b>	Monitoring System Temperature and Voltage with Auto Throttling Control
Expansion	
<b>Expansion</b>	1 x PCIe x 16 4 x PCI (Support 5V) 1 x PCIe x 4 1 x PCIe x 1
I/O	
<b>USB</b>	9 x USB 2.0 4 x USB 3.0
<b>SATA</b>	6 x SATA III
<b>COM Port</b>	5 x RS-232 1 x RS-232/422/485
<b>DIO</b>	1 x 8-bit GPIO
<b>MIO</b>	1 x PS/2 Keyboard 1 x PS/2 Mouse
Display	
<b>Chipset</b>	Intel® 4th Generation CPU integrated VGA + DVI + DP
<b>Resolution</b>	VGA: Max. resolution 1920 x 1200 @ 60Hz DVI: Max. resolution 1920 x 1200 @ 60Hz DP: Max. resolution 3840 x 2160 @ 24Hz
Audio	
<b>Chipset</b>	1 x Realtek ALC892 supports 5.1-CH
<b>Audio Interface</b>	Mic-in, Line-in and Line-out
<b>Audio Amplifier</b>	TI TPA3005D2 Stereo Class-D 6W x 2 Audio Amplifier
Ethernet	
<b>Chipset</b>	1 x Intel® I210AT 1 x Intel® I217LM
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Mechanical & Environmental	
<b>Power Type</b>	AT/ATX
<b>Operating Temperature</b>	0°C ~ 60°C (32°F ~ 140°F)
<b>Storage Temperature</b>	-20°C ~ 75°C (-4°F ~ 167°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (L x W)</b>	12" x 9.6" (304.8 mm x 243.84 mm)
<b>Weight</b>	1.32lbs (0.6 kg)
Power Requirement	
<b>Power Requirement</b>	+12V/+5V/5Vsb/+3.3V/-12V

### Ordering

EAX-C226-A1R  
Intel® LGA1150 Socket Supports Intel® Xeon® Processors ATX Motherboard With Intel® C226 Chipset

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660