





**Specifications**

<b>SYSTEM</b>	<b>Processor</b>	6th Generation Intel® Core™ Processors, LGA 1151 Socket Core i7-6700TE (Skylake-S/R0-SR2LP) / 35W / LGA1151 Core i7-6700 (Skylake-S/R0-SR2BT) / 65W / LGA1151 Core i5-6500 (Skylake-S/R0-SR2BX) / 65W / LGA1151 Core i5-6500TE (Skylake-S/R0-SR2LR) / 35W / LGA1151 Core i3-6100TE (Skylake-S/R0-SR2LS) / 35W / LGA1151 Core i3-6100 (Skylake-S/S0-SR2HG) / 51W / LGA1151 Pentium-G4400 (Skylake-S/R0-SR2DC) / 54W / LGA1151 Pentium-G4400TE (Skylake-S/R0-SR2LT) / 35W / LGA1151 Celeron G3900TE (Skylake-S/R0-SR2LU) / 35W / LGA1151
	<b>Chipset</b>	Intel® Q170 Chipset
	<b>Memory</b>	Two 260-pin SODIMM up to 32GB Dual Channel DDR4 1866/2133MHz
	<b>BIOS</b>	Insyde SPI 128Mbit
	<b>GRAPHICS</b>	<b>Controller</b> Intel® HD Gen 9 Graphics
	<b>Feature</b> OpenGL 5.0, DirectX 12, OpenCL 2.1 HW Decode: AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 HW Encode: MPEG2, AVC/H264, JPEG, HEVC/H265, VP8, VP9	
	<b>Display</b> 1 x eDP 1 x LVDS 1 x DP++ eDP: resolution up to 4096x2304@ 60Hz LVDS: resolution up to 1920x1080 @ 60Hz DP++: resolution up to 4096x2304@ 60Hz	
	<b>Triple Displays</b> DP++ + eDP + LVDS	
<b>EXPANSION</b>	<b>Interface</b> 1 x Full-size Mini PCIe (USB/PCIe/SATA, SATA by default) 1 x Half-size Mini PCIe (USB/PCIe/SATA, Mini PCIe by default) 1 x PCIe x16	
<b>AUDIO</b>	<b>Audio Codec</b> Realtek ALC888S-VD2-GR	
<b>ETHERNET</b>	<b>Controller</b> 1 x Intel® T219LM PCIe with iAMT11.0 (10/100/1000Mbps) (only Core i7/i5 supports iAMT) 1 x Intel® I211AT PCIe (10/100/1000Mbps)	
<b>REAR I/O</b>	<b>Ethernet</b>	2 x GbE (RJ-45)
	<b>USB</b>	4 x USB 3.0
	<b>Display</b>	1 x DP++
<b>INTERNAL I/O</b>	<b>USB</b>	4 x USB 2.0 (2.00mm pitch)
	<b>Display</b>	1 x LVDS LCD Panel Connector 1 x eDP
	<b>Audio</b>	1 x Audio (Line-out/Mic-in) 1 x Speaker (3W amplifier)
	<b>SATA</b>	2 x SATA 3.0 (up to 6Gb/s)
	<b>SMBus</b>	1 x SMBus (2.00mm pitch)
	<b>Serial</b>	2 x RS-232 (2.00mm pitch)
	<b>Others</b>	1 x Intrusion (2.54mm pitch) 1 x CPU FAN (2.54mm pitch) 2 x SYS FAN (2.54mm pitch)
	<b>WATCHDOG TIMER</b>	<b>Output &amp; Interval</b> System Reset, Programmable via Software from 1 to 255 Seconds
<b>SECURITY</b>	<b>TPM</b> TPM2.0 (opt.)	
<b>POWER</b>	<b>Type</b>	15~36V DC in
	<b>RTC Battery</b>	CR2032 Coin Cell
<b>OS SUPPORT</b>	Windows 7 Windows 10	Windows 8.1
<b>ENVIRONMENT</b>	<b>Temperature</b>	Operating: 0 to 60°C Storage: -40 to 85°C
	<b>Humidity</b>	Operating: 5 to 90% RH Storage: 5 to 90% RH
	<b>MTBF</b>	457, 253 hrs @ 25°C; 270, 131 hrs @ 45°C; 171, 981 hrs @ 60°C Calculation model: Telcordia Issue 2 Environment: GB, GC – Ground Benign, Controlled
<b>MECHANICAL</b>	<b>Dimensions</b>	Mini-ITX Form Factor 170mm (6.7") x 170mm (6.7")
	<b>Height</b>	PCB: 1.6mm Top Side: 16.34mm, Bottom Side: 4.2mm

**Ordering Information**

Model Name	P/N	Memory	GbE	DP++	LVDS	eDP	RS-232	SATA 3.0	USB 3.0	USB 2.0	Power	Thermal	Temp.
<b>SD106-Q170</b>	770-SD1061-000G	2 SODIMM	2	1	1	1	2	2	4	4	15~36V DC-in	Cooler	0 to 60°C

**Packing List**

• 1 SD106-Q170 motherboard	
• 1 COM port cable (Length: 250mm, 1 x COM ports)	A81-015011-001G
• 1 Serial ATA data with power cable (Length: 500mm)	332-553001-005G

**Optional Items**

• USB port cable (Length: 200mm)	A81-001032-016G
• COM port cable (Length: 250mm, 1 x COM ports)	A81-015011-001G
• Serial ATA data cable (Length: 500mm)	332-553001-005G
• Thermal solution (For 35W, Height: 37.3mm)	A71-103004-000G
• Thermal solution (For 65W, Height: 72.8mm)	552-200049-000G
• I/O shield	A49-SD1060-000G
• I/O shield (Thin Type)	A49-SD1060-110G
• I/O shield (Thin Type Non Audio)	A49-SD1060-100G

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660