

ARS-7235-5E-AC Series

Industrial 5-Port Gigabit Ethernet with Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router



Features


- ▶ Industrial 2x2 MIMO
- ▶ Qualcomm IPQ4029 SoC
- ▶ Supports IEEE 802.11a/b/g/n/ac
- ▶ Supports 5*10/100/1000 Base-TX WAN/LAN Ports
- ▶ Tx Power 25dB for 2.4GHz
- ▶ Tx Power 24dB for 5GHz
- ▶ WPA, WPA2, WPA3, WEP, TKIP, AES
- ▶ Power Input: 9~48VDC in 6-Pin Terminal Block
- ▶ Reverse Polarity Protection
- ▶ IP30 Protection
- ▶ DIN-Rail and Wall Mountable
- ▶ Operating Temperature Range: STD: -10°C to 60°C; EOT: -35°C to 70°C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' ARS-7235-5E-AC Series is an industrial dual-radio IEEE 802.11a/b/g/n/ac wireless LAN access point with added router capabilities and 5*10/100/1000Tx Gigabit Ethernet ports. Embedded with the Qualcomm IPQ4029 SoC chipset, it boasts network robustness, stability, and wide network coverage with a very low voltage input of 9V. Based on IEEE 802.11 a/b/g/n/ac, the access point supports high-speed data transmission of up to 867Mbps.

The ARS-7235-5E-AC Series is capable of operating in different modes, which makes it suitable for a wide variety of wireless applications including long-distance deployments. The unit also allows the user to position the wireless antennas in a better signal-broadcasting location for improved wireless coverage and signal strength or simply in a more convenient location.

DIMENSIONS



SPECIFICATIONS

Technology		Power Requirement	
Standards	IEEE 802.11a/b/g/n/ac Wireless LAN	Input Voltage	9~48VDC Redundant Input
	IEEE 802.3 10Base-T Ethernet	Power Connection	1 removable 6-contact terminal block
	IEEE 802.3u 100Base-TX Fast Ethernet	Reverse Polarity Protection	Present
	IEEE 802.3ab 1000Base-T Gigabit Ethernet	Overload Current Protection	Present
Protocol	IP, TCP, UDP, ARP, BOOTP, ICMP, HTTP, HTTPS, DNS Proxy, NTP, Dynamic DNS, SMTP, SNMP	System Power Consumption	3.5 Watts
	WLAN Operation Mode	AP/Client/Bridge/Repeater/Router	
Encryption Security		WPA, WPA2, WPA3, WEP, TKIP, AES, RADIUS, 802.1x/EAP	
Interface		Environmental Limits	
Ethernet Port	5*10/100/1000Tx	Operating Temperature	STD: -10°C to 60°C EOT: -35°C to 70°C
WLAN	Dual Band 2.4GHz/5GHz concurrent	Storage Temperature	-40°C to 80°C
Antenna	2*External SMA Antennas:	Ambient Relative Humidity	5 to 90%, (non-condensing)
	3dBi for 2.4GHz, 5dBi for 5GHz (MIMO support, Dual 2Tx/2Rx)		
LED Indicators	Power, Fault, Wi-Fi Signal, Diagnostic, Activity	Regulatory Approvals	
Frequency Range		EMI	FCC Part 15 Subpart B CE EN55032
IEEE 802.11a/b/g/n/ac (2.4GHz)	2.402G-2.482GHz, 25dBm	EMS	CE EN55024 IEC61000-4-2,3,4,5,6,8,11
IEEE 802.11a/b/g/n/ac (5GHz)	4.92G-5.92GHz, 24dBm	Free Fall	IEC60068-2-32
Mechanical Characteristics		Shock	IEC60068-2-27
Housing	Metal, IP30 rated	Vibration	IEC60068-2-6
Dimensions	46 x 155 x 115 mm (W x H x D)	Green	RoHS Compliant
Weight	Unit: 0.60 lb.	Certifications	FCC, CE
	Shipping: 1.0 lb.	Warranty	5 Years
Mounting	DIN-Rail mounting, Wall mounting		

ORDERING INFO

ARS-7235-5E-AC	Industrial 5-Port Gigabit Ethernet with Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router
ARS-7235-5E-AC-T	Industrial 5-Port Gigabit Ethernet with Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router; EOT: -35°C to 70°C

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660