

Optolinx IMP-100A

Industrial 10/100BaseTX to 100BaseFX Industrial PoE Media Converter




Features

- ▶ Embedded 1 Port PoE Injector Function
- ▶ RJ-45 Port Support Auto MDI/MDI-X Function
- ▶ Store-and-Forward Switching Architecture
- ▶ Built-in Link Loss Forwarding (LLF) & Link-Fault-Pass-Through (LFP)
- ▶ Wide Operating Temperature Model Available (-40° C to 80° C)
- ▶ DC 48V Redundant Power
- ▶ Provides EFT Protection 3000 VDC For Power Line
- ▶ Supports 6000 VDC Ethernet ESD Protection
- ▶ DIN-Rail or Wall Mountable
- ▶ IP30 Protection
- ▶ 5-Year Warranty



▶ Specifications



► Specifications

Standard

IEEE 802.3 10BaseT Ethernet
 IEEE 802.3u 100BaseTX/100BaseFX
 IEEE 802.3x Flow Control and Back-Pressure
 IEEE 802.3af Power over Ethernet

Switch Architecture

Store and forward

Transfer Rate

14,880pps for Ethernet Port
 148,800pps for Fast Ethernet Port

PoE Pin Assignment

RJ-45 Port Supports IEEE 802.3af End-Point, Alternative A Mode
 Positive (VCC+): RJ-45 Pin 1, 2
 Negative (VCC-): RJ-45 Pin 3, 6
 Data (1, 2, 3, 6)

Connector

100M Fiber: 1 x SC (Multi-Mode) or SC (Single-Mode, 30Km)
 10/100TX: 1 x RJ-45 w/ Auto MDI/MDI-X & Auto-Negotiation Function, Supports PoE Injector Function

Network Cable

10BaseT: 2-Pair UTP/STP Cat. 3, 4, 5 Cable
 EIA/TIA-568 100-ohm (100m)
 100BaseTX: 2-Pair UTP/STP Cat. 5 Cable
 EIA/TIA-568 100-ohm (100m)

Fiber Parameters

Fiber Core: Multi-Mode (62.5/125um ~ 50/125um)
 Single-Mode (9/125um ~ 10/125um)
 Wavelength: 1310nm
 Fiber Distance: Multi-Mode Fiber 2Km
 Single-Mode Fiber 30Km

Link Loss Forward

TX → Fiber: If TX port link down, will force Fiber port to link down
 Fiber → TX: If Fiber port link down, will force TX port to link down

DIP Switch

DIP 1: ON = Enables Port/Power Alarm
 OFF = Disables Port/Power Alarm
 DIP 2: ON = Enables Link Loss Forward & Link-Fault-Pass-Through
 OFF = Disables Link Loss Forward & Link-Fault-Pass-Through
 DIP 3: ON = 100BaseFX Half-Mode
 OFF = 100BaseFX Full-Mode
 DIP 4: ON = Media Mode (100TX to 100FX)
 OFF = Switching Mode

LED

Unit: Power, Power 1, Power 2 (Green), Fault (Red)
 TX: Link/Act (Green), 100M (Yellow), Feeding Power (Green)
 Fiber: Link/Act (Green), Full Duplex/Collision (Yellow)

Power

DC 48V Redundant power

Power Consumption

3.3 Watts (without PoE), 16.4 Watts (Full Load with PoE)

Overload Current Protection

Present

Mechanical

Casing: IP30 Metal Case
 Dimension (W x H x D): 30 x 140 x 95 mm (1.18 x 5.51 x 3.74 in.)
 Installation: DIN-Rail/Wall Mountable

Operation Temperature

Standard: -10° C to 70° C (14° F to 158° F)
 Wide Operating Temperature: -40° C to 80° C (-40° F to 176° F)

Operation Humidity

5% to 95% (Non-condensing)

Storage Temperature

-40° C to 85° C

EMI

FCC Class A
 CE EN6100-4-2/EN6100-4-3/EN6100-4-4/EN6100-4-5/EN6100-4-6/
 EN6100-4-8/EN6100-4-11/EN6100-6-2/EN6100-6-4

Safety

UL, cUL, CE EN60950-1

Stability Testing

Shock: IEC60068-2-27
 Free Fall: IEC60068-2-32
 Vibration: IEC60068-2-6

Warranty

5-Year Warranty

► Ordering Information

IMP-100A-M

Industrial PoE Media Converter, Multi-Mode Fiber, SC, 2 Km

IMP-100A-S3

Industrial PoE Media Converter, Single-Mode Fiber, SC, 30 Km

IMP-100A-M-T

Industrial PoE Media Converter, Multi-Mode Fiber, SC, 2 Km, Wide Operating Temperature

IMP-100A-S3-T

Industrial PoE Media Converter, Single-Mode Fiber, SC, 30 Km, Wide Operating Temperature

Optional Accessories

CBF-SC01ST-MD

SC to ST Multi-Mode, Duplex Fiber Cable (1 Meter)

CBF-SC01SC-MD

SC to SC Multi-Mode, Duplex Fiber Cable (1 Meter)

CBF-SC01SC-SS

SC to SC Single-Mode, Simplex Fiber Cable (1 Meter)

AD-SCM-STF-M

SC (Male) to ST (Female) Duplex Adapter (Multi-Mode)

AD-SCM-STF-S

SC (Male) to ST (Female) Duplex Adapter (Single-Mode)

Antaira Technologies

Toll-Free: (877) 229-3665
 Phone: (714) 671-9000
 FAX: (714) 671-9944

e-Mail: info@antaira.com
 Website: <http://www.antaira.com>

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660