

Vehicle Computer  
**COMPACT-VSL Series**

Embedded In-Vehicle Computer with Intel® Atom™ E39xx processor



## IPC/VSL81

This fan less Vehicle VSL COMPACT81 generation is based on the Intel® Atom™ E3900 (formerly Apollo Lake) processor technology and offers a wide range of interface options. The robust and uncompromising industrial design allows the implementation in the most demanding IoT applications and guarantees long term availability.

- Multi-core 64-bit Intel® Atom™ processor
- 24/7 continuous operation
- M12 connector for Power and LAN
- Shock and vibration resistant
- Full -40...+85°C on component level



### Product Highlights

Power Ignition controller  
Trusted Platform Module - TPM2.0  
Inertial Measurement Unit (IMU)  
GPS with dead reckoning  
Fanless, No moving parts  
Maintenance free / Long term availability

### Product Features

Intel® Atom™ E3900 Series  
up to 2.0GHz, up to 4 Cores  
RAM soldered on board up to 8GB  
Socket for CFast  
Ethernet, USB, CAN  
M12 connectors  
Stainless steel housing  
Protection class IP40  
LTE, GNSS, WiFi & Bluetooth options

### Markets / Applications

Automotive  
Transportation  
Automated Guided Vehicles (AGV)  
Special purpose vehicles  
Agriculture  
Industrial trucks

Order Code IPC/VSL81120-A153E<sup>1</sup>

Vehicle Computer

Processor / Performance		
Intel® Atom™ x7-E3950 2.00GHz (Burst)   1.6GHz Clock - Quad Core		•
Intel® Atom™ x5-E3940 1.80GHz (Burst)   1.6GHz Clock - Quad Core		optional
Memory		
L2 cache		2MB
RAM DDR3L 1866MT/s soldered on board		4GB
8GB DDR3 RAM <sup>1</sup>		optional
Features		
Inertial measurement unit (IMU) STMicroelectronics ISM330DHCXTR		•
Real time clock (RTC) with battery backup Renata CR2477N (950 mAh)		•
Hardware Watchdog & Temperature supervisor		•
Intelligent power management (Ignition controller)		•
TPM 2.0 according to ISO/IEC11889 Infineon SLB9665		•
Communication Interfaces		
DisplayPort 1.4 (up to 7680 x 4320 @ 60Hz)		1
USB version 3.1	(Type A)	1
USB version 2.0	(Type A)	1
Ethernet 10/100/1000 BASE-T (Intel I210-IT)	(M12 female x-coded)	2
PoE+ IEEE802.3at 10/100/1000Mbit <small>requires taller housing: w228 x h85 x d127 mm</small>	(M12 female x-coded)	optional
CAN 2.0A/2.0B & CAN FD (PEAK FPGA chip, SJA1000 compatible), isolated, The CAN signals give no network feedback and are attached via non-volatile I/O port on the I2C bus	(DSUB9)	2
CFast socket with retention frame <sup>2</sup>		1
M.2 Key B socket <sup>2</sup> , used for radio options depending on config	(3042)	1
M.2 Key E socket <sup>2</sup> , used for radio options depending on config	(2230)	1
Mini PCIe socket <sup>2</sup>	(full size)	1
MicroSD Card socket <sup>2</sup>		1
Buzzer		1
I2C bus <sup>2</sup>		1
Serial RS232 <sup>2</sup>		2
Serial RS422/485, isolated	(DSUB9)	optional
HD Audio, Line in / out <sup>2</sup>		optional
Digital I/O, 24VDC (latency <1ms)	(4 inputs, 4 outputs)	optional
Analog input, 16bit resolution, voltage input: -10 ... +10V / 0 ... 30V <small>Accuracy: +/- 0.1%</small>		optional
Wireless Connectivity		
4G cellular module (3G/2G fallback) Sierra Wireless EM7455 - M2M only! with dual nano SIM support	(2x SMA)	optional
GNSS positioning module with dead reckoning u-blox NEO-M9 Module	(1x SMA)	optional
Wireless LAN IEEE 802.11ac/a/b/g/n/ dual-band 2x2 MIMO <small>SparkLAN WNF6-263ACNI(BT)</small>	(2x RP-SMA)	optional
Technical Data		
Exterior dimensions [mm]		w228 x h55 x d127
Net weight [gram]		~ 1750
Non-isolated input voltage, reverse polarity protected	(M12 4P male a-coded)	8.4 ... 45VDC
Current consumption typ. in mA @ 24V without Add-Ins, idle		~ 500
Power consumption typ. in Watt @ 24V without Add-Ins, idle		~ 12
Environmental Conditions		
Operating temperature <sup>3</sup>		-40°C ... +70°C
Storage temperature		-40°C ... +85°C
Ingress Protection standard EN60529 (ISO 20653)		IP40
Road vehicles (UNECE-R10 'E-mark')		on request
Conformal coating <sup>4</sup>		on request
Shock		EN60068-2-27
Vibration		EN60068-2-64
EMC Conformity		EN55032 / EN55035
Safety (designed to meet)		EN62368-1
Radio and Telecommunication (designed to meet)		RED
MTBF @ 25°C <small>according to Telcordia SR-332, Environment GB, excluding battery and optional extensions</small>		~ 480 000h

<sup>1</sup> Please contact factory for minimum order quantities

<sup>2</sup> Internal connector

<sup>3</sup> Depending on installation situation and interface connection. Please see user documentation.

<sup>4</sup> On all possible components (excl. Connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2021 Syslogic Datentechnik AG  
All rights reserved

Syslogic Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 1.0 | October 2021

For further information and support:  
info@syslogic.com  
support@syslogic.com  
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)  
+49 7741 967 14 20 Germany and Austria



## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660