



EMX-H310C

Intel® 8/9th Gen. Core™
i7/i5/i3/Pentium®/Celeron®/Processor Mini ITX
Motherboard With Intel® H310 Chipset

- > Intel® 8/9th Gen. Core™/Pentium®/Celeron®/Processor (Max. TDP at 65W)
- > Intel® H310 Chipset
- > 2 x 260-pin DDR4 2400/2666MHz SO-DIMM socket, supports up to 64GB
- > 2 x Realtek RTL8111H Gigabit Ethernet
- > VGA, HDMI, Dual-CH LVDS co-lay eDP(By BOM option, default no LVDS & no eDP)
- > 2 x SATA III
- > 1 x Mini PCI-e supports USB 2.0 with SIM card slot
- > 1 x mSATA slot
- > 1 x M.2 (2230) E-Key, support WiFi module
- > 1 x PCI-e x1
- > 4 x USB3.1 Gen1, 6 x USB 2.0, PS2 KB/MS + 2 x USB 2.0 at I/O, 2 x USB2.0 by pin header
- > 5 x RS232, 1 x RS232/422/485
- > ATX Power

Spec

-System Information-	
Processor	Intel® LGA1151 Socket Supports 8/9th Generation Core™/Pentium®/Celeron® Processors (MAX. TDP 65W)
Platform Controller Hub	Intel® H310 Chipset
System Memory	2 x 260-pin DDR4 2400/2666MHz SO-DIMM supports up to 64GB
I/O Chipset	ITE8786E
BIOS Information	AMI uEFI BIOS, 128Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 5~255 seconds/5~255 minutes
H/W Status Monitor	CPU temperature monitoring, Voltages monitoring, CPU fan speed control
Board	Mini ITX Board
Expansion	
Expansion	1 x PCI-e x1 1 x Full size Mini PCI-e supports USB 2.0 with SIM card slot 1 x M.2 (2230) E-Key, supports WiFi module (1 x PCI-e x1 and USB 2.0 Signal)
Storage	
Storage	1 x mSATA slot (w USB 2.0 Signal only)
I/O	
USB Port	6 x USB 3.1 Gen1, 2 x USB 2.0, PS2 KB/MS + 2 x USB2.0
COM Port	5 x RS232 1 x RS232/422/485
SATA	2 x SATA III
DIO	1 x 8-bit GPIO
Display	
Graphic Chipset	Intel® 8/9th Generation CPU integrated
Spec. & Resolution	VGA: 2048 x 1536 @ 60 Hz HDMI 1.4b: 4096x2160@30Hz LVDS : 1024x768@60Hz default, colay eDP 2 lanes 1920 x 1080@60Hz by BOM optional *default no LVDS, no eDP
Multiple Display	Dual Display
LVDS	Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS)- By BOM option
Audio	
Audio Codec	Realtek ALC897 Audio Codec colay ALC662
Audio Amplifier	3W Amplifier
Ethernet	
LAN Chipset	1 x Realtek RTL8111H Gigabit Ethernet
LAN Port	2 x RJ-45
Mechanical & Environmental	
Operating Temperature	0~60°C (32~140°F)
Storage Temperature	-40 ~ 75°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.4 kg
Power Requirement	+12V/+5V/5VSB/+3.3V/-12V
ACPI	Single power ATX Support S0, S3, S4, S5
Power Mode	AT/ATX
Dimension (L x W)	6.7" x 6.7" (170mm x 170mm)
Ordering Information	



Ordering Information

EMX-H310C-A1R
Intel® 8/9th Gen. Core™/Pentium®/Celeron® Processor Mini ITX Motherboard With Intel® H310 Chipset (no LVDS, no eDP)

www.avalu.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660