

M133WK, 13.3-inch Ultra Rugged Tablet

An Ultra Rugged Tablet that Survives Any Environment and Gets Real Work Done

M133WK boasts a robust set of features designed to withstand industrial use while providing high tech solutions that increase productivity, improve safety, and reduce operational costs. With processing power coming from 8th Gen. Intel[®] Core[™] i5-8265U Whiskey Lake processor, the M133WK features a sunlight readable 1920 x 1080 PCAP touchscreen with wide viewing angle and direct optical bonding technology. The built-in kickstand allows the device to stand firmly on nearly any surfaces to become an ultra-rugged, yet compact mobile workstation with reliable performance.



Highlights

- Intel[®] Core[™] i5-8265U Whiskey Lake processor
- 13.3" 1920 x 1080 IPS wide viewing angle LED Panel
- Magnesium alloy housing with all-around elastomeric rubber
- Built-in kickstand usable as carrying handle(indefinitely adjustable)
- Cold swap Battery Pack
- IP65 waterproof and dustproof
- Optical bonding technology
- TPM 2.0

 The device images are for reference only. Actual device may vary





M133WK, 13.3-inch Ultra Rugged Tablet

An Ultra Rugged Tablet that Survives Any Environment and Gets Real Work Done

Display Specification

Size Resolution Panel Brightness Touch

Contrast Ratio

Viewina Anale

Technology

13.3-inch 1920 x 1080 500 nits with Optical Bonding Multi-touch Projected Capactive with Glove/Rain/Stylus Modes Support 1000.189/89/89/89

- Anti-glare technology (Default)
- Intel HD Graphics (built-in CPU) video controller

System Specification

Processor System Memory Storage 1 Storage 2 Operating System Intel[®] Core[™] i5-8265U, 1.60 GHz (up to 3.90 GHz), 4GB SODIMM DDR4-2400 (up to 16GB)¹ 1 x 128GB M.2 SSD (up to 512GB) Optional M.2 SSD (up to 512GB) Windows 10 IoT Enterprise

Wireless Communication

WLAN WWAN Bluetooth GNSS

802.11 a/b/g/n/ac 4G LTE (Optional) Bluetooth 5.0 GPS/GLONASS (Optional)

Interface

Docking Connector 1 x Docking connector I AN 1 x RJ45-10/100/1000 Mbps LAN 2 x USB 3.0 Type A USB 2 x USB 3.0 Type A USB Type-C 1 x USB 3.1 Type-C (Gen1) Power Input 1 x Power Jack (DC Input) SD 1 x SDXC Slot Access to SSD + 2 x WiFi Service Window

Keyboard and Input

Touch Button	 10-point multi-touch, support Hand / Gloves, Rain Mode, and Active Pen On-screen QWERTY keyboard 7 membrane keys: 1 x power, 1 x menu, 3 x function key (Programmable function key)
Status Indicators	
LED Indicators	Power, Battery, SSD, RF
Audio	
Microphone Speaker	$1 \ x$ built-in Digital Mic with Noise Cancellation $2 \ x \ 1$ watt speaker
Certifications	
Certifications	CF. FCC

Security Function

Security

 Trusted Platform Module (TPM) V2.0 2 · Kensington lock slot

Mechanical and Environment

Dimension (W x L x H) Housing	338.2 x 240 x 30 mm (13.3 x 9.4 x 1.18 inches) ³ Rear Magnesium Alloy Die-Casting Design
Cooling System	Fanless thermal design
Weight	2.2kg (w/ kickstand)
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	30% to 80% RH, non-condensing
IP Proof	IP65
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
Drop	MIL-STD-810G Method 516.6, 4 ft to concrete

Power Management

Power Input 19V DC Battery 14.8V, typ. 5900 mAh Li-Polymer Battery (4S1P) Battery Operating Time More than 10 hours (BAPCo TabletMark v3)⁴ Adapter 100-240V, 50-60Hz / 19V DC

Accessories

Standard Accessories

Adapter and Power Cord Standard Battery Stylus Stand with Integrated Handle

Optional Accessories

VESA Mounting Kit VESA Mounting Kit 2 RAM Mounting Kit Vehicle Charger

98KT00A00000 98KT00A00019 98K000A0007Z 9226065W19V0


922D065W19V1


98K000A000DU

9AN0000000V

98K000A000DV

Drawing ⁶





Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example) Do not expose bare skin to this product when handling this unit in extreme

1. Total usable memory will be less depending upon actual system configuration

2. TPM 2.0 available upon request. 3. Length measurements do not include protrusions. Weight varies with options

4. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached

5. This is a simplified drawing and some components are not marked in detail.



Revised Date: 24-Apr-2020 V1.1



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660