

iEP-9012E

Expendable Edge AIoT Platform

Preliminary



**KEY FEATURES**

- Intel® 12<sup>th</sup> Gen Core™ Processors with H610 Chipset
- 2 x 260-pin DDR4 SO-DIMM up to 64GB (32GB per DIMM)
- 1 x M.2 Key B, 1 x M.2 Key E, 2 x Mini PCIe
- 2 x USB 3.2 Gen2x1, 2 x USB 3.2 Gen1x1, 2 x USB 2.0, 6 x COM, 4 x SATA3, 8 x DI, 8 x DO
- 4 x Intel 2.5G LAN (2 support PoE)
- 1 x Displayport, 1 x HDMI 2.0b, 1 x VGA

**SPECIFICATIONS**

**Processor System**

CPU	Intel® 12 <sup>th</sup> Gen Core™, Pentium or Celeron Processors
Chipset	Intel® H610
Socket	LGA 1700

**Memory**

Technology	Dual Channel DDR4 2933MHz
Capacity	64 GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

**Graphics**

Controller	Intel® UHD Graphics
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
VGA	Max resolution up to 1920x1200@60Hz

**Expansion Slot**

Mini-PCIe	2 x Full/Half size with PCIe Gen3 x1 and USB 2.0
RF& Antenna	8 x SMA connector hole reserved
M.2	1 x M.2 (Key E, 2230) with CNVI/PCIe Gen3 x1 and USB2.0 for Wi-Fi/BT module 1 x M.2 (Key B, 2280/3042/3052) with PCIe Gen3 x1 / USB2.0 for 4G / 5G
SIM Socket	2 x Nano SIM Card slot (1 connected to Mini PCIe, 1 connected to M.2 Key B)

**Audio**

Interface	Realtek ALC897, High Definition Audio.
-----------	--

**Ethernet**

Controller/ Speed	4 x Intel 2.5G LAN (2 support PoE, each port supports IEEE 802.3AF PoE, PoE output max.15.4W/port)
Connector	4 x RJ45

**Storage**

SATA	4 x SATA3 (6Gb/s) 4 x 2.5" HDD/SSD Tray
CFast (Option)	1 x Type II socket (Shared with SATA3)

**Rear I/O**

DisplayPort	1
HDMI	1
VGA	1
Ethernet	4 x 2.5G LAN
USB	2 x USB 3.2 Gen2x1, 2 x USB 3.2 Gen1x1, 2 x USB 2.0, 1 x USB2.0 internal connector w/ lock function
Audio	1 x Mic-in, 1 x Line-out
COM	4 x RS232/422/485 2 x RS232
DIO	8DI/8DOs

**Watchdog Timer**

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

**Power Requirements**

Input PWR	9V~36V VDC with Ignition control and remote power on/off switch. 80V Surge Protection, OVP, UVP, OCP and reverse protection Ignition Power Input w/ 13-mode condition
-----------	---

**Environment**

Operating Temperature	35W CPU: -40°C~70°C ( -40°F~158°F) 46W~65W CPU: -40°C~50°C ( -40°F~122°F) (w/ air flow 0.5~0.8 m/s)
Storage Temperature	-40°C~85°C ( -40°F~185°F)
Humidity	~95% @ 40°C (non-condensing)
Shock	Operating: 50 G, half sine 11ms duration with SSD
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes with SSD
ESD	Contact +/-4kV, Air +/-8kV
EMC	EN61000-6-4/-2, CE & FCC Class A
Safety	LVD

**Mechanical**

Construction	Aluminum heatsink + Metal chassis
Mounting	Desk Mount
Dimensions	202mm (W) x 244mm (D) x 108.7mm (H) (7.95" x 9.61" x 4.28")
Net Weight	6.5kg

**Others**

OS Support	Windows 10 & Linux
TPM	TPM 2.0
Real-Time Enablement	TSN, TCC support under YOCTO

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660