

# EMS-EHL-USB

Intel® Elkhart Lake Atom®/Celeron®  
Processor Fanless Rugged Embedded System,  
w\_USB IET Module



## Product Features

- Intel® Celeron®/Atom™ J6413/x6425E SoC BGA Processor
- Rich I/O, 8-USB3.2, 3-USB2.0, 1-DP, 1-HDMI, 2-COM, 2-LAN, 1-8bit GPIO
- Fanless operation temperature from -40°C ~ 70°C (WT) / 0°C ~ 65°C (ST)
- Wide range DC power input from +9~36V
- Support IET modules
- 1 x 260-pin SODIMM socket Max. up to 32GB DDR4 3200MT/s
- Support 5G (Sub-6G) module, HDMI 2.0b (4K @ 60Hz), LAN 2.5G Base-Tx GbE
- CE, FCC Class B, LVD 62368-1, IP50
- Support HW TPM 2.0

## Specification

### System Information

<b>Processor</b>	Intel® Celeron® Processor J6413 (1.5M Cache, up to 3.00Ghz), ST, Tj=105°C Intel® Atom® Processor x6425E(1.5M Cache, up to 3.00Ghz), WT, Tj=-40°C ~105°C
<b>System Memory</b>	1 x 260-pin SODIMM socket Max. Up to 32GB DDR4 3200 MT/s
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec.
<b>H/W Status Monitor</b>	CPU & system temperature monitoring and Voltages monitoring
<b>TPM</b>	TPM 2.0
<b>SBC</b>	EBM-EHLS

### Expansion

<b>M.2</b>	1 x M.2 Key-B 2242/3042/3052 support SATA3/ PCIe III/ USB3.2 Gen.1 and SIM slot1 (internal), default support 3.3V, jumper setting to adjust 3.3V/ 3.8V 1 x M.2 Key-E 2230 for Wi-Fi & BT Module (USB2.0/ PCIe III)
------------	---

**Storage**

<b>M.2</b>	1 x M.2 Key-B 2242/2280, support SATA 1 x M.2 Key-B 2242, support SATA (share with expansion slot)
------------	---

**Rear I/O**

<b>USB</b>	3 x USB 2.0 6 x USB 3.1 Gen.1 (5Gbp/s), via USB Hub 2 x USB 3.1 Gen.2 (10Gbp/s)
------------	---

<b>LAN Port</b>	2 x RJ45
-----------------	----------

<b>Audio</b>	1 x Mic-In, 1 x Line-Out
--------------	--------------------------

<b>DP</b>	1 x DP 1.4
-----------	------------

<b>HDMI</b>	1 x HDMI 2.0b
-------------	---------------

<b>Antenna</b>	2 x Antenna with dust cover
----------------	-----------------------------

**Right I/O**

<b>Antenna</b>	2 x Antenna with dust cover
----------------	-----------------------------

**Left I/O**

<b>Antenna</b>	2 x Antenna with dust cover
----------------	-----------------------------

**Display**

<b>Graphic Chipset</b>	Intel® UHD Graphics for 10th Gen Intel® Processors
------------------------	--

<b>Resolution</b>	DP++ 1.4: 4096x2304 @ 60Hz HDMI 2.0b : Max. resolution 4096x2304 @ 60Hz
-------------------	--

**Audio**

<b>Audio Codec</b>	Realtek ALC888S (co-lay with ALC897) HD codec
--------------------	---

**Ethernet**

<b>LAN Chipset</b>	2 x Intel I226-IT
--------------------	-------------------

<b>Specification</b>	2 x 10/100/1000/2.5G Base-Tx GbE compatible
----------------------	---

**Power Requirement**

<b>ACPI</b>	Single power ATX Support S0,S3, S4, S5 ACPI 5.0 Compliant
-------------	--

<b>Power Mode</b>	AT/ATX (ATX is default setting)
-------------------	---------------------------------

**Software Support**

**OS** Win 10 64bit / Win 11 64 bit/ Linux

**Certification**

**Certification Information** CE, FCC Class B, LVD 62368-1

**Mechanical & Environmental**

**Operating Temp.** -40°C ~ 70°C (w/SSD) ambient w/ 0.5 air flow, WT sku, x6425E  
 -40°C ~ 60°C (w/SSD) ambient w/ 0.2 air flow, WT sku, x6425E  
 0°C ~ 65°C (w/SSD) ambient w/ 0.5 air flow, ST sku, J6413  
 0°C ~ 55°C (w/SSD) ambient w/ 0.2 air flow, ST sku, J6413

**Storage Temp.** -30°C ~ 70°C (-22°F ~ 158°F)

**Operating Humidity** 40°C @ 95% Relative Humidity, Non-condensing

**Dimension (W x L x H)** 240mm x 150mm x 64 mm (w/ IET module)

**Weight** 1.9 kg (System)  
 2.7 kg (w\_Package)

**Vibration Test** With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis

**Shock Test** With SSD : 55Grms, IEC 60068-2-27, Half Sine, 11ms

**IP Rating** IP 50

**Mounting Kit** Wall mount kit (standard)  
 DIN RAIL (optional)

**Ordering Information**

**Ordering Information** Intel® Elkhart Lake Atom®/Celeron® Processor Fanless Rugged Embedded System, w\_USB IET Module

EMS-EHL-X64-A1-8R (x6425E)  
 EMS-EHL-J64-A1-8R (J6413)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660