

**Hisense**

HOA Series



# HOA SERIES

## P6 OUTDOOR LED DISPLAY

HOA series outdoor LED solutions are perfect for any billboard or large scale LED wall project. These ultra reliable, high brightness, low power consumption modules also feature an IP65 rating and auto brightness adjustment for the ultimate impact in any climate or weather conditions. Hisense LED modules include cable-less internal construction and rear access for ease of maintenance.

### Highlights



#### Ultra high brightness

With 5,500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



#### 120° High viewing angle

The extra wide 120° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



#### High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



#### Ultra high contrast ratio

LED display could reveal more details, including layers and colors, than traditional displays do.



#### Long Lifespan

The HOA series boasts an incredibly long lifespan of upto 100000hrs.



#### Clear and consistent picture

LED display providing a clear and consistent picture throughout it's lifespan.




#### Effortless set-up and maintenance

LED display could reveal more details, including layers and colors, than traditional displays do.



#### Durable in Outdoor Environments

The fully waterproof module ensures the TES LED display series with ongoing performance when exposed to high temperature, high-humidity and a variety of natural and unintentional scenarios.



# Hisense


HOA Series

## Specifications

### HOA6.0-TAM9696R

|                               |                      |
|-------------------------------|----------------------|
| Pixel Pitch                   | 6                    |
| LED Package                   | SMD copper wire      |
| LED Type                      | SMD2727              |
| Thickness                     | 153mm                |
| Module Resolution             | 32x32                |
| Module Size (WxH/mm)          | 192x192              |
| Cabinet Dimension (WxH)       | 960(W)x960(H)        |
| Cabinet Resolution            | 160x160              |
| Cabinet Weight (kg/panel)     | ≤33kg                |
| Cabinet materials             | Metal plate          |
| Brightness (Nits)             | 5500 Nits            |
| Contrast Ratio                | ≥4000:1              |
| Maintenance                   | Rear Access          |
| IP Rating                     | Front:IP65/Rear:IP54 |
| Max Power Consumption (W/sqm) | ≤850                 |
| Avg Power Consumption (W/sqm) | ≤280                 |
| Viewing Angle (H/V)°          | ≥120 degrees         |
| Refresh Rate (Hz)             | >1920                |
| Operating Environment         | From -20~60oc        |
| Relative Humidity             | 10~90%RH             |
| Life Span                     | ≥100,000hrs          |

## Display Dimensions



### HISENSE B2B EUROPE

Beechavenue 139,  
1119 RB ScHOAhol-Rijk,

Netherlands  
sales@hisense-b2b.com

www.hisense-b2b.com  
+44 (0)115 8248811

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660