

AI Vehicle Computer

**COMPACT AI Vehicle Series**

Computer Vision Edge Unit with NVIDIA Jetson Xavier NX

optional  
LTE / GNSS / Wi-Fi




2x USB 2.0  
microSD  
DisplayPort

Image similar

Power Supply  
9 ... 45VDC

CAN

2x GBit LAN

USB 3.1

HDMI

**IPC/COMPACT A3N - RS**

This fanless COMPACT A3N generation is based on the NVIDIA Jetson Xavier NX processor module and offers a wide range of interface options. The robust and uncompromising industrial design allows the implementation in the most demanding mobile AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- Passively cooled, no moving parts
- Long term availability with fixed BOM



**Product Highlights**

Maintenance free  
Power Ignition Controller  
Shock and vibration resistant  
LTE, GNSS and Wi-Fi connectivity options  
No moving parts / passively cooled

**Product Features**

384-core NVIDIA Volta™ GPU with 48 Tensor Cores  
6-Core ARM v8.2 64-bit NVIDIA Carmel CPU  
8GB / 16GB 128-bit LPDDR4x RAM  
M.2 NVMe slot for storage expansion up to 2TB  
USB 3.1 and HDMI 2.0 ports with dust covers  
Ethernet, passive or active CAN  
LTE, GNSS & WiFi  
Aluminum & Stainless steel housing  
Protection class IP65

**Industries / Applications**

Autonomous Mobile Robots (AMRs)  
Automotive  
Transportation  
Robotics  
Agriculture  
Construction Vehicles



Order Code IPC/RSA3NI19-E102S<sup>1,5</sup> IPC/RSA3NI19-F106S<sup>1,5</sup>

Processor module / Performance		
NVIDIA Jetson Xavier NX   384-core NVIDIA Volta™ GPU with 48 Tensor Cores 6-Core ARM v8.2 64-bit NVIDIA Carmel CPU	•	•
NVIDIA Jetson Xavier NX (16GB RAM)   384-core NVIDIA Volta™ GPU with 48 Tensor Cores 6-Core ARM v8.2 64-bit NVIDIA Carmel CPU	optional	optional
AI Performance (INT8)	21 TOPs	21 TOPs
Memory / Storage		
Data Cache Size	2MB	2MB
128-bit LPDDR4x RAM soldered on board	8GB	8GB
eMMC 5.1 Flash Storage on board	16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) <sup>5</sup>	1	1
microSD card socket <sup>2</sup>	1	1
Features		
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Inertial measurement unit (IMU) <sup>1</sup> STMicroelectronics ISM330DHCXTR	on request	on request
Communication Interfaces		
Display output <sup>behind the service cover</sup>	DisplayPort 1.4	DisplayPort 1.4
Internal USB version 2.0 OTG <sup>behind the service cover</sup> (micro USB Type AB)	1	1
USB version 2.0 <sup>behind the service cover</sup> (Type A)	2	2
Display output	HDMI 2.0	HDMI 2.0
USB version 3.1 (5 Gbit/s) (Type A)	1	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT) (M12 female, x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (M12 female, a-coded)	1	1
Mini PCIe socket <sup>2</sup> , used for extensions depending on configuration	2	2
Serial RS232 <sup>1</sup> (M12 female, a-coded)	optional	optional
USB version 2.0 <sup>1</sup> (M12 female, a-coded)	optional	optional
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>	on request	on request
Wireless Connectivity		
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS <sup>Telit LE910C4-WWX</sup> <sup>6</sup> (Dual nano SIM support)	none	3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.0 <sup>Emwicon WMX6218</sup> <sup>6</sup>	none	2x RP-SMA
High Accuracy GNSS Positioning Module w/ RTK & optional heading support <sup>1</sup> u-blox ZED F9R / F9P	on request	on request
Technical Data		
Dimensions [mm] (housing, excl. mounting)	w182 x h60 x d127	w182 x h60 x d127
Dimensions [mm] (housing, incl. mounting)	w218 x h60 x d127	w218 x h60 x d127
Net weight [gram]	~1600	~1650
Non isolated input voltage, with ignition controller, reverse polarity protected (M12 male, a-coded)	9... 45VDC	9... 45VDC
Power consumption typ. in Watt @ 24V without Add-Ins, idle	~8.5	~8.5
Environmental Conditions		
Operating temperature <sup>3</sup>	-25°C ... +70°C	-25°C ... +70°C
Storage temperature	-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529	IP65	IP65
Conformal coating <sup>4</sup>	on request	on request
Shock (designed to meet)	EN60068-2-27	EN60068-2-27
Vibration (designed to meet)	EN60068-2-64	EN60068-2-64
EMC-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	n/a	RED
MTBF @ 25°C ambient <sup>according to Telcordia SR-332, Environment GB, excluding battery and SSD</sup>	~530 000h	~375 000h

<sup>1</sup> Please contact factory for minimum order quantities

<sup>2</sup> Internal connector

<sup>3</sup> Depending on installation situation and interface connection. Please see user documentation.

<sup>4</sup> On all possible components (excl. Xavier NX module, connectors and wireless devices)

<sup>5</sup> It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes:

IPC/RSA3NI19-[E/F]10xS-01 = 120GB | IPC/RSA3NI19-[E/F]10xS-02 = 240GB | IPC/RSA3NI19-[E/F]10xS-05 = 480GB | IPC/RSA3NI19-[E/F]10xS-10 = 960GB

<sup>6</sup> These LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL (previous products: IPC/RSA3NI19-F102S)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG  
All rights reserved

Syslogic Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:  
info@syslogic.com  
support@syslogic.com  
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)  
+49 7741 9671-420 Germany and Austria



## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660