



ARC-1535-B

**15" Intel® Atom™ SoC Processor
x6211E/x6413E/x6425E Fanless Rugged Touch
Panel PC with IET Expansion**

- > Onboard Intel® Atom™ Elkhart Lake x6211E/x6413E/x6425E Processor
- > Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- > One 260-pin SODIMM sockets supports up to 32GB DDR4 3200 SDRAM
- > 4 x USB3.2, 2 x COM
- > Dual Intel Gigabit LAN
- > 2 x M.2 Slots (Key-B 2242/3042/3052, Key-E 2230)
- > Support Wi-Fi / BT / 4G / 5G (by option)
- > Wide Voltage +12V ~ +24V Input, ErP Power
- > Available Expansion for Audio, USB, COM, HDMI, MPCIe, GPIO, CAN Bus
- > IP65 Compliant Front Panel, IP41 Rear Box
- > With Panel Mount kits included
- > TPM 2.0 Function
- > Fanless Operation Wide temp. from -20°C ~ 55°C (-4°F ~ 131°F)

+ Spec	
-System Information-	
Processor	Onboard Intel® Elkhart Lake Processor Intel Atom® x6211E Processor (6W, 1.5M Cache, up to 3.00 GHz) Intel Atom® x6413E Processor (9W, 1.5M Cache, up to 3.00 GHz) Intel Atom® x6425E Processor (12W, 1.5M Cache, up to 3.00 GHz)
System Memory	1 x 260-pin DDR4 3200 MHz SO-DIMM socket, supports up to 32GB Max (In-BEND ECC supported)
I/O Chipset	EC ITE IT5571
Watchdog Timer	H/W Reset, 1sec. ~ 65535min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
TPM	Onboard NuvoTon NPC-T754AABYX support TPM 2.0
SBC	ARC-EHL
Expansion	
Expansion	1 x M.2 Key-B 2242/3042/3052 with SIM card slot Support SATA3 (BOM option for USB or PCIe for LTE(4/5G)) 1 x M.2 Key-E 2230 Support PCIe/USB Wi-Fi/BT module 1 x 80-pin IET interface
Storage	
Storage	1 x 2.5" Drive Bay (7mm HDD Restricted)
Panel	
LCD Size	15", 4:3
Display Type	XGA
Resolution	1024 x 768
Pixel pitch	0.297mm(H) x 0.297mm(V)
Luminance	300 cd/m ²
Contrast ratio	2000
Viewing angle	88 (U), 88 (D), 88 (L), 88 (R)
Response time	16 ms
Backlight	LED
Touch Type	Projective Capacitive Multi-Touch up to 10 points
Touch Light Transmission	89 %
Touch Controller	USB touch (ILITEK ILI2511, COF)
I/O	
USB Port	4 x USB 3.0
COM Port	1 x RS-232/422/485 1 x RS-232
SATA	1 x SATA III
Other	7 x Knockouts for Antenna Mounting *5 from rear cover + 2 from IET bracket
Display	
Graphic Chipset	Intel® Elkhart Lake SoC integrated Graphics Supports optional dual display
Spec. & Resolution	HDMI: Max. resolution 4096x2160 @ 24Hz (Optional by IET module)
Audio	
Audio Codec	Realtek ALC888S(co-layout 897)
Speaker Output	2 x 2W
Certifications	
Certification Information	CE FCC Class B
Ethernet	



LAN Chipset	2 x Intel® I225-IT 2.5 Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Power Requirement	
DC Input	+12V ~ +24V
DC Input Connector	Lockable DC Jack
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	Wide temp. -20°C ~ 55°C (-4°F ~ 131°F)
Storage Temperature	Wide temp. -30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	3.7 Kgs
Vibration Test	With SSD/M.2 SSD : 3Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30mins/axis
Shock Test	Operating with SSD/M.2 : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G
IP Rating	Front IP65 Rear IP41
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
Power Mode	AT/ATX (ATX is default setting)
System Fan	Fanless
Construction - Front	Die Casting with Cover lens
Construction - Rear	Black Die Casting
Dimension	350.51 x 274.51 x 56.5 mm
Software Support	
OS Information	Win10 / Linux
Ordering Information	
Ordering Information	<p>ARC-1535-X13-B1-1R 15" 1024x768 Industrial Touch Panel PC, ErP Design, PCAP Multi Touch(ALC888S) Intel Atom SoC x6413E 1.50 GHz CPU/2GLAN/2COM/4USB/SPK/12~24V input/12V Adapter</p> <p>Optional IET Module list:</p> <p>ACC-ARC-USB-01R 4 x USB 3.0 IET module for ARC-1535/38</p> <p>ACC-ARC-AUDIO-01R HDMI + 5.1 CH audio IET module for ARC-1535/38</p> <p>ACC-ARC-MPCIE-02R HDMI + MPCIE w/SIM IET module for ARC-1535/38</p> <p>ACC-ARC-COM-01R 2 x Isolated RS-232 IET module for ARC-1535/38</p> <p>ACC-ARC-COM-02R 3 x RS-232 IET module for ARC-1535/38</p> <p>ACC-ARC-COM-03R 2 x RS-232 + USB IET module for ARC-1535/38</p> <p>ACC-ARC-COM-04R 2 x RS-232 + LAN IET module for ARC-1535/38</p> <p>ACC-ARC-GPIO-01R 12-bit GPIO + 2-pin CAN bus IET module for ARC-1535/38</p> <p>ACC-ARC-OBDI-01R OBDII - CAN bus IET module for ARC-1535/38 (OBDII/OBD for small vehicle)</p> <p>ACC-ARC-OBDI-02R OBDII - CAN bus IET module for ARC-1535/38 (J1939J1708 for large vehicle)</p> <p>ACC-ARC-OBDI-03R OBDII - CAN bus IET module for ARC-1535/38 (ISO15765-4 for special large vehicle)</p> <p>E1702031835R USA Power Cord</p> <p>E170203183DR EU Power Cord</p> <p>E170203183BR Japan Power Cord</p> <p>E170203183ER UK Power Cord</p> <p>E1702031800R Australia Power Cord</p>

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660