



HID-2132

21.5" Slim design Multi-touch Medical Panel PC

- > 21.5" 16:9 1080P Display with PCAP Multi touch
- > Onboard 6th Gen. Intel® Core™ i7/i5 / i3/ Celeron Processor
- > Support 1x 260 pin SO-DIMM up to 16GB DDR4 SDRAM
- > Anti-Microbial Finish
- > 4x USB3.0, 1x RS-232/422/485, 1x RS-232, 2x Intel® Gigabit LAN
- > iAMT 11.0 support (for i7/i5 CPU)
- > Dual LED Reading Light Bar
- > Stylish Front OSD keypad touch control button
- > Front Panel IP65 & Fanless Design
- > Ultra-slim design only at 45.5mm thickness
- > 5-kV Isolation USB/ COM/ LAN ports by IET module
- > Built-in NFC module

Spec

-System Information-	
Processor	6th Generation Intel® Core™ i7/i5/i3/Celeron Processor
Platform Controller Hub	integrated in Processor (SOC)
System Memory	1 x 260-pin DDR4 SODIMM (non ECC) support up to 16GB
I/O Chipset	EC ITE IT8528VG/FX
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec. and 1sec./step
H/W Status Monitor	Monitoring System Temperature & Voltage
TPM	Infineon TPM 2.0 (SLB 9665 TT2.0)
SBC	ARC-SKLU + Isolation IET board (Default IET: ARC-SKLU DB-A I/O Ports -> Extend 1x USB / 1x COM / 1x LAN Optional IET : ARC-SKLU DB-B I/O Ports -> Extend 2x USB 2.0 / 1x HDMI/ 1x Line out / 1x Mic in)
Other	iAMT 11.0 support for i7/i5 CPU
Expansion	
Expansion	1 x Full size mini PCIe slot (for mSATA & PCIe & USB2.0 signal)
Storage	
Storage	1 x 2.5" Drive Bay
Panel	
LCD Size	21.5"
Display Type	Full HD
Resolution	1920 x 1080
Pixel pitch	0.24795 (H) x 0.24795 (V)
Luminance	250 cd/m ²
Contrast ratio	1000
Viewing angle	89(U), 89(D), 89(L), 89(R)
Response time	18ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	86%
Touch Controller	USB touch (EETI EXC3188)
I/O	
USB Port	4 x USB 3.0 2 x USB 2.0 (by pin header) 1 x Isolation 5-kV USB1.1 (by IET module)
COM Port	1 x RS-232/422/485 1 x RS-232 1 x Isolation 5-kV RS-232/422/485 (by IET Module)
SATA	1 x SATA III
Other	Dual LED Reading Light Bar I/O Cover Optional MSR/SCR Module with MOQ apply Optional Smart Backup Battery Module Optional WIF/BT module (by mini PCIe) Optional Handset & 1D Barcode Scanner
Display	
Graphic Chipset	Intel® HD Graphics 520
Spec. & Resolution	HDMI: 3840 x 2160 @ 24Hz (optional by IET module)
Audio	
Audio Codec	Realtek ALC888S
Speaker Output	2 x 2W
Certifications	



Certification Information	<p>CE : IEC/EN60601-1-2</p> <p>FCC : Part 15 Class B</p> <p>UL60601-1: AAMI/ANSI ES60601-1:2005/(R)2012 and A1:2012,C1:2009/(R)2012 and A2:2010/(R)2012</p> <p>CB: IEC 60601-1/A1:2012 & EN 60601-1/A1:2013 (Ed 3.1) EN 60601-1:2006+A11:2011+A1:2013+A12:2014</p>
Ethernet	
LAN Chipset	1 x Intel® I211AT, 1 x Intel® I219LM 1 x Isolation 5-kV Intel® I210AT (by IET Module)
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45 1 x RJ-45 (by IET module)
Power Requirement	
DC Input Connector	Lockable DC Jack, +12V~+26V
Power Mode	AT/ATX (ATX is default setting)
Adapter	Medical grade Input: 100~240 Vac/50~60Hz; Output: 90W Adapter (19V/4.74A Adapter)
Battery Operating Time	max. 20 mins backup operation
Battery	1100mAh 4S1P (by optional)
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F~140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	539.6 x 342.6 x 45.2 mm
Weight	6.3 Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
IP Rating	Front IP65
System Fan	Fanless
Construction - Front	White Plastic
Construction - Rear	White Plastic
Finishing	Anti-Microbial
Fanless	Yes
Color	White
Software Support	
OS Information	Win 7, 8.1, 10, Linux
Ordering Information	
Ordering Information	<p>HID-2132-660-A2R Intel® Core™ i7-6600U Processor/8GB DDR4 Memory/PCAP touch/RFID/2*GLAN/ 4*USB3.0/2*COM/Isolation USB/COM/LAN/19V Adapter</p> <p>HID-2132-630-A2R Intel® Core™ i5-6300U Processor/8GB DDR4 Memory/PCAP touch/RFID/2*GLAN/ 4*USB3.0/2*COM/Isolation USB/COM/LAN/19V Adapter</p> <p>HID-2132-610-A2R Intel® Core™ i3-6100U Processor/8GB DDR4 Memory/PCAP touch/RFID/2*GLAN/ 4*USB3.0/2*COM/Isolation USB/COM/LAN/19V Adapter</p> <p>HID-2132-395-A2R Intel® Celeron® 3955U Processor/8GB DDR4 Memory/PCAP touch/RFID/2*GLAN/ 4*USB3.0/2*COM/Isolation USB/COM/LAN/19V Adapter Power Cord: EU E170203183DR US E1702031835R JP E170203183BR UK E170P060370R AU E1702031800R</p>

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660