

# L17W5S-RT

Plastic case, 17" LCD monitor, 1440x900, 400nits

## Specification



### Features

- No guessing or stressing. User friendly controls allow you to operate your monitor easily so you can devote your full attention to the fabulous images on screen.
- The stable removable base is engineered for the physical demands of touch screen use. The sturdy design helps foster intuitive operator entry and flexibility with a variety of applications to help reduce training time and costs and operational errors and help increase employee productivity and customer satisfaction.
- Mouse and keyboard free, use your fingers directly, easy to use for POS display, information board, industrial field, medical and transportation.

Panel	Cell Type / Glass Surface		TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size		Wide / 17" viewable diagonal area	
	Active Area / Pixel Pitch		367.2(H) x 229.5(V) mm / 0.255(H) x 0.255(V) mm	
	Native Resolution / Colors		1440(H) x 900(V) / 262K	
	Brightness / Contrast		400 cd/m² (typ) / 600 : 1	
	Response Time		≤ 12 ms	
	Viewing Angle (typical)		H. 140º(- 70º ~ + 70º) , V. 120º(- 60º ~ + 60º)	
	Light Source		CCFL , Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz	
	Audio System	2W speaker x 2		
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)			
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz			
Power Consumption	Operation / Power Saving	18 watt , < 2 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	0ºC ~ 50ºC (32ºF ~ 122ºF) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 20ºC ~ 60ºC (- 4ºF ~ 140ºF) , 10% ~ 90% (no condensation)		
Certification	FCC , CE			
Dimensions	Physical	With Base(W x H x D) : 414.0 x 338.5 x 240.9 (mm)		
		Without Base(W x H x D) : 414.0 x 273.0 x 60.4 (mm)		
	Carton	W x H x D = 455 x 366 x 160 mm		
Weight	N.W. / G.W.	3.0 Kgs / 4.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)		

Touch (Option)	Resolution	Transparency	Linearity	Durability	Driver
Resistive	2048 x 2048	80% ± 3%	X ≤ 1.0%, Y ≤ 1.0%	35 Million Times	MS-OS, Linux, QNX
Capacitive	2048 x 2048	88% ± 2%	X ≤ 1.0%, Y ≤ 1.0%	200 Million Times	MS-OS, Linux, QNX

**Winsonic**<sup>®</sup>

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com  
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download [www.ewinsonic.com](http://www.ewinsonic.com)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660