

AI Rugged Computer

**COMPACT AI Rugged Vehicle Series**

Computer Vision Edge Unit with NVIDIA Jetson AGX Xavier

LTE / GNSS / Wi-Fi



Dual nanoSIM  
microSD  
HDMI  
USB

Image similar

DC supply | RS232 | 2 x CAN M12 a-coded | 2 x LAN M12 x-coded | USB 3.1 | Digital I/Os

**RPC/COMPACT RSL A3 (E2)**

This fanless RPC COMPACT-A3 is based on the NVIDIA Jetson AGX Xavier processor module and offers a wide range of highly integrated interface options.

The ultra rugged and uncompromising design allows the use in the most demanding AI applications on mobile systems as well as in outdoor applications with harsh environmental conditions and guarantees long-term availability.

- 24/7 continuous operation
- Extended AI computing
- Wide temperature range
- Sealed housing with IP67, IP69 protection
- Shock and vibration resistant



**Product Highlights**

- Ultra rugged
- Sealed housing, protection class IP67 & IP69
- Maintenance free
- Power Ignition controller
- No moving parts / passively cooled
- Pressure equalization membrane
- Resistance to chemicals
- Long term availability (fixed BOM)

**Product Features**

- AGX Xavier or AGX Xavier Industrial
- 512-core NVIDIA Volta™ GPU
- 8-Core ARM v8.2 64-bit NVIDIA Carmel CPU
- 32GB 256-Bit LPDDR4x RAM soldered on board
- NVMe M.2 2280 storage options
- Ethernet, RS232, Digital I/O, USB 3.1, CAN-FD
- SAE J1939 support
- Rugged M12 connectors

**Industries**

- Agriculture
- Construction
- Transportation
- Off-Highway Vehicles
- Heavy Industry
- Autonomous Mobile Robots (AMRs)
- Outdoor applications

Order Code RPC/RSLA3K22-M134S<sup>1</sup> RPC/RSLA3K22-N132S<sup>1</sup>

Rugged AI Computer

Processor module / Performance			
NVIDIA Jetson AGX Xavier   <b>32GB RAM</b>   512-core NVIDIA Volta™ GPU with 64 Tensor Cores		•	•
8-Core ARM v8.2 64-bit NVIDIA Carmel CPU		•	•
AI Performance		32 TOPs	32 TOPs
NVIDIA Jetson AGX Xavier   <b>64GB RAM</b>   512-core NVIDIA Volta™ GPU with 64 Tensor Cores		on request	on request
NVIDIA Jetson AGX <b>Xavier Industrial</b> 512-Core NVIDIA Volta™ GPU (ECC) with 64 Tensor Cores		on request	on request
Memory / Storage			
Data L3 Cache Size		4MB	4MB
256-Bit LPDDR4x RAM soldered on board		32GB	32GB
eMMC 5.1 Flash Storage on board		32GB	32GB
microSD Card socket		1	1
M.2 2280 Key M socket (for NVMe SSD) <sup>2</sup>		1	1
Features			
Inertial measurement unit (IMU) <small>STMicroelectronics ISM330DHCXTR</small>		•	•
Real time clock (RTC) with battery backup <small>Renata CR2477 (950 mAh)</small>		•	•
Communication Interfaces			
Display output <small>behind the back service cover</small>	(1x Standard HDMI connector)	HDMI 2.0	HDMI 2.0
Internal USB version 2.0 OTG <small>behind the back service cover</small>	(micro USB Type AB )	1	1
USB version 2.0 <small>behind the back service cover</small>	(Type A )	2	2
Ethernet 10/100/1000 Mbit BASE-T	(M12 female x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated	(M12 female a-coded)	2	2
Digital I/O's, 12/24VDC <sup>1</sup>	(M12 male a-coded)	4 in & 2 out	4 in & 2 out
Serial RS232 <small>RX, TX, RTS, CTS, GND</small>	(M12 male a-coded)	1	1
USB version 3.1 (5Gbit/s)	(Type A, IP67)	1	1
Mini PCIe socket <sup>2</sup>		1	1
PPS Input <sup>1, 3.3V (LVCMOS), connected to Xavier GPIO</sup>	(1x SMA)	on request	on request
Power over Ethernet - IEEE802.3at 10/100/1000Mbit <sup>1, taller housing: h105mm</sup>	(M12 female x-coded)	on request	on request
GMSL2 camera inputs <sup>1, taller housing: h105mm</sup>	(4x/8x FAKRA-Z)	on request	on request
Wireless Connectivity			
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS <sup>6, Sierra Wireless EM7590 (Dual nano SIM support)</sup>		3x SMA	on request
Wireless LAN (Wi-Fi 5) 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.1 <sup>Intel Wireless-AC 9260</sup>		2x RP-SMA	on request
Cellular 5G module (4G/3G fallback) with GNSS		on request	on request
Wireless LAN (Wi-Fi 6) 802.11ax/ac/a/b/g/n dual-band 2x2 MIMO		on request	on request
High Accuracy (RTK) GNSS positioning module with optional heading support <sup>u-blox ZED F9R / F9P</sup>		on request	on request
Technical Data			
Dimensions mm (housing, excl. mounting)		w250 x h75 x d170	w250 x h75 x d170
Net weight in gram		~3050	~3000
Non isolated input voltage, with Ignition controller <small>reverse polarity protected</small>	(M12 5P male a-coded)	9 ... 45VDC	9 ... 45VDC
Power consumption <sup>3</sup>		depends on power mode (15W, 30W, MAXN)	
Environmental Conditions			
Operating temperature <sup>3</sup>		-25°C ... +65°C	-25°C ... +65°C
Storage temperature		-25°C ... +80°C	-25°C ... +80°C
Ingress protection standard according to EN60529 (ISO 20653)		IP67 / IP69	IP67 / IP69
Conformal coating <sup>4</sup>		on request	on request
Road vehicles, UN/ECE R10 (E-mark) <sup>5</sup>		on request	on request
Shock ISO 15003 / EN60068-2-64 (designed to meet)		•	•
Vibration ISO 15003 / EN60068-2-64 (designed to meet)		•	•
EMI-Conformity		EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)		EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)		RED	RED
MTBF @ 25°C ambient <small>according to Telcordia SR-332, Environment GB, excluding battery</small>		~300 000h	~400 000

<sup>1</sup> Please contact factory for minimum order quantities

<sup>2</sup> Internal connector

<sup>3</sup> Depending on installation situation, power mode and interface connection. See user documentation.

<sup>4</sup> On all possible components (excl. NVIDIA Xavier Module, connectors and wireless devices)

<sup>5</sup> UN/ECE-R10 is the type-approval test for European automotive electronics. It includes a variety of testing including RF immunity and emissions, transient immunity and emissions.

<sup>6</sup> The first versions of this product, featured the Sierra Wireless EM7455 LTE module (RPC/RSLA3K22-M132S), this has been switched to the EM7590 for mass production, due to the EM7455 being EOL.

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG  
All rights reserved

Syslogic Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 1.0 | January 2023

For further information and support:

info@syslogic.com  
support@syslogic.com  
www.syslogic.com

+41 56 200 90 40  
+49 7741 9671-420

Switzerland (Headquarters)  
Germany and Austria



## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660