

NVIDIA® Jetson Rugged Computer



NRU-160-AWP Series

IP66 Waterproof Jetson Orin™ NX/ Nano AI Computer with 6x GMSL2 or 4x PoE+ GbE Ports



CE FC

Key Features

- Powered by NVIDIA® Orin™ NX or Orin™ Nano SoM bundled with JetPack
- IP66 waterproof and dustproof
- -25°C to 70°C fanless operation (No throttling at 70°C with 20W TDP Mode)
- 6x GMSL2 automotive cameras via FAKRA Z connectors (NRU-161V-AWP)
- 4x PoE+ GbE via M12 X-coded connectors (NRU-162S-AWP)
- 1x CAN FD and 1x RS232 via M12 A-coded connectors
- 225 x 136 x 55 mm low-profile design
- 8V to 35V wide-range DC input with built-in ignition power control

Introduction

The NRU-160-AWP series is a rugged, IP66 waterproof edge AI computer driven by an NVIDIA® Jetson Orin™ NX or Orin™ Nano. Its target applications include smart city roadside installations, AI inspection in food factories, perception units for outdoor robots, and ADAS for off-highway vehicles. Furthermore, it aims to redefine rugged, wide-temperature edge AI with its waterproof features at an affordable cost, achieved through a streamlined mechanical design, carefully selected waterproof connectors and standardized cable kit.

Powered by NVIDIA® Jetson Orin™ NX, the NRU-160-AWP delivers superior AI inference with up to 100 sparse TOPS (INT8) and can transcode up to eighteen 1080P video streams simultaneously. Designed to accommodate various camera requirements for vision-based AI applications, the NRU-160-AWP comes in two models: the NRU-161V-AWP, which supports up to 6x GMSL2 automotive cameras with pre-built drivers for selected cameras with IMX390, ISX031, and IMX490 CMOS sensors; and the NRU-162S-AWP, which offers 4x PoE+ GbE ports for IP or industrial GigE cameras. Additionally, a waterproof GbE port is provided for data transmission with other computers or LiDAR.

The NRU-160-AWP is designed for edge deployment, whether in-cabinet, in-vehicle, or in-robot. Its compact 225 x 136 x 55 mm profile makes it ideal for confined spaces. It is equipped with an 8V to 35V wide DC input range, ignition power control, 1x CAN FD bus port, and 1x RS232 port. It also features one mini-PCIe socket for CAN/ COM/ WiFi modules and one M.2 B-key socket for 4G LTE/ 5G NR mobile communication modules.

The integration of IP66 waterproof capability, Orin NX AI performance, and rich onboard camera connectivity strikes a balance between ruggedness, performance, and cost. It is a ready-to-deploy waterproof edge AI platform for smart agriculture, mining, construction, roadside applications, edge inspection, and outdoor AMRs.


Specifications

System Core		Internal I/O Interface	
Processor	NVIDIA® Jetson Orin™ NX system-on-module (SOM), comprising NVIDIA® Ampere GPU and ARM Cortex CPU	Mini PCI Express	1x full-size mini PCI Express socket (PCIe + USB 2.0)
Memory	16GB/ 8GB LPDDR5 @ 3200 MHz on SOM	M.2	1x M.2 3042/3052 B key (USB 3.2 Gen 1 + USB 2.0) for LTE/5G module with dual micro SIM support
eMMC	N/A	Storage	
Panel I/O Interface		M.2 NVMe	1x M.2 2242 M key socket (PCIe Gen 3x1) for NVMe SSD
GMSL2	NRU-161V-AWP	Power Supply	
	6x waterproof GMSL2 FAKRA Z connectors, supporting multiple configurations: Configuration A. 6x AC-IMX390 (2MP@30FPS) Configuration B. 6x AC-ISX031 (3MP@30FPS) Configuration C. 4x AC-IMX490 (5MP@30FPS)	DC Input	
Ethernet Port	NRU-161V-AWP	8V to 35V DC input and ignition power control via M12 A-coded, 5-pin connector (IGN/ GND/ V+) ^[1]	
	NRU-162S-AWP	Mechanical	
PoE+	NRU-162S-AWP	Dimension	
	IEEE 802.3at PoE+ PSE for Port 1 to Port 4 with 50W total power budget	225 mm (W) x 136 mm (D) x 55 mm (H) (excluding wall-mount)	
USB		Weight	
	2x USB 2.0 ports via M12 A-coded 8-pin connector 1x USB Type C port (for system flashing and OTG, under service door)	3.0 kg (excluding wall-mount)	
Video Port	1x VGA, supporting 1920x1080 at 60Hz via M12 A-coded 17-pin connector	Mounting	
Serial Port	1x RS-232 port via M12 A-coded 8-pin connector	VESA 75 mount (standard) Wall-mount (standard)	
CAN bus	1x CAN FD port via M12 A-coded 8-pin connector	Environmental	
Isolated DIO	1x isolated GPS PPS input via M12 A-coded 8-pin connector	Operating Temperature	
		-25°C to 70°C with passive cooling (20W TDP mode) ^[2]	
		Storage Temperature	
		-40°C to 85°C	
		Humidity	
		10% to 90%, non-condensing	
		Vibration	
		MIL-STD-810H, Method 514.8, Category 4	
		Shock	
		MIL-STD-810H, Method 516.8, Procedure I	
		EMC	
		CE/ FCC Class A, according to EN 55032 & EN 55035 EN 50121-3 (EN 50155:2017, Clause 13.4.8) (NRU-162S-AWP only)	


^[1]The required DC input range is 8V to 35V when the system load is under 60W. The required DC input range is 12V to 35V when the system load is between 60W to 96W. The required DC input range is 20V to 35V when the system load is between 96W to 160W.
^[2]For sub-zero and over 60°C operating temperature, a wide temperature HDD or Solid State Disk (SSD) is required.

NRU-160-AWP Series

Appearance



Dimensions



Ordering Information

Model No.	Product Description
NRU-161V-AWP	IP66 Waterproof Jetson Orin™ NX/ Nano Edge AI Computer with 6x GMSL2 Ports
NRU-162S-AWP	IP66 Waterproof Jetson Orin™ NX/ Nano Edge AI Computer with 4x PoE+ GbE Ports
Jetson Module Option	Options for Different Jetson Orin™ NX and Jetson Orin™ Nano SKUs
NVMe Option	Options for Different Capacities of M.2 2242 NVMe Storage

Optional Accessories

PA-60W-OW	60W AC/ DC power adapter 12V/ 5A; cord end terminals for terminal block, operating temperature: -30 to 60°C
PA-160W-OW	160W AC/ DC power adapter 20V/ 8A; 18AWG/ 120cm; cord end terminals for terminal block, operating temperature: -30 to 70°C
AC-ISX031-H60	Sony ISX031 CMOS sensor w/ built-in ISP; 1920x1536 @30fps, HFOV H63.9°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-ISX031-H120	Sony ISX031 CMOS sensor w/ built-in ISP; 1920x1536 @30fps, HFOV H120.6°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-ISX031-H190	Sony ISX031 CMOS sensor w/ built-in ISP; 1920x1536 @30fps, HFOV H195.9°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX390-H60	Sony IMX390 CMOS sensor camera; 1920x1080 @ 30fps; LFM; HFOV 63.9°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX390-H120	Sony IMX390 CMOS sensor camera; 1920x1080 @ 30fps; LFM; HFOV 120.6°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX390-H190	Sony IMX390 CMOS sensor camera; 1920x1080 @ 30fps; LFM; HFOV 186°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX490-H30	Sony IMX490 CMOS sensor camera; 2880x1860 @30fps; LFM; HFOV 30.0°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX490-H60	Sony IMX490 CMOS sensor camera; 2880x1860 @30fps; LFM; HFOV 62.5°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap
AC-IMX490-H120	Sony IMX490 CMOS sensor camera; 2880x1860 @30fps; LFM; HFOV 120°; IP67+IP69K; -40°C to 85°C operating temperature; male FAKRA connector; active alignment; without lens cap

All specifications and photos are subject to change without prior notice

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660