

iEP-6010E Series

Industrial IoT Controller

Preliminary



Basic SKU



POE SKU



5G SKU

KEY FEATURES

- NVIDIA Jetson Orin NX SOM support, up to 100 SPARSE (50 DENSE) INT8 TOPS
- NVIDIA Jetson Orin Nano SOM support, up to 40 SPARSE (20 DENSE) INT8 TOPS
- Wide range operating temperature (-25 ~ 60°C)
- 12V ~ 36V wide range DC input
- 2nd DC IN Interface for USB Type-C power adaptor
- Ultra Compact Size
- Carrier board reserved 2pcs Dual Lane MIPI-CSI2 connectors****

SPECIFICATIONS

Processor System

System on Module	- NVIDIA Jetson Orin NX SOM 16GB support (Basic SKU iEP-6010E-000, PoE SKU iEP-6010E-001, 5G SKU iEP-6010E-003) - NVIDIA Jetson Orin NX SOM 8GB support (Basic SKU iEP-6011E-000) - NVIDIA Jetson Orin Nano SOM 8GB support (Basic SKU iEP-6012E-000, PoE SKU iEP-6012E-001, 5G SKU iEP-6012E-003) - NVIDIA Jetson Orin Nano SOM 4GB support (Basic sku iEP-6013E-000)
Video	1 x HDMI 2.0 (Orin NX) / 1.4 (Orin Nano)
Memory	16GB 128-bit LPDDR5 (Jetson Orin NX 16GB) 8GB 128-bit LPDDR5 (Jetson Orin NX 8GB) 8GB 128-bit LPDDR5 (Jetson Orin Nano 8GB) 4GB 64-bit LPDDR5 (Jetson Orin Nano 4GB)
TPM	TPM2.0

I/O Interface

Ethernet	2 x Gigabit LAN
PoE (Option)	2x Intel I210AT ports, each port supports IEEE 802.3AF PoE (Orin NX SOM 16GB PoE SKU iEP-6010E-001, Orin Nano SOM 8GB PoE SKU iEP-6012E-001)
Serial Port	1 x RS-232, 1 x RS-232/422/485 (Pin9 default is N/A, +5V or +12V/1A software programmable.)
USB	2 x USB 3.2 Gen 2x1 (one with Locking) 2 x USB 2.0, 1 x Micro USB 2.0 (Device mode only, for OS Flash)
Proprietary IO	DPR connector: 1 x DB15 for 4*DI, 4*DO, GND, Power Pin (Default is N/A, +5V/1A software programmable), PowerOn, LED+, LED-, GND, Reset ISC connector: 1 x DB15 for Power Pin (Default is N/A, +3V/1A software programmable), 5 x GND, 1 x I2C, 1 x SPI, 1 x CANBUS

Expansion

SIM	1 x Nano SIM Card slot
RF& Antenna (Option)	up to 4x 5G/4G LTE antenna + 2 x Wi-Fi antenna for 5G SKU
M.2 Socket	1 x M.2 (Key B, 3042/3052/2280) -For PCIe Gen3 x1 / USB3.2 Gen2x1 5G module (Option) (5G SKU Only, Orin NX SOM 16GB 5G SKU iEP-6010E-003, Orin Nano SOM 8GB 5G SKU iEP-6012E-003) -For PCIe Gen3 x1 / USB3.2 Gen2x1 4G LTE module (Option) (5G SKU Only, Orin NX SOM 16GB 5G SKU iEP-6010E-003, Orin Nano SOM 8GB 5G SKU iEP-6012E-003) -For PCIe Gen3 x1 M.2 B Key 2280 SSD module (Option, Basic SKU Only) 1 x M.2 (Key E, 2230) for PCIe Gen3 x1 Wi-Fi and USB2.0 Bluetooth module****

Power Requirements

DC Input	1 st DC IN source: 12V~36V DC input, 80V Surge Protection, OVP, UVP, OCP, Reverse Protection, Phoenix type connector 2 nd DC IN source: PD3.0 20V USB Type-C power adaptor interface (Locking feature), It can be backup DC input when 1 st DC IN is 21V~36V
AC to DC Adaptor (Option)	For Basic SKU: 120W Adaptor (latch type), AC input 100-240Vac, 1.8A 50-60Hz, DC output 19V, 6.32A For POE/5G SKU: 330W Adaptor, AC input 100-240Vac, 4.2A 50-60Hz, DC output 24V, 13.75A

Storage Device

M.2 Socket	1 x M.2 (Key M, 2280) for wide temperature PCIe Gen3 x4 NVMe SSD module (System Operating temperature -25°C~60°C) 1 x M.2 (Key M, 2280) for wide temperature PCIe Gen4 x4 NVMe SSD module (System Operating temperature -25°C~55°C) PCIe Gen4 x4 SSD only supported by Orin NX SOM
Micro SD Card slot	1 x Micro SD Card Slot (UHS-I/SDR-50)

Mechanical

Dimensions	Basic SKU : 55(W) x 170(H) x 134(D) mm POE/5G SKU : 68(W) x 170(H) x 134(D) mm
Indicator	1 x Storage LED 1 x 2 nd DC-IN LED
Function	Power on button with LED, OS Flash Button, Reset Tact Switch Enable/Disable Auto power on Switch
Net Weight	Basic SKU: 1.3kg, 5G/POE SKU: 1.6kg
Mounting (Option)	Wall mounting or VESA mounting bracket (horizontal mounting for Basic SKU only) Wall mounting or Din Rail mounting bracket (vertical mounting for all SKU)

Environmental

Operating Temperature	-25~60°C (-13~140°F) for Basic sku, PoE sku, or 5G sku w/ 4G LTE Module when installed with WT SSD Gen3 x4 -25~55°C (-13~131°F) for Basic sku, PoE sku, or 5G sku w/ 4G LTE Module when installed with WT SSD Gen4 x4 -25~55°C (-13~131°F) for 5G sku w/ 5G Module when installed with WT SSD Gen4 x4 or WT SSD Gen3 x4 (w/ air flow 0.5~0.8m/s)
Storage Temperature	-40°C~85°C (-40°F~185°F)
Humidity	~90% @ 45°C (non-condensing)
EMC	CE, FCC Class A (EN61000-6-4/-2) *(e)
Safety	LVD*(e)

Add-on Feature / OS Support

2 nd DC IN Interface	PD3.0 20V USB Type-C power adaptor interface (Locking feature), It can be backup DC input when 1 st DC IN is 21V~36V
Carrier board feature	Carrier board reserved 2pcs Dual Lane MIPI-CSI2 connectors****
OS Support	NVIDIA JetPack 5.1.1 *(e)

*(e) means estimation.

****Boot, shutdown or resume from suspend may fail randomly. It is current NVIDIA JetPack 5.1.1 limitation.

*****Bluetooth function is disable and it is current NVIDIA JetPack 5.1.1 limitation for Intel AX210 Industrial SKU.

*****MIPI-CSI2 camera need to be turned off before system going to sleep mode.

It is current NVIDIA JetPack 5.1.1 limitation.

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660