

AI Vehicle Computer

COMPACT AI Vehicle Series

Intelligent Machine Learning Unit with NVIDIA Jetson TX2



AI Vehicle Computer

IPC/COMPACT A2 - RS

This fanless RS COMPACT-A2 generation is based on the NVIDIA Jetson TX2(i) processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- No moving parts / passive cooling
- Product lifecycle management
- Long term availability with fixed BOM

 **nvidia.** Linux for Tegra (L4T)

Product Highlights

Maintenance free
No moving parts / passive cooling
ARM CPU core
Hardware watchdog
Temperature supervision
ESD- protection on all interfaces
Long term availability (fixed BOM)
Shock and vibration resistant

Product Features

256-core NVIDIA Pascal™ GPU
Dual-Core NVIDIA Denver 2 64-Bit CPU
Quad-Core ARM® Cortex®-A57 MPCore
8GB 128-bit LPDDR4 RAM soldered on board
Socket for CFast
Ethernet, USB, Passive or Active CAN
Aluminum & Stainless steel housing
Protection class IP40

Markets / Applications

Automated Guided Vehicles (AGV)
Transportation
Cleantech



Processor module / Performance		Order Code	IPC/RSA2I20-A103S ¹
NVIDIA Jetson TX2 256-core NVIDIA Pascal™ GPU			•
NVIDIA Jetson TX2i 256-core NVIDIA Pascal™ GPU			on request
NVIDIA Jetson TX2 4GB 256-core NVIDIA Pascal™ GPU			on request
Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore			•
AI Performance			1.3 TOPs
Memory / Storage			
Data Cache Size			2MB
4ch x 32-bit LPDDR4 RAM soldered on board			8GB
eMMC 5.1 Flash Storage on board			32GB
microSD Card socket ²			1
CFast socket with retention frame ²			1
Features			
Inertial measurement unit (IMU) STMicroelectronics ISM330DLC			•
Real time clock (RTC) with battery backup Renata CR2450N (540mAh)			•
Communication Interfaces			
Graphic interface			DisplayPort 1.2
USB version 3.0		(Type A)	2
Internal USB version 2.0 OTG behind the cover		(micro USB Type AB)	1
Ethernet 10/100/1000Mbit (1x native, 1x I210-IT)		(M12 female x-coded)	2
Active/passive-CAN ESD protected, isolated		(1x DSUB9)	2
RS232 / RS422/485 ESD protected		(DSUB9)	optional
Mini PCIe socket ²			1
I2C bus ²			•
Buzzer			•
MIPI CSI-2 Camera Interface ²			•
Wireless Connectivity			
Cellular Module (LTE/UMTS/GSM) with GNSS positioning functionality ¹		(3x SMA)	on request
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 4.1		(2x RP-SMA)	•
Technical Data			
Dimensions w174 x h52 x d127 mm (housing without mounting bracket)			•
Net weight in gram			~950
Non isolated input voltage, with Ignition controller, reverse polarity protected		(M12 4P male a-coded)	9... 45VDC
Current consumption typ. in mA @ 24V without Add-Ins, idle			~400
Power consumption typ. in Watt @ 24V without Add-Ins, idle			~10
Environmental Conditions			
Operating temperature ³			-25°C ... +70°C
Storage temperature			-25°C ... +80°C
Extended operating temperature -40°C ... +70°C			with TX2i
Extended storage temperature -40°C ... +85°C			with TX2i
Protection standard			IP40
UN/ECE R10 (E-mark) certification			on request
Conformal coating ⁴			on request
Shock (designed to meet)			EN60068-2-27
Vibration (designed to meet)			EN60068-2-64
EMC/EMI-Conformity			EN55032 / EN55035
Safety (designed to meet)			EN62368-1
Radio and Telecommunication (designed to meet)			RED
MTBF @ 25°C ambient according to Telcordia SR-332, Environment GB, excluding battery			~700 000h

¹ Please contact factory for minimum order quantities

² Internal connector

³ Depending on installation situation and interface connection. Please see user documentation

⁴ On all possible components (excl. TX2(i) Module, connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG
All rights reserved

Syslogic Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:

info@syslogic.com
support@syslogic.com
www.syslogic.com

+41 56 200 90 40 Switzerland (Headquarters)
+49 7741 9671-420 Germany and Austria

 **syslogic**
industrial computing

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660