

CS-W121C/P2102

21.5" TFT-LCD Sunlight Readable and Modular Panel PC with 8th Gen. Intel® Core™ U Series Processor



- 21.5" TFT-LCD with Ultra-high Brightness up to 1,000 nits and 1920 x 1080 Resolution
- Onboard 8th Generation Intel® Core™ U Series Processor
- 2x DDR4 SO-DIMM Socket, Supports Up to 2400MHz, 64GB
- Supports Triple Independent Display
- Integrated USB 3.2 Gen 2 supports up to 10Gbps
- M.2 E Key Socket for Wireless Module or Intel CRF Module
- Supports Ignition Sensing Function (IGN) (with optional CFM module)
- Supports 2x PoE+ Function (with optional CFM module)
- Wide Range Operating Temperature 0°C to 70°C
- Designed with Rugged Aluminum Die-casting Front Bezel
- True Flat IP65 Compliant Front Panel Protection
- Supports Panel / VESA / Rack Mounting

Overview

The CS-W121C/P2102 is a 21.5" TFT-LCD sunlight readable panel PC that offers sufficient screen brightness for better image quality in outdoor usage. The panel PC is powered by Intel® 8th generation Core™ U series processor that brings outstanding computing performance boost up to 84% at a TDP of 15 watts, compared to 6th generation Intel® Core™ U series. To enable faster responsiveness and deal with multi tasks with ease, the CS-W121C/P2102 is equipped with two DDR4 2400 SODIMM sockets for up to 64 GB memory.

With its slim design, the CS-W121C/P2102 offers extensive I/O to fulfill different connectivities and can easily fit into almost any space limited environment. For wireless connectivity, the CS-W121C/P2102 has 1x M.2 2230 E key and 2x full-size Mini-PCIe expansions which can be installed various add-on cards to enable Wi-Fi, 3G, and LTE communication. Besides, the CS-W121C/P2102 supports Control Function Module (CFM) Technology to install optional CFM modules for increasing power over ethernet and power ignition sensing functions according to user's specific applications. Featuring rigorous industrial protections, wide range operating temperature (0°C to 70°C), IP65 dust/waterproof front panel, and wide range DC power input (9 to 48VDC), the CS-W121C/P2102 is appropriate for tough outdoor applications under direct sunlight. Furthermore, the CS-W121C/P2102 supports Cincoze patented Convertible Display System (CDS) technology, allowing users to replace display module or computer module on-site easily and thereby reducing maintenance costs and downtime.

Specifications

Display

| | |
|---------------------|------------------------------|
| LCD Size | • 21.5" (16:9) |
| Max. Resolution | • 1920x1080 (Full HD) |
| Brightness (cd/m2) | • 1,000 |
| Contrast Ratio | • 5,000:1 |
| LCD Color | • 16.7M |
| Pixel Pitch (mm) | • 0.24825 (H) x 0.24825 (V) |
| Viewing Angle (H-V) | • 178 / 178 |
| Backlight MTBF | • 50,000 hrs (LED Backlight) |

Touch

| | |
|----------------------|---|
| Projected Capacitive | V |
|----------------------|---|

System

| | |
|-----------|---|
| Processor | <ul style="list-style-type: none"> • Onboard 8th Intel® Core™ U Processors (Whiskey Lake) - Intel® Core™ i5-8365UE Quad Core Processor (6M Cache, up to 4.10 GHz) - Intel® Core™ i3-8145UE Dual Core Processor (4M Cache, up to 3.90 GHz) - TDP: 15 W |
| Memory | <ul style="list-style-type: none"> • 2x DDR4 2400 MHz 260-Pin SO-DIMM Socket • Supports up to 64 GB (un-buffered and non-ECC) |

Graphics

| | |
|------------------------|---|
| Graphics Engine | • Integrated Intel® UHD Graphics 620 |
| Maximum Display Output | • Supports Triple Independent Display (via VGA and DisplayPort Outputs) |

Audio

| | |
|-------------|-----------------------------------|
| Audio Codec | • Realtek ALC888-GR |
| Line-out | • 1x Speaker-out Phone Jack 3.5mm |
| Mic-in | • 1x Mic-in, Phone Jack 3.5mm |

External I/O Interface

| | |
|-----|--|
| VGA | • 1x VGA (1920 x 1200 @60Hz) |
| DP | • 1x DisplayPort (4096 x 2304 @ 60Hz) |
| LAN | • 2x GbE LAN (Supports WoL, Teaming, Jumbo Frame & PXE), RJ45 - GbE1: Intel® I219-LM - GbE2: Intel® I210 |
| USB | • 3x USB 3.2 Gen2 (Type A) • 2x USB 2.0 (Type A) |
| COM | • 4x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9 |

DIO

| | |
|-----|---|
| DIO | • 16x Isolated DIO (8x DI/8x DO), 20-Pin Terminal Block |
|-----|---|

Storage

| | |
|---------|--|
| SSD/HDD | • 2x 2.5" HDD/SSD Drive Bay (SATA 3.0) |
| RAID | • Supports RAID 0/1 |

Expansion

| | |
|---|---|
| M.2 Express | • 1x M.2 2230 E Key for Socket Wireless Module, Supports Intel CRF Module |
| Mini PCI Express | • 2x Full-size Mini-PCIe Socket |
| SIM Socket | • 1x Front Accessible SIM Socket |
| CFM (Control Function Module) Interface | • 2x Control Function Module (CFM) Interface |
| Antenna Hole | • 4x Antenna Hole |

Other Function

| | |
|------------------------|--|
| Internal Speaker | • AMP 2W + 2W |
| Power Ignition Sensing | • 1x Ignition DIP Switch (12V/24V, need to work with CFM module) |
| Clear CMOS Switch | • 1x Clear CMOS Switch |
| Rest Button | • 1x Reset Button |
| Instant Reboot | • Supports Instant Reboot Technology (0.2 sec) |
| Watchdog Timer | • Software Programmable Supports 256 Levels System Reset |
| OSD Function | • LCD On/Off, Brightness Up, Brightness Down |

Power

| | |
|--------------------------|--|
| Power Button | • 1x ATX Power On/Off Button |
| Power Mode Switch | • 1x AT/ATX Mode Switch |
| Power Input | • 9 - 48VDC, 3-pin Terminal Block |
| Remote Power On/Off | • 1x Remote Power On/Off Connector, 2-pin Terminal Block |
| Power Adapter (Optional) | • AC/DC 12V/5A 60W or AC/DC 24V/5A 120W |

Physical

| | |
|-------------------------|--|
| Dimension (W x D x H) | • 550 x 330.5 x 76 mm |
| Weight Information | • 7.8 Kg |
| Mechanical Construction | • Rugged Aluminum Die-casting Front Bezel and Heavy Duty Metal Chassis |
| Mounting | • Panel / VESA / *Rack Mounting (*with optional mounting kit) |
| Physical Design | • Fanless Design • Jumper-less Design |

Reliability & Protection

| | |
|--------------------------------|--|
| Reverse Power Input Protection | • Yes |
| Over Voltage Protection | • Protection Range: 51~58V • Protection Type: shut down operating voltage, re-power on at the preset level to recover |
| Over Current Protection | • 15A |
| Surge Protection | • 3.84 kV (impedance 12 ohm 1.2/50µs waveform) |
| CMOS Battery Backup | • SuperCap Integrated for CMOS Battery Maintenance-free Operation |
| ESD Protection | • +/-8kV (air), +/-4kV (contact) |

Operating System


| | |
|---------|----------------------|
| Windows | • Windows® 10 |
| Linux | • Support by Project |

Environment


| | |
|-----------------------|--|
| Operating Temperature | • 0°C to 70°C (with Extended Temperature Peripherals; Ambient with Air Flow) |
| Storage Temperature | • -20°C to 70°C |
| Relative Humidity | • 95% RH @ 39°C (Non-condensing) |
| EMC | • CE, FCC, ICES-003 Class A |
| IP Level | • IP65 Compliant Front Panel |

External Layout


Front I/O




Rear I/O




Left I/O



Right I/O



Dimensions



Unit: mm

Ordering Information

Available Models

| Model No. | Description |
|---------------------------|--|
| CS-W121C-R10/P2102-i5-R10 | 21.5" Full HD TFT-LCD Modular Panel PC with 8th Gen. Intel Core i5-8365UE Quad Core Processor and P-Cap. Touch |
| CS-W121C-R10/P2102-i3-R10 | 21.5" Full HD TFT-LCD Modular Panel PC with 8th Gen. Intel Core i3-8145UE Dual Core Processor and P-Cap. Touch |

Package Checklist

- | | |
|--|------------------------------------|
| • CS-W121C/P2102 Panel PC x 1 | • DIO Terminal Block Connector x 2 |
| • Thermal Pad (for CPU Thermal Block) x 1 | • Utility Driver DVD x 1 |
| • Power Terminal Block Connector x 1 | • Screws Pack x 5 |
| • Remote Power On/Off Terminal Block Connector x 1 | • Panel Mounting Kit x 1 |

Optional Modules

| Model No. | Description |
|------------|---|
| CFM-IGN101 | CFM Module with Power Ignition Sensing Control Function, 12V/24V Voltage Detection Selectable |
| CFM-PoE04 | CFM Module with PoE Control Function, Individual Port 25.5W |
| URM01 | Universal 19" Rack Mount Kit for Industrial Panel PC & Industrial Monitor |

Optional Accessories

| Model No. | Description |
|---------------|---|
| GST60A12-CIN1 | Adapter AC/DC 12V 5A 60W, GST60A12-CIN1, wide temp (-30°C ~ +70°C), level VI |
| GST120A24-CIN | Adapter AC/DC 24V 5A 120W, GST120A24-CIN, wide temp (-30°C ~ +70°C), level VI |

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660