

Interactive Flat Panel Displays

IFD55TH652/3





Key Features



Different Sizes for various classrooms

Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



Ease of use with Android

Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.



Wireless Presentation

Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screen at the same time.



Palm Erase

Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.



Panel

Screen Size	55"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	400 cd/m ²
Native Resolution	UHD: 3840 x 2160 - HDR10	Contrast Ratio (typical)	1300:1
Dynamic Contrast Ratio	40000:1	Panel Life Time (Min.)	30000 Hr
Response Time (typical)	6 ms	Active Area (H x V)	1210 x 681 mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	16.7 M (8-bit)
Screen Treatment	2H	Haze Level	8%
Refresh Rate	60 Hz	Front Type	Black Super Narrow Bezel
Orientation	Horizontal	Operation Hours	16/7
Area of Usage	Indoor		

Built-in System

Mainboard Model 17MB135VS

Monitor Connectivity

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	3xHDMI2.0, 2xUSB2.0, USB2.0(Internal), 1xMicroSD	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), 2*Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Touch Interactivity

Sensitivity Any touch with finger, gloved hand or pointer Windows®7, Windows®8, Compatibility Windows®10, Vista, XP, Mac® OS, Linux, Android Calibration No need Accuracy Reporting Rate Up to 450 fps Glass Type Anti Glared (AG), 4mm Tempered Frame Rate up to 450 fps Communication USB 2.0 Power Supply Mode USB Supply Voltage Average Current 400mA Response Time Touch Accuracy UNImited	Type of Touch Technology	Infrared (IR) Technology	Continuous Touch Points	10 Points
Compatibility Windows®10, Vista, XP, Mac® OS, Linux, Android Calibration No need Accuracy Reporting Rate Up to 450 fps Glass Type Anti Glared (AG), 4mm Tempered Frame Rate up to 450 fps Communication USB 2.0 Power Supply Mode USB Supply Voltage DC 5V +/- 5% Average Current 400mA Response Time Landscape support Landscape support USB 2.0 DC 5V +/- 5% 10ms	Sensitivity		Connectivity	HID, TUIO, Flash
Reporting Rate Up to 450 fps Glass Type Anti Glared (AG), 4mm Tempered Frame Rate up to 450 fps Communication USB 2.0 Power Supply Mode USB Supply Voltage DC 5V +/- 5% Average Current 400mA Response Time 10ms	Compatibility	Windows®10, Vista, XP, Mac® OS,	Orientation	Landscape support
Frame Rate up to 450 fps Communication USB 2.0 Power Supply Mode USB Supply Voltage DC 5V +/- 5% Average Current 400mA Response Time 10ms	Calibration	No need	Accuracy	%90
Power Supply Mode USB Supply Voltage DC 5V +/- 5% Average Current 400mA Response Time 10ms	Reporting Rate	Up to 450 fps	Glass Type	Anti Glared (AG), 4mm Tempered
Average Current 400mA Response Time 10ms	Frame Rate	up to 450 fps	Communication	USB 2.0
	Power Supply Mode	USB	Supply Voltage	DC 5V +/- 5%
Touch Accuracy +/-2mm (over 90% area) Touch Durability Unlimited	Average Current	400mA	Response Time	10ms
, (* * * * * * * * * * * * * * * * * * *	Touch Accuracy	+/-2mm (over 90% area)	Touch Durability	Unlimited
HID Compatibility Yes USB Object Sizes for Touch 5mm	HID Compatibility	Yes USB	Object Sizes for Touch	5mm

Mechanical

Product Dimensions (WxDxH)	1280 x 123 x 751 mm	Package Dimensions (WxDxH)	1480 x 265 x 930 mm
Product Weight	29.45 kg	Package Weight	38.15 kg
Vesa Mounting	400 x 200 mm	Bezel Width	B:34 T:34 L/R:34 mm

Environmental Conditions

Operating Temperature $+40^{\circ}\text{C} / 0^{\circ}\text{C}$ Operating Humidity 90%

Power

Power Supply 90% 110 VAC - 240 VAC



Power Consumption

Typical	138 W	Maximum	180 W
Deep Standby	≤0.5W		

Features

Main Features	USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up	Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance	Speaker	2 x 8 W

Accessory

QSG, IB, Power Cord, Remote
Control, RC Battery, Mounting Kit,
Extension Brackets, IR Extender
Cable

Certification

Safety	YES	EMC	YES
CE	YES	Reability Approval	YES



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660